Implementing DirectAccess with Windows Server 2016

Richard M. Hicks



Implementing DirectAccess with Windows Server 2016



Richard M. Hicks

Apress[®]

Implementing DirectAccess with Windows Server 2016

Richard M. Hicks Rancho Santa Margarita California, USA

ISBN-13 (pbk): 978-1-4842-2058-0 DOI 10.1007/978-1-4842-2059-7 ISBN-13 (electronic): 978-1-4842-2059-7

Library of Congress Control Number: 2016952413

Copyright © 2016 by Richard M. Hicks

This work is subject to copyright. All rights are reserved by the Publisher, whether the whole or part of the material is concerned, specifically the rights of translation, reprinting, reuse of illustrations, recitation, broadcasting, reproduction on microfilms or in any other physical way, and transmission or information storage and retrieval, electronic adaptation, computer software, or by similar or dissimilar methodology now known or hereafter developed. Exempted from this legal reservation are brief excerpts in connection with reviews or scholarly analysis or material supplied specifically for the purpose of being entered and executed on a computer system, for exclusive use by the purchaser of the work. Duplication of this publication or parts thereof is permitted only under the provisions of the Copyright Law of the Publisher's location, in its current version, and permission for use must always be obtained from Springer. Permissions for use may be obtained through RightsLink at the Copyright Clearance Center. Violations are liable to prosecution under the respective Copyright Law.

Trademarked names, logos, and images may appear in this book. Rather than use a trademark symbol with every occurrence of a trademarked name, logo, or image we use the names, logos, and images only in an editorial fashion and to the benefit of the trademark owner, with no intention of infringement of the trademark.

The use in this publication of trade names, trademarks, service marks, and similar terms, even if they are not identified as such, is not to be taken as an expression of opinion as to whether or not they are subject to proprietary rights.

While the advice and information in this book are believed to be true and accurate at the date of publication, neither the authors nor the editors nor the publisher can accept any legal responsibility for any errors or omissions that may be made. The publisher makes no warranty, express or implied, with respect to the material contained herein.

Managing Director: Welmoed Spahr Acquisitions Editor: Susan McDermott Developmental Editor: Laura Berendson Technical Reviewers: Jason Jones, Martin Solis Editorial Board: Steve Anglin, Pramila Balen, Laura Berendson, Aaron Black, Louise Corrigan, Jonathan Gennick, Robert Hutchinson, Celestin Suresh John, Nikhil Karkal, James Markham, Susan McDermott, Matthew Moodie, Natalie Pao, Gwenan Spearing Coordinating Editor: Rita Fernando Copy Editor: April Rondeau Compositor: SPi Global Indexer: SPi Global Cover image: Selected by Freepik

Distributed to the book trade worldwide by Springer Science+Business Media New York, 233 Spring Street, 6th Floor, New York, NY 10013. Phone 1-800-SPRINGER, fax (201) 348-4505, e-mail orders-ny@springer-sbm.com, or visit www.springer.com. Apress Media, LLC is a California LLC and the sole member (owner) is Springer Science + Business Media Finance Inc (SSBM Finance Inc). SSBM Finance Inc is a Delaware corporation.

For information on translations, please e-mail rights@apress.com, or visit www.apress.com.

Apress and friends of ED books may be purchased in bulk for academic, corporate, or promotional use. eBook versions and licenses are also available for most titles. For more information, reference our Special Bulk Sales-eBook Licensing web page at www.apress.com/bulk-sales.

Any source code or other supplementary materials referenced by the author in this text is available to readers at www.apress.com. For detailed information about how to locate your book's source code, go to www.apress.com/source-code/.

Printed on acid-free paper

To Anne, the love of my life and my best friend.

Contents at a Glance

About the Author	xix
About the Technical Reviewers	xxi
Acknowledgments	xxiii
Introduction	XXV
Chapter 1: DirectAccess Overview	1
Chapter 2: Plan for DirectAccess	9
Chapter 3: Install DirectAccess	21
Chapter 4: Configure DirectAccess with the Getting Started Wizard	45
Chapter 5: Configure DirectAccess with the Remote Access Setup Wizard	57
Chapter 6: Configure DirectAccess Load Balancing	83
Chapter 7: Configure DirectAccess Geographic Redundancy	103
Chapter 8: Enable Two-Factor Authentication	133
Chapter 9: Support Windows 7 Clients	159
Chapter 10: Monitor and Report	175
Chapter 11: Troubleshoot	195
Chapter 12: Migrate to Windows Server 2016 DirectAccess	231
Chapter 13: Managing Out	237

CONTENTS AT A GLANCE

Appendix A: DirectAccess with Native IPv6	251
Appendix B: DirectAccess and Force Tunneling	261
Appendix C: DirectAccess Security Hardening	267
Index	273

Contents

About the Author	xix
About the Technical Reviewers	xxi
Acknowledgments	xxiii
Introduction	xxv
Chanter 1: DirectAccess Averview	1
Soomloss and Transport	1
Di directionel	I
	۱
	2
IPV6	
IPv6 Transition Technologies	2
Outbound Management	2
Network Topology and IPv6 Transition Technologies	3
IPv6 Translation Components	3
Evolution of DirectAccess	
Forefront Unified Access Gateway	4
Forefront UAG Challenges	4
Windows Server 2012	4
Windows Server 2012 R2	4
Windows Server 2016	4
How DirectAccess Works	5
DirectAccess Supported Clients	5
••	

DirectAccess Security	6
Why DirectAccess?	7
DirectAccess vs. VPN	7
DirectAccess Limitations and Drawbacks	7
Choosing Between DirectAccess and VPN	8
Summary	8
Chapter 2: Plan for DirectAccess	9
DirectAccess Server	9
System Requirements	9
Domain Membership	9
Windows Firewall	
IPv6	
Redundancy	
Load Balancing	
Geographic Redundancy	
Network Topology	
Edge Firewall Configuration	
Network Topology Considerations	
DirectAccess Clients	14
Supported Clients	
Windows Firewall	
IPv6	
Connectivity Validation	
Active Directory	
Forest and Domain Functional Levels	
Read-Only Domain Controllers (RODC)	
Administrative Rights	
Security Groups	15
Group Policy Objects	15
Additional GPOs	

Certificates	
Computer Certificates	16
Certification Authority	16
Certificate Requirements	
SSL Certificates	
Network Location Server	
Web Server	17
SSL Certificate	17
DNS	
Internal	17
External	
Strong User Authentication	
Certificate Server	
RSA SecurID	
One-Time Passwords (OTP)	
Smart Cards	
Security Groups	
User Accounts	
Force Tunneling	
Manage Out	
ISATAP	
Supportability	19
Summary	
Chapter 3: Install DirectAccess	
DirectAccess Server	
Operating System Installation	
Single-NIC Configuration	21
Dual-NIC Configuration	
Join Domain and Apply Updates	
Third-Party Software	

Certificates	29
Installing the DirectAccess-VPN Role	
Configuring Additional Nodes	43
Summary	43
Chapter 4: Configure DirectAccess with the Getting Started Wizard	45
Before We Begin	45
Getting Started Wizard	45
Deployment Options	46
Installing DirectAccess	47
Review and Edit Settings	49
Confirm Policy Application	54
Limitations and Drawbacks	55
DirectAccess Client Targeting	55
Network Location Server	56
IP-HTTPS Certificate	56
Client Support	56
Deployment Flexibility	56
Summary	56
Chapter 5: Configure DirectAccess with the Remote Access Setup Wiz	ard 57
Remote Access Setup Wizard	57
Deployment Options	58
Installing DirectAccess	59
Step 1: Remote Clients	60
Step 2: Remote Access Server	64
Step 3: Infrastructure Servers	69
Confirm Policy Application	80
Step 4: Application Servers (Optional)	81
Summary	82

Chapter 6: Configure DirectAccess Load Balancing	83
Load Balancing	83
DirectAccess Load Balancing	83
Windows Network Load Balancing	
NLB Drawbacks	
External Load Balancer	84
Capacity Planning	85
Preparing for Load Balancing	85
Add NLB Feature	85
Hyper-V and NLB	
Enable Network Load Balancing (NLB)	89
VMware and NLB	94
Add DirectAccess Servers	
Enable External Load Balancer (ELB)	
VIP Assignment	
Load Balancer Configuration	
Summary	101
Chapter 7: Configure DirectAccess Geographic Redundancy	103
Client Support	103
Windows 8.x and Windows 10	
Windows 7	
Preparing for Multisite	104
DirectAccess Servers	104
Security Groups	
DNS	
IP-HTTPS Certificate	
Enable Multisite	105
Create the First Entry Point	105
Add Additional Entry Points	113
Enable Load Balancing for an Entry Point	

Multisite and GSLB	123
GSLB Deployment Scenarios	
GSLB Configuration	
Enable GSLB Post-Deployment	
GSLB Operation	
Summary	
Chapter 8: Enable Two-Factor Authentication	
Smart Cards	
Physical Smart Cards	
Virtual Smart Cards	
One-Time Passwords	
Supported OTP Solutions	
Prerequisites	
Client Authentication	
Certification Authority	
OTP and Force Tunneling	
Windows 7 Clients	
DirectAccess Configuration	
Enable Smart Card Authentication	
Configure DirectAccess	
Smart Card End User Experience	
Enable OTP Authentication	
Configure Certificate Templates	
Configure Certification Authority (CA)	
Configure RADIUS OTP	
Configure DirectAccess	
OTP End User Experience	
Deployment Considerations	
Increased Complexity	
Added Expense	

Limited Flexibility	157
Incomplete OTP Functionality	158
Reduced Scalability and Performance	158
Diminished User Experience	158
Summary	158
Chapter 9: Support Windows 7 Clients	
Deployment Considerations	
Multisite Support	159
Degraded Performance	
Reduced Scalability	
DirectAccess Connectivity Assistant (DCA) v2.0	160
Configuring DCA 2.0	
Deploy Group Policy Templates	
Create Group Policy Object	
Create WMI Filter	
Deploy Group Policy Object	
Installing DCA 2.0	
DCA Operation	
Connectivity Status	
Advanced Diagnostics	
Local DNS Resolution	
Summary	173
Chapter 10: Monitor and Report	
System Monitoring	175
Dashboard	
Operations Status	
User Monitoring	179
Remote Access Client Status	

Accounting	
Inbox Accounting	
RADIUS Accounting	
Reporting	187
Summary	193
Chapter 11: Troubleshoot	
DirectAccess Client Connection Process	195
Server and Client Configuration	
DirectAccess Server	
Group Policy	
Server Health	
Network Connectivity	199
Name Resolution	
Authentication	
Certificates	
IPv6	
Windows Firewall	
Services	204
Unsupported Configurations	
DirectAccess Client	205
Operating System SKU	
Group Policy	
Network Connectivity	
Domain Connectivity	
Certificates	
IPv6	
IPv6 Transition Technologies	
Services	212
Windows Firewall	212

Connection Security Rules	214
Ping Tunnel Endpoints	216
Ping Internal Servers	218
IPsec Connections	219
Name Resolution	
Helpful Tools and Commands	223
DirectAccess Connection Status	
DirectAccess Connectivity Assistant	
IPsec Auditing	
Firewall Logging	
Message Analyzer	
Nmap	
Tracing	
DirectAccess Client Troubleshooting Tool	
Summary	229
Chapter 12: Migrate to Windows Server 2016 DirectAccess	231
Requirements	231
IP Addresses	231
Public Hostname	
Public Hostname Security Groups	
Public Hostname Security Groups Group Policy Objects	
Public Hostname Security Groups Group Policy Objects	
Public Hostname Security Groups Group Policy Objects Configuration Client Migration	231 232 232 232 232 232
Public Hostname Security Groups Group Policy Objects Configuration Client Migration Additional Use Cases	231 232 232 232 232 234 234 235
Public Hostname Security Groups Group Policy Objects Configuration Client Migration Additional Use Cases QA and Testing	231 232 232 232 232 234 235 235
Public Hostname Security Groups Group Policy Objects Configuration Client Migration Additional Use Cases QA and Testing Delegated Administration	231 232 232 232 232 232 234 234 235 235 235
Public Hostname Security Groups Group Policy Objects Configuration Client Migration Additional Use Cases QA and Testing Delegated Administration Configuration Changes	231 232 232 232 232 234 234 235 235 235 235 235
Public Hostname Security Groups Group Policy Objects Configuration Client Migration Additional Use Cases QA and Testing Delegated Administration Configuration Changes Unique Client Requirements	231 232 232 232 232 232 234 235 235 235 235 235 235 235
Public Hostname Security Groups Group Policy Objects Configuration Client Migration Additional Use Cases QA and Testing Delegated Administration Configuration Changes Unique Client Requirements	231 232 232 232 232 234 234 235 235 235 235 235 235 235 235

Chapter 13: Managing Out	237
IPv6	
ISATAP	
Supportability	237
ISATAP Router	
ISATAP Client	
Manual Configuration	238
DNS	238
Group Policy	
Connectivity Testing	241
Remote Management	
DirectAccess Management Computers	
Windows Firewall	
GP0	
Additional Services	
Summary	
Appendix A: DirectAccess with Native IPv6	251
IPv6 Readiness	
Remote Access Setup Wizard	
Load Balancing	
Multisite	
Network Prefix Routing	
6to4	
Teredo	259
IP-HTTPS	
Native IPv6 HTTPS	
Managing Out	
Summary	

Appendix B: DirectAccess and Force Tunneling	
How It Works	
Use Cases	
Web-Browsing Policy	261
Network Bridging	261
Prerequisites	
Enable Force Tunneling	
Name Resolution Policy Table	263
Define Corporate Proxy	
Limitations and Drawbacks	
Poor Performance	264
Reduced Scalability	264
Web-Browsing Experience	265
Force Tunneling and OTP	
All or Nothing	
Summary	265
Appendix C: DirectAccess Security Hardening	
Security Best Practices	
IP-HTTPS Preauthentication	
Windows Firewall	
Considerations for ICMP	270
SSL/TLS	
Null Cipher Suites	271
Server Core	
Minimal Server Interface	
Summary	
Index	273

About the Author



Richard M. Hicks (MCP, MCSE, MCTS, MCITP:EA, MCSA, MVP) is a network and information security expert specializing in Microsoft technologies. As a Microsoft Cloud and Datacenter/Enterprise Security MVP, he has traveled around the world speaking to network engineers, security administrators, and IT professionals about Microsoft networking and security. Richard has nearly 20 years of experience working in large-scale corporate computing environments and has designed and deployed perimeter defense and secure remote access solutions for some of the largest companies in the world. Richard is Founder and Principal Consultant of Richard M. Hicks Consulting and focuses on helping organizations both large and small implement DirectAccess, VPN, and Cloud networking solutions on Microsoft platforms. Richard is a contributing author for TechGenix (WindowSecurity.com, WindowsNetworking.com, CloudComputingAdmin.com) and the Petri IT Knowledgebase. He has also produced video training courses for

Pluralsight. Richard is an avid fan of Major League Baseball and in particular the Los Angeles Angels (of Anaheim!). He also enjoys fish tacos, craft beer, and single malt Scotch whisky. He lives and works in beautiful, sunny Southern California. Keep up to date on all things DirectAccess by visiting his website at https://directaccess.richardhicks.com or follow him on Twitter @richardhicks.

About the Technical Reviewers



Martin J. Solis has worked at Microsoft for 21 years in various support teams and has been in the computer industry for over 30 years. As a PFE (Premier Field Engineer) at Microsoft, Martin supports large enterprise customers in the areas of DirectAccess, Active Directory, PKI, IPSec, ISA/TMG, and networking.



Jason Jones is a Principal Security Consultant for Microsoft Consulting Services (MCS) in the United Kingdom. He provides design, architectural, and technical consulting to Microsoft's customers and partners. His specialties include Microsoft Security, Identity and Access solutions with in-depth knowledge of Active Directory Certificate Services, DirectAccess, and Forefront edge security (TMG and UAG). Jason is a former Microsoft Most Valuable Professional (MVP).

Acknowledgments

On a technical note, this book would not have been possible without the contributions of the following individuals.

Jason Jones, my good friend and one of the technical reviewers of this book, has been an invaluable resource for me for DirectAccess. His deep technical expertise and broad deployment experience have been incredibly helpful for me over the years. We've had countless conversations and many late-night (for him!) email threads discussing the finer details of DirectAccess, and he's always made think more critically about the security aspects of the solution. Much of the content in this book is the direct or indirect result of my interactions with Jason. His contribution as technical reviewer has also served to make this a better book. I can't thank him enough for agreeing to work with me on this project. I hope we get the chance to work together again soon.

Ed Horley and Joe Davies each had a tremendous impact on the information in this book. Ed's book *Practical IPv6 for Windows Administrators* taught me a great deal about the intricacies of IPv6 in Windows, which is vital to the operation of DirectAccess. Ed has an immense working knowledge of and experience with the IPv6 protocol, and having the opportunity to work closely with Ed as one of the technical reviewers for his book was an invaluable learning experience. I consider Joe's book, *Understanding IPv6*, the bible for IPv6 in Windows. In addition, Joe's work on the *TCP/IP Protocols and Services* books for past releases of the Windows operating systems were foundational to my becoming closely involved with Windows networking and remote access. Thank you both for your continued commitment to IPv6 education and information sharing.

Martin Solis, another technical reviewer for this title, has been deeply influential on the outcome of this book. Martin is incredibly adept with DirectAccess troubleshooting, a topic that could fill an entire book of its own. His valuable insight and unique experience gained from implementing and supporting one of the largest DirectAccess deployments in the world has been enormously beneficial. Thank you so much for jumping into the middle of this project and agreeing to take on such a heavy workload, in spite of all your existing commitments. I am truly grateful for your efforts.

Michelle Lawson has had a profound influence on my technology writing. If any of this book is even remotely coherent, it is due in large part to her generosity and kindness in offering to review my work, often at a moment's notice. Without her efforts and mentoring, the outcome of this book might have been 300 pages of unintelligible drivel. Thank you for always being available to offer guidance and suggestions. They are always helpful and informative, and I appreciate it more than you know.

To my fellow MVPs, Shannon Fritz, Jordan Krause, and Benoit Sautiere, thanks for always engaging on the mailing list and making me consider new and different aspects of DirectAccess. To Benoit especially, your advocacy of DirectAccess and OTP, along with your documentation of OTP integration and troubleshooting, has been essential. And thanks also to Fredrik Johnsson, who has been exceedingly helpful with regard to all aspects of certificate authentication and Public Key Infrastructure (PKI).

Special thanks to current and former Microsoft product managers Scott Roberts, Bala Natarajan, Daniel Havey, and Mihai Peicu for always being open to engaging with me and answering my deep and sometimes unusual technical questions about DirectAccess.

On a personal note, there are some important people close to me without whose contributions this book would not have been possible.

ACKNOWLEDGMENTS

To my mom and dad, thank you for all the years of support and unconditional love. I would not be where I am today without you.

To my mother-in-law, Judy Pearce, thank you for believing in me and investing in me nearly 20 years ago. You are single-handedly responsible for launching my career as an IT professional. I am deeply indebted to you, always.

To Anne, my amazing wife and best friend of more than 30 years, thank you for your unending love and support. I am nothing without you. There are no words to describe how truly blessed I am to have you in my life. If I am successful in the least, it is because of you.

And finally, to my Lord and Savior Jesus Christ, thank you for the amazing gift of life.

Introduction

In today's world, organizations that support telecommuting for their employees have a distinct competitive advantage in the marketplace. The available talent pool they have to draw on is not restricted to a limited radius around physical office locations. This enables them to hire the best people and ensure they are always productive regardless of their location.

The security and management of field-based assets have always been a challenge for IT administrators. Ensuring that remote devices remain updated and secure is difficult when corporate network access is sporadic.

DirectAccess, a remote access technology included as part of the Unified Remote Access role in Windows Server 2016, provides seamless and transparent always-on remote network connectivity for managed (domain-joined) Windows clients.

It provides ubiquitous connectivity and access to internal applications and data, and does so without requiring any user interaction. The solution allows remote workers to access internal resources in the same familiar way, regardless of their physical location, resulting in a superior remote access experience and increased productivity.

DirectAccess client computers have consistent remote network access, enabling them to update group policy and check in with systems-management servers more consistently than traditional client-based VPN allows. DirectAccess connections are also bidirectional, allowing IT administrators to proactively manage their field-based assets just as they do their on-premise systems. The end result is having fully managed and secure mobile computers.

DirectAccess is built using commonly deployed Windows platform technologies like Active Directory Domain Services (AD DS) and Group Policy, Active Directory Certificate Services (AD CS), and IPsec. DirectAccess also relies heavily on IPv6. While it is true that there are a lot of moving parts with DirectAccess, many of these technologies are likely to be familiar to Windows administrators. Technologies such as PKI and IPv6 will be required skills in the near future, so implementing DirectAccess is an excellent opportunity to get some exposure and practical deployment experience with these technologies.

This book is not written to be a comprehensive technical reference for DirectAccess. The technologies that support DirectAccess are already well documented, so the goal for this book is to create a clear, concise, and applicable installation and configuration guide to help you install, configure, troubleshoot, and support DirectAccess itself. It provides practical, real-world guidance for implementing DirectAccess in the most reliable and secure way possible. It also includes valuable tips and tricks that I've learned from deploying DirectAccess on a daily basis for the last five years.

I sincerely hope you find this book helpful and informative. Enjoy!

CHAPTER 1

DirectAccess Overview

The Unified Remote Access Role in Windows Server 2016 includes several remote access technologies. This book will focus on one of them—DirectAccess. For many years, Virtual Private Networking (VPN) has been the de facto standard for providing secure remote access, and is likely familiar to most system administrators today. VPN use in Windows networks has been around for quite some time, with roots dating back to Windows NT 4.0. By comparison, DirectAccess is a relative newcomer. It was first introduced with Windows Server 2008 R2, and has since undergone subtle but vitally important changes in architecture and infrastructure. DirectAccess is a unique and compelling way to provide secure remote access for Windows devices managed by the IT department. It provides a superior user experience when compared to traditional, client-based VPN, and it allows IT administrators to better manage their remote Windows systems.

DirectAccess

In 2007, Microsoft chairman and software visionary Bill Gates outlined his vision for something he called "anywhere access." Mr. Gates envisioned a world where data and information, applications, resources, and content would be available instantly and easily, no matter where in the world the user happened to be. DirectAccess is the realization of that dream for businesses. Many IT professionals mistakenly believe that DirectAccess is just another VPN solution. While there are some similarities between the two technologies, both in terms of the underlying technology and the functionality, DirectAccess brings some significant improvements over its predecessor.

Seamless and Transparent

DirectAccess is a paradigm shift in the way corporate IT provides secure remote access. Unlike traditional VPN, which is user initiated, DirectAccess works at the machine level to provide seamless and transparent, always-on secure remote corporate network connectivity any time the computer has an active Internet connection. Because it requires no user interaction,¹ it streamlines and simplifies the remote access experience for the end user.

Bi-directional

DirectAccess is also bi-directional, which is a key differentiator between it and VPN. The bi-directional nature of DirectAccess enables some interesting new use cases for secure remote access. For example, an administrator on the corporate network can initiate a remote desktop connection to a remotely connected DirectAccess client for the purposes of troubleshooting or providing assistance. Configuration and software can be deployed to DirectAccess clients using System Center Configuration Manager (SCCM), and vulnerability scans can be performed remotely.

¹Unless strong user authentication is enabled

Not a Protocol

DirectAccess is not a protocol. It is a collection of Windows platform technologies that are assembled to provide secure remote access to on-premise data and applications for users who are located outside of the corporate network. DirectAccess relies on IPv6 for transport, IPsec for security, and Active Directory, Kerberos, and digital certificates for authentication. On the client side, DirectAccess leverages the Windows Firewall with Advanced Security (WFAS) and the Name Resolution Policy Table (NRPT).

IPv6

IPv6 is an integral part of the DirectAccess solution. In fact, DirectAccess communication takes place exclusively over IPv6. IPv6 was not commonly deployed, which was a significant challenge to the adoption of the DirectAccess technology. Early on, however, Microsoft introduced some new features to address this challenge, which included adding support for IPv6 transition technologies and translation components to enable DirectAccess clients to communicate with intranet hosts configured only with IPv4.

IPv6 Transition Technologies

Most commonly, the DirectAccess server and clients will be connected to the IPv4 public Internet. Since DirectAccess uses IPv6 exclusively for client-to-server communication, DirectAccess leverages IPv6 transition technologies to tunnel IPv6 packets over the IPv4 Internet. When the DirectAccess client is outside of the corporate network, it will choose one of three IPv6 transition technologies. They are:

- **6to4** the client chooses 6to4 when it has a public IPv4 address assigned to its network interface. 6to4 tunnels IPv6 packets over IPv4 using IP protocol 41. 6to4 does not work when the DirectAccess server or client are located behind a network device performing Network Address Translation (NAT).
- **Teredo** the client chooses Teredo when it has a private IPv4 address assigned to its network interface, or when 6to4 is not available for use. Teredo is designed to work when the client (but not the server) is behind a NAT device. Teredo tunnels IPv6 packets over IPv4 using UDP port 3544. To support Teredo, the DirectAccess server must have two *consecutive* public IPv4 addresses assigned to its external network interface. In addition, Teredo requires that ICMPv4 and ICMPv6 echo requests be allowed to all Intranet hosts.
- **IP-HTTPS** the client chooses IP-HTTPS when it has a private IPv4 address assigned to its network interface and 6to4 or Teredo are not available. IP-HTTPS is supported when the DirectAccess client and/or the DirectAccess server is behind a NAT device. IP-HTTPS tunnels IPv6 packets over IPv4 using HTTP with SSL/TLS over TCP port 443. When supporting Windows 7 clients, performance and scalability can suffer because IPsec-encrypted traffic is encrypted again with SSL/TLS. This double encryption adds significant protocol overhead and places high demands on the CPU. Microsoft introduced support for null encryption beginning with Windows 8, which eliminates the double encryption and provides comparable performance to that of 6to4 and Teredo.

Outbound Management

The Intrasite Automatic Tunnel Addressing Protocol (ISATAP) is an IPv6 transition technology that is used for initiating outbound communication from the internal network to connected DirectAccess clients. It is recommended that if outbound management to DirectAccess clients is required then native IPv6 be deployed. Deploying IPv6 is not trivial though, so ISATAP can provide a simple and effective alternative to a full IPv6 deployment. The use of ISATAP for outbound management is only supported for single-server DirectAccess deployments.

Network Topology and IPv6 Transition Technologies

The DirectAccess server must have two network interfaces with a public IPv4 address assigned to the external network adapter to support the 6to4 protocol. Two *consecutive* public IPv4 addresses are required to support Teredo. If the DirectAccess server is configured with private IPv4 addresses in a perimeter or DMZ deployment with one or two network adapters, only the IP-HTTPS protocol is supported.

IPv6 Translation Components

IPv6 transition technologies allow the DirectAccess client to communicate with the DirectAccess server over the public IPv4 Internet. IPv6 *translation* components enable the client (which uses IPv6 exclusively) to communicate with intranet hosts that are only configured with IPv4. The following IPv6 translation technologies are automatically installed when DirectAccess is configured.

- **DNS64** The DNS64 service (pronounced "DNS six-to-four") runs on the DirectAccess server that is functioning as a DNS proxy and translator for DirectAccess clients. DirectAccess clients send all name-resolution requests for the internal corporate namespace to this service. The DNS64 service receives DNS AAAA (quad-a) name-resolution requests from DirectAccess clients for internal hostnames. The DNS64 service makes another request to internal corporate DNS servers for the same name, usually receiving an A resources record back with an IPv4 address. It then converts this IPv4 address into an IPv6 address for the DirectAccess client to use.
- **NAT64** The NAT64 service (pronounced "NAT six-to-four") runs on the DirectAccess server that is functioning as an IPv6-to-IPv4 translator for DirectAccess clients. NAT64 receives inbound IPv6 packets from DirectAccess clients, translates them to IPv4, and forwards them to the IPv4 address on the internal network.

While it is not necessary to understand IPv6 to implement DirectAccess, a working knowledge of IPv6 will most certainly be required to perform any troubleshooting should the need arise.

Note I realize that the reliance on IPv6 for DirectAccess can strike fear in the heart of an IT administrator. Don't let that prevent you from taking advantage of this amazing technology! There was a time when we all had to learn IPv4, and so it is with IPv6. The world is moving to IPv6, so having this important skill in your tool belt will only help in the future. DirectAccess provides a practical application for the use of IPv6 and is an excellent way to begin developing a working knowledge of this important protocol. To learn more about IPv6, I encourage you to read Ed Horley's excellent book *Practical IPv6 for Windows Administrators* (Apress, 2013; ISBN: 978-1-4302-6370-8).

Evolution of DirectAccess

DirectAccess was first introduced as a feature of the Microsoft Windows network operating system in Windows Server 2008 R2. The original release required that IPv6 be deployed on the corporate intranet, which was a significant barrier to adoption. The deployment of IPv6 in general has been slow, and the adoption of IPv6 on private corporate networks is still in its infancy.

Implementing IPv6 is non-trivial, and takes a substantial investment of time and effort to effectively deploy it. Many organizations were unwilling to deploy IPv6 just to support DirectAccess. As such, DirectAccess in Windows Server 2008 R2 was not widely deployed.

Forefront Unified Access Gateway

Microsoft introduced Forefront Unified Access Gateway (UAG) 2010 in December of 2009. Forefront UAG was a remote access gateway that included support for SSL VPN, traditional client-based VPN, web application publishing, and much more. It also included new technologies designed to ease the transition to DirectAccess. Forefront UAG added the DNS64 and NAT64 services that translate IPv6 communications from DirectAccess clients to IPv4. Together, these two technologies eliminated the need to deploy IPv6 on the corporate network just to support DirectAccess, thus improving adoption rates.

Forefront UAG Challenges

While Forefront UAG 2010 eased some of the challenges of deploying DirectAccess, it also introduced its own unique set of challenges. Forefront UAG was itself difficult to implement and support, as it had steep hardware requirements, limited local redundancy, and no native support for geographic redundancy. In addition, Forefront UAG had its own licensing requirements, making the solution more expensive. Furthermore, it had only one supported network deployment model—edge facing. The Forefront UAG 2010 server had to be deployed with public IPv4 addresses to enable the DirectAccess role. The prospect of placing a domain-joined Windows server directly on the public Internet didn't sit well with many, even though Forefront UAG 2010 was capably protected by the Forefront Threat Management Gateway (TMG) enterprise-class firewall that was included.

Windows Server 2012

To address the shortcomings and limitations associated with both Windows Server 2008 R2 and Forefront UAG 2010 DirectAccess, Microsoft integrated the DNS64 and NAT64 IPv6 translation technologies into the core operating system in Windows Server 2012 enabling the deployment of DirectAccess without the need to deploy additional software. In addition, Microsoft added much-needed scalability and performance improvements, including native support for load balancing (integrated and external), geographic redundancy (multisite), and improvements to key IPv6 transition technologies. More important, Microsoft introduced flexible network placement with support for deploying the DirectAccess server in a perimeter or DMZ network behind a NAT device, and even support for a single Network Interface Card (NIC) deployment. Additionally, Microsoft added support for multiple domains and removed the requirement to deploy a Public Key Infrastructure (PKI) in some scenarios.

Windows Server 2012 R2

With the introduction of Windows Server 2012 R2, Microsoft did not make any significant changes to the core functionality of DirectAccess. However, they did make many subtle enhancements aimed toward improving security, reliability, and performance. This release mostly included updates that were available as hotfixes in Windows Server 2012 to address a variety of issues, including problems with one-time password (OTP) authentication, load-balancing configuration, and more.

Windows Server 2016

Once again, DirectAccess in Windows Server 2016 remains essentially unchanged from the version in Windows Server 2012 R2. The only significant change is the removal of support for Microsoft Windows Network Access Protection (NAP) integration, as this feature was formally deprecated in Windows Server 2012 R2 and has been removed with Windows 10 and Windows Server 2016.

There are no new features or functionality in this latest release. From a technology perspective, DirectAccess is mature, and since the release of the Windows 10 client operating system, it is now being deployed rapidly. Organizations large and small have adopted the technology, and those early adopters who deployed DirectAccess with Windows Server 2008 R2 and Forefront UAG 2010 are now migrating to DirectAccess with Windows Server 2016.

How DirectAccess Works

When a client provisioned for DirectAccess is outside of the corporate network, it will automatically attempt to establish a secure remote connection to the DirectAccess server over the Internet. The DirectAccess connection takes place at the machine level and requires no user interaction.² Most commonly, the DirectAccess client will be on the IPv4 Internet, so an IPv6 transition technology will be selected and a tunnel will be established with the DirectAccess server. Inside the IPv6 transition tunnel, authenticated and encrypted IPsec tunnels are established between the client and the server. It is over these tunnels that communication to resources on the corporate network takes place. The DirectAccess IPsec tunnels are defined as Connection Security Rules (CSR) in the Windows Firewall with Advanced Security on both the DirectAccess client and the server.

DirectAccess Supported Clients

DirectAccess is designed specifically for managed (domain-joined) Windows clients. It is primarily aimed at large enterprise organizations, as it requires the Enterprise edition of the Windows desktop client operating system. However, small and mid-sized organizations can still take advantage of DirectAccess as long as they meet the implementation requirements. The following is a list of supported Windows desktop client operating systems:

- Windows 10 Enterprise
- Windows 10 Education
- Windows 8.x Enterprise
- Windows 7 Enterprise
- Windows 7 Ultimate

Additionally, the following Windows Server operating systems are also supported as DirectAccess clients:

- Windows Server 2016
- Windows Server 2012 R2
- Windows Server 2012
- Windows Server 2008 R2

Any non-Enterprise editions (other than Windows 10 Education and Windows 7 Ultimate) or any other previous Windows desktop client or server operating systems (for example, Windows 10 Professional, Windows 7 Home Edition, or Windows Server 2008) are not supported.

²Unless strong user authentication is enabled

DirectAccess Security

DirectAccess IPsec tunnels use Authenticated IP (AuthIP³) and are authenticated using a combination of digital certificates, NTLM, and Kerberos. Both the computer and the user are authenticated separately. DirectAccess provides a high level of assurance that remotely connected devices and users are indeed legitimate.

In a typical configuration, two distinct IPsec tunnels are established—an infrastructure tunnel and an intranet tunnel.

- Infrastructure tunnel Provides secure remote network access to limited internal resources. Specifically, only infrastructure services such as domain controllers and systems-management servers are available over this first tunnel. The infrastructure tunnel requires two forms of authentication. First, the client machine is authenticated using a computer certificate issued by the corporate PKI. Second, the client machine's computer account is authenticated against Active Directory using NTLM. If the client successfully passes both authentication steps, the infrastructure tunnel is established and the client can access infrastructure resources defined by the remote access policy. This tunnel uses 192-bit AES encryption and SHA-1 for integrity.
- **Intranet tunnel** Provides the end user with full access to the corporate network. It is initiated when the user logs on to the DirectAccess client. The intranet tunnel also requires two forms of authentication. First, the computer is authenticated once again using the computer certificate issued by the corporate PKI. Second, the user account is authenticated against Active Directory using Kerberos. If the client successfully passes both authentication steps, the intranet IPsec tunnel is established. Like the infrastructure tunnel, this IPsec tunnel uses 192-bit AES encryption and SHA-1 for integrity.

The supporting infrastructure requirements make DirectAccess inherently more resistant to unauthorized access. For attackers to compromise a DirectAccess connection, they would require a computer that is a member of the organization's Active Directory domain, and the computer account would need to belong to the defined DirectAccess security group. In addition, a computer certificate issued by the company's internal PKI is required. The attacker would also need valid user credentials to access corporate resources.

An unauthorized user cannot gain full access to internal resources from just any machine. For an attacker to successfully spoof both an AD computer account and a computer certificate is extremely difficult. If successful, the attacker has likely already compromised the target organization.

Note The default configuration of the IP-HTTPS IPv6 transition technology in DirectAccess may allow an unauthorized user to obtain an IPv6 address on the DirectAccess client network. Once this happens, the attacker can launch IPv6-related Denial-of-Service (DoS) attacks and potentially perform network reconnaissance. It is possible to mitigate these challenges using a custom configuration. More details can be found here: https://directaccess.richardhicks.com/2016/05/10/directaccess-ip-https-preauthentication-using-citrix-netscaler/.

³https://technet.microsoft.com/en-us/magazine/2007.10.cableguy.aspx

Why DirectAccess?

DirectAccess was designed to meet two very common and specific needs of many organizations. The first was to provide an easy-to-use, secure remote access solution. The second was to provide a better way to manage field-based Windows devices.

The DirectAccess user experience is incredibly simple. Compared to VPN, it is infinitely easier to use. From the user's perspective, resources on the corporate network are accessed in the same way, regardless of where they themselves are located. Mapped drives and shortcuts to files and applications work the same outside of the network as they do inside.

DirectAccess clients are always managed too. Because DirectAccess clients are securely connected to the corporate network whenever they have an active Internet connection, IT administrators can more effectively manage and monitor their remote Windows devices. DirectAccess clients update group policy on a regular basis and report to systems management servers much more frequently. The client's configuration and security posture are maintained, and compliance can be verified with existing management platforms.

DirectAccess connectivity is bi-directional, enabling administrators who are on-premise to initiate outbound communication to remote-connected clients. This enables help desk administrators to use Remote Desktop or Remote Assistance to provide assistance for users. In addition, security auditors can perform vulnerability scans on clients, and any software deployment mechanisms that use push technology will also continue to work when Windows devices are out of the office.

DirectAccess vs. VPN

VPN connections are user initiated and therefore optional. It is up to the user to decide when they want to connect to the corporate network. By comparison, DirectAccess is seamless and transparent in nature, is completely automatic, and requires no user interaction to establish a connection.

Many VPN protocols aren't firewall friendly, which can impede the successful establishment of a VPN connection. DirectAccess can establish its secure remote connection using HTTPS, which is commonly allowed through most firewalls.

VPNs often require investments in proprietary hardware and per-user licensing. DirectAccess can be deployed on existing virtual infrastructure and does not require additional user licensing.

Proprietary software is commonly required to leverage all of the features provided by VPN solutions. This software must be deployed and managed by IT administrators. DirectAccess requires no additional third-party software to be installed. All settings for DirectAccess are managed through Group Policy Objects (GPOs) in Active Directory.

A VPN connection can be established from any client machine with the VPN client software installed. This makes integration with a multifactor authentication solution an essential requirement, which makes the solution more complex and difficult to support. A DirectAccess connection can only be established from a client computer that has been provisioned for DirectAccess by IT, reducing the need to employ strong authentication for DirectAccess connections.

DirectAccess Limitations and Drawbacks

As capable as DirectAccess is, it is not a comprehensive remote access solution. It is designed for managed (domain-joined) Windows clients *only*. DirectAccess does not work with non-Enterprise versions of Windows (with the exception of Windows 10 Education and Windows 7 Ultimate), Windows RT, or Windows Phone mobile operating systems. It also does not work with any non-Microsoft operating systems.

As DirectAccess relies exclusively on IPv6 for client-to-server communication, there are some instances in which certain applications may not be compatible with DirectAccess. For example, applications that use protocols that have IPv4 addresses embedded in them (such as SIP and FTP) or applications that make calls directly to IPv4 addresses will not work with DirectAccess.

Choosing Between DirectAccess and VPN

You might be asking yourself, "Should I implement DirectAccess or VPN?" Actually, you can implement both. After all, DirectAccess and VPN aren't mutually exclusive. They are, in fact, quite complementary. DirectAccess can be used to provide secure remote access and enhanced management for Windows laptops managed by IT, while VPN can be deployed for non-managed devices. While you may not be able to entirely eliminate VPN with DirectAccess, it will certainly allow you to decrease the number of VPN licenses required and reduce your investment in proprietary hardware, management tools, and dedicated administrators, all of which translates into reduced capital investment and operational costs.

Summary

DirectAccess is a paradigm shift in the way secure remote access is provided for computers managed by the IT department. Unlike traditional client-based VPN, DirectAccess is seamless and transparent, always on, and bi-directional. It leverages existing, commonly deployed Windows platform technologies that are mature and well understood. DirectAccess essentially works by establishing secure, authenticated IPsec tunnels between the DirectAccess client and DirectAccess server. DirectAccess works with all Enterprise editions of Windows 7, 8, and 10, in addition to a few other selected SKUs. It provides a secure remote corporate network connection with a high level of assurance for provisioned clients. DirectAccess can be used to address the unique challenges of IT administrators tasked with managing field-based assets. DirectAccess isn't a comprehensive remote access technology, and may not completely eliminate the need for VPN, but it has the potential to significantly reduce an organization's dependence on it. Ultimately, the choice between DirectAccess and VPN isn't an either/or one. In fact, the two technologies are complementary and serve to address the unique and specific remote access needs of different users and device types.

CHAPTER 2

Plan for DirectAccess

Planning is by far the most important aspect of a DirectAccess deployment project. DirectAccess can be deployed in many different configurations to meet a variety of implementation requirements. Many design decisions and deployment options have implications for security, scalability, performance, client support, and general supportability. There are scenarios in which features are mutually exclusive. Some implementation models may limit future deployment flexibility or prevent additional security features from being enabled. A clear understanding of the implementation goals will help the architect design a solution that is reliable, secure, flexible, and supportable.

DirectAccess Server

DirectAccess can be installed and configured on Windows Server 2016 Datacenter, Standard, and Essentials SKUs. DirectAccess should be configured on a server dedicated to this workload. It should not be collocated with other workloads, such as Active Directory Domain Services (AD DS), Active Directory Certificate Services (AD CS), SQL, Exchange, and so forth. Although remote access roles such as VPN and Web Application Proxy (WAP) can be collocated with DirectAccess in some scenarios,¹ implementation best practices dictate that they be installed on separate servers. Crucially, collocating VPN or WAP on the DirectAccess server will also result in the loss of support for IP-HTTPS null encryption, which reduces performance and scalability for Windows 8.x and Windows 10 clients.

System Requirements

Windows Server 2016 and DirectAccess should be installed on a dedicated physical server for optimum performance. However, Windows Server 2016 and DirectAccess can be installed on a virtual machine hosted on any Microsoft Server Virtualization Validation Program (SVVP) validated hypervisor, including Microsoft Hyper-V, VMware, and many others. It is recommended that the server (physical or virtual) be provisioned with a minimum of four processor cores, 8GB of RAM, and 60GB of hard disk space.

Domain Membership

The DirectAccess server must be joined to an Active Directory Domain Services (AD DS) domain.² The DirectAccess server receives configuration settings from Active Directory group policies. In addition, IPsec tunnels used by DirectAccess are authenticated via Active Directory.

¹The Web Application Proxy (WAP) is only supported on the DirectAccess server in single-server deployments. Additional information can be found here: https://technet.microsoft.com/en-us/library/dn451298.aspx ²Azure Active Directory (AAD) is not supported for use with DirectAccess.

The DirectAccess server can be joined to any domain in the forest. There is no requirement for the DirectAccess server to be joined to the same domain as the DirectAccess clients. If DirectAccess servers or clients are members of different forests, there must exist a full two-way transitive trust between the forests.

Windows Firewall

The Windows Firewall with Advanced Security (WFAS) is a critical component for DirectAccess. Fundamentally, DirectAccess IPsec tunnels are defined as Connection Security Rules (CSRs) in the Windows Firewall. Therefore, proper DirectAccess operation requires the Windows Firewall to be enabled for all profiles. The Windows Firewall must not be disabled on the DirectAccess server.

Third-party firewalls can be installed on the DirectAccess server, but they are not recommended. Many third-party firewalls interfere with DirectAccess operation. If a third-party firewall is required on the DirectAccess server, the Windows Firewall must remain enabled. Also, it is a good idea to consult the thirdparty vendor for specific configuration guidance for DirectAccess.³

IPv6

Communication between the DirectAccess client and server takes place exclusively over IPv6. IPv6 transition technologies included with DirectAccess eliminate the need to place the DirectAccess server on the IPv6 Internet or to deploy IPv6 on the corporate LAN.

Occasionally IPv6 is disabled via the Windows registry.⁴ Although IPv6 does not have to be explicitly configured and deployed, it must not be proactively disabled in the registry on DirectAccess servers and clients. Doing so will break DirectAccess functionality.

Redundancy

Eliminating critical single points of failure in the DirectAccess architecture is essential to ensuring reliable connectivity. High availability can be configured with DirectAccess, both locally and geographically. The following topics describe load-balancing requirements and redundancy considerations.

Load Balancing

DirectAccess supports two types of local load balancing: integrated Windows Network Load Balancing (NLB) and external load balancers (ELB). For optimum performance, a physical external load balancing appliance is preferred. For small to mid-size deployments, a virtual external load balancer or NLB can be implemented.

Virtual IP Addressing

A virtual IP address (VIP) is assigned to the DirectAccess cluster when load balancing is enabled. VIP addressing requirements differ depending on the type of load balancer used. The following describes the VIP requirements for NLB and ELB:

- NLB
 - Each DirectAccess cluster requires a VIP.

³https://technet.microsoft.com/en-us/library/ee382257(v=ws.10).aspx

⁴Disabling IPv6 via the registry will prevent DirectAccess from working. More information about enabling and disabling IPv6 in Windows can be found here: https://support.microsoft.com/en-us/kb/929852
- The VIP must be on the same IP subnet as the dedicated IP addresses of the DirectAccess servers.
- DirectAccess servers with two Network Interface Cards (NICs) must be configured with a VIP for each interface.
- The dedicated IP address of the first cluster member becomes the VIP. A new dedicated IP address must be assigned to the DirectAccess server.
- If consecutive dedicated IP address assignments for DirectAccess servers are desired, plan to assign the IP address for the VIP to the first DirectAccess server during initial configuration.
- ELB
 - The VIP does not have to be on the same IP subnet as the DirectAccess servers.
 - The dedicated IP address of the first cluster member becomes the VIP. A new dedicated IP address must be assigned to the DirectAccess server.
 - If consecutive dedicated IP address assignments for DirectAccess servers are desired, plan to assign the IP address for the VIP to the first DirectAccess server during initial configuration.

Note When an external load balancer is configured, it is recommended that the 6to4 and Teredo IPv6 transition technologies be disabled for DirectAccess clients and the load balancer be configured for IP-HTTPS exclusively.

Geographic Redundancy

Only Windows 8.x and later clients provide full support for geographic redundancy with automatic site selection and transparent failover. Windows 7 clients are supported in multisite deployments, but must be assigned to a single entry point. They always connect to their assigned entry point regardless of physical location and do not automatically fail over. To further enhance geographic redundancy for Windows 8.x and later clients, a Global Server Load Balancing (GSLB) solution can be used.

Network Topology

DirectAccess supports flexible network configuration and can be deployed in one of three topologies: Edge facing, Perimeter/DMZ, or LAN.

Edge Facing

The DirectAccess server must be configured with two Network Interface Cards (NICs). In addition, the following requirements must be met:

- External NIC
 - Requires at least one public IPv4 address
 - Two consecutive public IPv4 addresses are required for Teredo support

- Internal NIC
 - Requires one private IPv4 address
 - Can be located in a perimeter/DMZ network or on the LAN
 - If configured in perimeter/DMZ, it is recommended that all protocols/ports from the DirectAccess server(s) to the LAN be allowed
 - Static routes must be configured for all remote internal IP subnets

Perimeter/DMZ

The DirectAccess server can be configured with one or two NICs. In addition, the following requirements must be met:

- External NIC (behind transparent firewall)
 - Requires at least one public IPv4 address
 - Teredo support requires two consecutive public IPv4 addresses
- External NIC (behind edge firewall performing Network Address Translation [NAT])
 - Requires one private IPv4 address
- Internal NIC
 - Can be located in a perimeter/DMZ network or on the LAN
 - If configured in perimeter/DMZ, all protocols/ports from the DirectAccess server(s) to the LAN should be allowed
 - Static routes must be configured for all remote internal IP subnets
- Single NIC
 - Requires one private IPv4 address
 - All protocols/ports from the DirectAccess server(s) to the LAN should be allowed

LAN

The DirectAccess server only requires a single NIC configured with one private IPv4 address.

Edge Firewall Configuration

The topics covered in the following sections describe the firewall requirements for deployment topologies.

Edge Facing

Edge firewall rules are not applicable if the DirectAccess server is connected directly to the IPv4 public Internet. If the DirectAccess server is located behind a transparent (layer 2) firewall, it should be configured to allow the following protocols and ports inbound and outbound:

IP protocol 41

- UDP port 3544
- TCP port 443

If the DirectAccess server is configured with a globally routable IPv6 address, it should be configured to allow the following protocols and ports inbound and outbound as well:

- IP protocol 41
- UDP port 500

Perimeter/DMZ

If the perimeter/DMZ network is publicly routable, the edge firewall should be configured to allow the following protocols and ports inbound and outbound:

- IP protocol 41
- UDP port 3544
- TCP port 443

If the DirectAccess server is configured with a globally routable IPv6 address, it should be configured to allow the following protocols and ports inbound and outbound as well:

- IP protocol 41
- UDP port 500

Perimeter/DMZ (NAT)

If the perimeter/DMZ network is located behind an edge firewall performing NAT, the edge firewall should be configured to allow the following protocols and ports inbound and outbound:

- TCP port 443
- NAT rule translating traffic from the public IPv4 address to the IPv4 address assigned to the external interface of the DirectAccess server

LAN

If the DirectAccess server is located on the LAN, the edge firewall should be configured to allow the following protocols and ports inbound and outbound:

- TCP port 443
- NAT rule translating traffic from the public IPv4 address to the DirectAccess server

Network Topology Considerations

Choosing which network topology to deploy DirectAccess with is based primarily on the existing network infrastructure. However, there are important security considerations to be made. An edge-facing deployment provides the greatest flexibility and widest IPv6 transition technology support. However, unless the DirectAccess server is protected with another firewall, this introduces some potential risk. The DirectAccess server must be joined to the domain, and having a domain-joined Windows server connected directly to an untrusted network (the public Internet) presents some risks. Here, the DirectAccess server is protected only with the Windows

Firewall. The Windows Firewall is a very capable host-based firewall, but it provides only a single layer of defense. Security best practices dictate that security should be performed in layers, making the deployment of the DirectAccess server behind an edge firewall an inherently more secure configuration.

Placing the DirectAccess server behind an edge firewall in transparent mode, or placing it in a publicly routable perimeter/DMZ network, is the preferred network topology. However, it is most common that perimeter/DMZ networks are not routable and use private, RFC1918⁵ IPv4-based addressing. In these scenarios, the edge firewall also performs NAT. IP-HTTPS is the only IPv6 transition technology supported in this scenario. When supporting Windows 7 clients, scalability and performance are sacrificed at the expense of additional security. Windows 8.x and Windows 10 clients do not suffer from this limitation, as they support null encryption for IP-HTTPS.

DirectAccess Clients

DirectAccess clients must be joined to a domain. Ideally, they should be joined to the same domain as the DirectAccess server, but they can be joined to any domain in any forest that has a full two-way trust with the domain where the DirectAccess server(s) are joined.

Supported Clients

DirectAccess clients must be provisioned using one of the following Windows desktop client operating systems SKUs:

- Windows 10 Enterprise Edition
- Windows 10 Education Edition
- Windows 8.x Enterprise Edition
- Windows 7 Enterprise Edition
- Windows 7 Ultimate Edition

Additionally, the following Windows Server operating systems are also supported as DirectAccess clients:

- Windows Server 2016
- Windows Server 2012 R2
- Windows Server 2012
- Windows Server 2008 R2

Windows Firewall

The Windows Firewall must be enabled for the Public and Private profiles. Third-party firewalls are supported, but the Windows Firewall must still be enabled. In addition, third-party firewalls must not interfere with DirectAccess operation. Consult with the vendor for guidance on proper configuration for DirectAccess.

IPv6

IPv6 must be enabled on all DirectAccess clients. The IP-HTTPS IPv6 transition technology must also be enabled. Other IPv6 transition technologies (6to4, Teredo, and ISATAP) can be enabled or disabled per individual deployment requirements.

^shttps://tools.ietf.org/html/rfc1918

Connectivity Validation

The Network Connectivity Assistant (NCA), included in the Windows 8.x and Windows 10 client operating systems, validates remote corporate network connectivity via the DirectAccess connection. Windows 7 clients can be configured with the optional DirectAccess Connectivity Assistant (DCA) v2.0, which provides similar functionality to the NCA. DCA 2.0 deployment can be automated with settings managed through Group Policy. DCA 2.0 must be installed on Windows 7 clients when the deployment is configured to use One-Time Password (OTP) authentication.

Active Directory

The topics in the following sections describe Active Directory requirements and configuration for DirectAccess.

Forest and Domain Functional Levels

Any supported forest or domain functional level is acceptable as long as DFS-R is used for the distribution of Group Policy objects (SYSVOL replication). If SYSVOL replication uses the File Replication Service (FRS), DirectAccess is not supported.⁶

Read-Only Domain Controllers (RODC)

RODCs are not supported. DirectAccess servers must have access to a writeable domain controller.⁷

Administrative Rights

Deployments are most functional when the DirectAccess administrator is a member of the Domain Admins security group in Active Directory. If not feasible, then the minimum requirement is to grant the DirectAccess administrator full access to DirectAccess Group Policy Objects (GPOs). The DirectAccess administrator must have local administrator rights on any DirectAccess server(s).

Security Groups

DirectAccess requires at least one Active Directory security group. To support Windows 7 clients in a multisite deployment, each entry point in the organization requires an additional security group.

Group Policy Objects

GPOs are created in Active Directory during initial DirectAccess configuration. If the DirectAccess administrator is not a member of the Domain Admins group or does not have permission to create GPOs, GPOs must be preconfigured with full control permissions delegated to the DirectAccess administrator. For single-domain, single-site DirectAccess deployments, two GPOs will be required—one for DirectAccess Server Settings and another for DirectAccess Client Settings. For multisite deployments where Windows 7 support is required, an additional GPO per entry point for Windows 7 DirectAccess clients will be required. Multidomain deployments will require additional GPOs.

[%]https://technet.microsoft.com/en-us/library/dn464274.aspx#bkmk_frs

⁷https://technet.microsoft.com/en-us/library/dn464274.aspx#bkmk_rodc

Additional GPOs

Additional GPOs may be required to deploy the Windows 7 DirectAccess Connectivity Assistant (DCA), optional client configuration settings, optimizations, and automated client provisioning.

Certificates

The DirectAccess server requires two different types of certificates. A computer (machine) certificate is required for IPsec authentication (in some scenarios), and an SSL certificate is required for the IP-HTTPS IPv6 transition technology. The following topics describe certificate requirements and configuration for DirectAccess.

Computer Certificates

While computer certificate authentication is optional for some DirectAccess deployment scenarios, enabling any of the following features will require computer certificate authentication for DirectAccess clients:

- Windows 7 client support
- Load balancing (integrated or external)
- Multisite deployment
- Strong user authentication (OTP, smart card)
- Force tunneling

Certification Authority

Computer certificate authentication should be enabled for all implementations so as to provide the best security and greatest configuration flexibility. Computer certificates must be issued to the DirectAccess server(s) and each DirectAccess client by an internal private certificate authority (CA). The DirectAccess server(s) and clients must trust the internal CA. For best results, a Microsoft Enterprise CA is recommended.

Certificate Requirements

Computer certificates issued to the DirectAccess server and clients must include a subject name that matches the hostname of the computer they are being issued to. The certificate must also include the Client Authentication (1.3.6.1.5.5.7.3.2) Enhanced Key Usage (EKU) Object Identifier (OID).

SSL Certificates

The IP-HTTPS IPv6 transition technology requires an SSL certificate for authentication and encryption. Best practice is to obtain the SSL certificate from a publicly trusted third-party CA. However, an SSL certificate can be issued from the internal PKI. If Windows 7 clients are supported, the Certificate Revocation List (CRL) must be externally accessible.

For multisite deployments, a wildcard certificate may be used. If a wildcard certificate is not feasible, a unique certificate for each entry point is required. Multi-SAN certificates are not supported.⁸

^{*}https://directaccess.richardhicks.com/2016/03/28/directaccess-and-multi-san-sslcertificates-for-ip-https/

Network Location Server

The Network Location Server (NLS) is a critical infrastructure component in a DirectAccess deployment that allows clients to determine whether they are inside or outside of the corporate network. The following topics describe the requirements for the NLS.

Web Server

Any web server can be used for the NLS, including IIS, Apache, Nginx, and others. An Application Delivery Controller (ADC) can also be configured to serve as the NLS. Ideally, the server should be dedicated to the NLS role and should be made highly available. For large deployments where the internal network spans many physical locations and geographies, additional steps should be taken to ensure NLS availability in all locations.⁹ Existing web application servers like Exchange OWA, SharePoint, and so on should not be used as the NLS.

SSL Certificate

The NLS requires an SSL certificate issued by a CA trusted by DirectAccess clients and servers. It is not necessary to use a public SSL certificate on the NLS; the certificate can be issued by the internal private PKI. The certificate requires a subject name that matches the NLS fully-qualified domain name (FQDN) defined in the DirectAccess configuration (for example, nls.corp.example.com). In addition, the certificate must also include the Server Authentication (1.3.6.1.5.5.7.3.1) Enhanced Key Usage (EKU) Object Identifier (OID), and the CRL must be available. Also, the NLS must be configured to allow inbound ICMPv4 echo requests from the DirectAccess server(s).

DNS

The following topics describe Domain Name System (DNS) requirements and configuration for DirectAccess.

Internal

Entries in DNS are made during the initial configuration of DirectAccess.¹⁰ The DirectAccess administrator must have the ability to create new DNS entries. If that is not possible, the following DNS entries must be preconfigured by a DNS administrator.

Name	Record Type	Data
DirectAccess-CorpConnectivityHost	А	127.0.0.1
DirectAccess-CorpConnectivityHost	AAAA	<client ipv6="" prefix="">:0:0:7f00:1</client>
DirectAccess-WebProbeHost	А	<ipv4 address="" directaccess="" of="" server<br="">Internal Network Interface></ipv4>

⁹More information about NLS considerations for large enterprises read http://directaccess.richardhicks. com/2015/04/06/directaccess-nls-deployment-considerations-for-large-enterprises/. ¹⁰https://directaccess.richardhicks.com/2015/07/06/directaccess-dns-records-explained/

External

A DNS entry must be configured that resolves the DirectAccess public hostname to the external public IPv4 address of the DirectAccess server (or edge firewall, in a perimeter/DMZ deployment). For multisite deployments, each entry point will require a unique public hostname and corresponding DNS entry. An additional DNS entry must be configured when GSLB is implemented.

Strong User Authentication

The enforcement of strong user authentication is optional, but does have some drawbacks. OTP solutions negatively impact the seamless and transparent nature of DirectAccess, resulting in a degraded end-user experience. However, DirectAccess supports integration with a variety of multifactor authentication solutions, including RSA SecurID, OTP, and physical or virtual smart cards.

Certificate Server

To enforce strong user authentication, a Microsoft Enterprise CA must be deployed to issue certificates. This can be the same CA used for DirectAccess computer authentication and IPsec encryption.

RSA SecurID

RSA SecurID OTP authentication using physical or soft tokens is supported.

One-Time Passwords (OTP)

Most RADIUS-based OTP solutions can be integrated with DirectAccess. However, OTP solutions that use RADIUS challenge/response or employ CAPTCHA are not supported. In addition, RADIUS user accounts that are in new PIN or next token modes are not supported.

Smart Cards

Both physical and virtual smart cards are supported with DirectAccess.

Security Groups

Users that require exemption from strong user authentication must be part of an Active Directory security group configured for the purpose.

User Accounts

DirectAccess uses a predefined user account to monitor RADIUS server availability. A corresponding and matching user account must be created on the RADIUS server to eliminate failed authentication attempts.

Force Tunneling

Strong user authentication using RADIUS OTP cannot be configured with force tunneling. These options are mutually exclusive.

Manage Out

DirectAccess connectivity is bi-directional, enabling hosts on the corporate network to initiate outbound network communication to connected remote DirectAccess clients. In order to natively support manage-out functionality, IPv6 must be deployed on the corporate network.

ISATAP

If IPv6 has not been deployed on the corporate network, the Intrasite Automatic Tunnel Addressing Protocol (ISATAP) IPv6 transition technology can be leveraged to create an IPv6 overlay network used solely for this purpose. ISATAP is automatically configured on the server when DirectAccess is installed, and management clients can be configured to use the DirectAccess server as their ISATAP router.

Supportability

ISATAP is only supported for single-server DirectAccess deployments.

Summary

As you can see, there are a lot of moving parts involved in a DirectAccess implementation that make the initial planning vital to the success of the deployment. The Windows platform technologies that DirectAccess relies on are commonly deployed and well understood, making the deployment of DirectAccess less challenging for those with Windows systems-management experience.

CHAPTER 3

Install DirectAccess

Once the DirectAccess planning and design phase is complete, it's time to move on to preparing the first DirectAccess server. A physical server or virtual machine will be provisioned that meets the necessary minimum requirements for the deployment. The Windows Server 2016 operating system will be installed, joined to the domain, and updated as required. Additional preparation will include network interface configuration for multihomed servers, along with computer and SSL certificate installation. Finally, the DirectAccess role itself can be installed.

DirectAccess Server

After the physical or virtual server has been provisioned, the Windows Server 2016 operating system can be installed. Both server core and full graphical user interface (GUI) versions of Windows Server 2016 are supported. However, it is recommended that the server be configured with a GUI initially to make the installation and configuration of DirectAccess easier. Once the server has been tested, and prior to placing it into production, the GUI can be safely removed and the server managed remotely.

Operating System Installation

There are no special requirements for installing the Windows Server 2016 operating system. You can install the OS using the installation media provided by Microsoft, or it can be deployed using an automated provisioning process. Avoid installing the OS using an image that is heavily customized or has third-party firewall or antivirus software installed by default. These commonly interfere with the proper operation of DirectAccess. Instead, install the operating system from Microsoft media and then deploy DirectAccess. Once DirectAccess operation has been verified, any additional third-party software required can be installed.

Single-NIC Configuration

DirectAccess can be deployed with a single network adapter in both perimeter/DMZ and LAN deployments. There is no special configuration required for single-Network Interface Card (NIC) deployments. Simply provide an IPv4 address, subnet mask, and default gateway as required.

Dual-NIC Configuration

The most common network configuration for the DirectAccess server is multihomed, where the server is configured with two NICs. Dual NICs are required for edge-facing deployments. They are optional for perimeter/DMZ deployments. When the DirectAccess server is configured with two network adapters (multihomed), one network interface is defined as internal, the other as external. Which network the internal and external network interfaces reside on depends on the chosen topology.

- Edge-facing deployments
 - External interface connected to the public Internet using public IPv4 addressing
 - Internal interface connected to a perimeter or DMZ network or the LAN using private IPv4 addressing
- Perimeter/DMZ deployments
 - External interface connected to the perimeter or DMZ network using public or private IPv4 addressing
 - Internal interface connected to a perimeter or DMZ network or the LAN using private IPv4 addressing

Internal Interface

Open **Network Connections** by pressing **Window Key + X** and clicking **Network Connections**. Rename the network connections intuitively so they can be quickly identified in the future. Renaming them **Internal** and **External** should be sufficient. Network adapters can be renamed by right-clicking them and choosing **Rename** or by simply highlighting a network adapter and pressing **F2** (Figure 3-1).

Network Connections		-		×
← → · · ↑ 👰 > Network Connecti	√ Ū	Search Network Cor	nnections	P
Organize Disable this network device	»		•	?
Ethernet Unidentified network Microsoft Hyper-V Network Adap	Inte lab. Mic	rnal richardhicks.net rosoft Hyper-V Netwo	rk Adap	
2 items 1 item selected				

Figure 3-1. Rename network connections

To configure the Internal network interface, right-click the Internal network connection and choose **Properties**. Highlight **Internet Protocol Version 4 (TCP/IPv4)** and then click **Properties**. Provide an IPv4 address and a subnet mask. **DO NOT** specify a default gateway! Provide the IP addresses for DNS servers on the corporate LAN as necessary (Figure 3-2).

Internet Protocol Version 4 (TCP/IP)	v4) Properties	>
General		
You can get IP settings assigned au this capability. Otherwise, you need for the appropriate IP settings.	tomatically if your network supports I to ask your network administrator	
Obtain an IP address automati	cally	
• Use the following IP address:		
IP address:	172 . 16 . 1 . 240	
Subnet mask:	255.255.255.0	
Default gateway:		
Obtain DNS server address au	tomatically	
• Use the following DNS server a	addresses:	
Preferred DNS server:	172 . 16 . 1 . 200	
Alternate DNS server:	172 . 16 . 2 . 200	
Validate settings upon exit	Advanced	
	OK Cancel	

Figure 3-2. Assign IPv4 address, subnet mask, and corporate DNS servers to the Internal network interface

Note A multihomed Windows server must have a default gateway defined on **one interface only**. That interface must be the external, Internet-facing network interface. Any remote internal subnets will require static routes to be defined on the DirectAccess server to reach them.

External Interface

To configure the External interface, right-click the External adapter and choose **Properties**. Highlight **Internet Protocol Version 4 (TCP/IPv4)** and then click **Properties**. Provide an IPv4 address, subnet mask, and default gateway. **DO NOT** specify any DNS servers! (See Figure 3-3.)

Internet Protocol Version 4 (TCP/IPv	/4) Properties	×
General		
You can get IP settings assigned aut this capability. Otherwise, you need for the appropriate IP settings.	tomatically if your network supports to ask your network administrator	
Obtain an IP address automatic	cally	
• Use the following IP address:		
IP address:	203 . 0 . 113 . 240	
Subnet mask:	255.255.255.0	
Default gateway:	203 . 0 . 113 . 254	
Obtain DNS server address aut	tomatically	
• Use the following DNS server a	ddresses:	
Preferred DNS server:		
Alternate DNS server:	• • •	
Validate settings upon exit	Advanced	
	OK Cancel	

Figure 3-3. Assign IPv4 address, subnet mask, and default gateway to External network interface

Click **Advanced**. If Teredo support is required, click **Add** under the **IP addresses** section and specify the next consecutive public IPv4 address and subnet mask (Figure 3-4).

TCP/IP Address		×
IP address:	203 . 0 . 113 . 241	
Subnet mask:	255.255.255.0	
	Add	Cancel

Figure 3-4. Assign additional IPv4 addresses (if required)

Select the DNS tab and uncheck the box next to Register this connection's addresses in DNS (Figure 3-5).

Advanced T	CP/IP S	ettings			×
IP Settings	DNS	WINS			
DNS serve	r addres	sses, in order of	use:		
					t
					3
	[Add	Edit	Remove	
Append App App Append	d primary pend par d these (y and connection rent suffixes of DNS suffixes (in	n specific DNS su the primary DNS order):	ffixes suffix	
					3
		Add	Edit	Remove	
DNS suffix	for this	connection:]
Begiste	e <mark>r this co</mark> s connec	onnection's addre ction's DNS suffi	esses in DNS x in DNS registra	tion	
				OK (Cancel

Figure 3-5. Uncheck the option to register this connection's address in DNS

Select the **WINS** tab and uncheck the box next to **Enable LMHOSTS lookup**. In addition, in the **NetBIOS setting** section select the option to **Disable NetBIOS over TCP/IP** (Figure 3-6).

Advanced TCP/IP Settings	×
IP Settings DNS WINS	
WINS addresses, in order of use:	
1	È i
	L
Add Edit Remove	
If LMHOSTS lookup is enabled, it applies to all connections for which TCP/IP is enabled.	
Enable LMHOSTS lookup Import LMHOSTS.	
NetBIOS setting	
O Default: Use NetBIOS setting from the DHCP server. If static IP addre is used or the DHCP server does not provide NetBIOS setting enable NetBIOS over TCP/IP.	ss ,
C Enable NetBIOS over TCP/IP	
Disable NetBIOS over TCP/IP	
ОК Са	ncel

Figure 3-6. Uncheck the option to enable LMHOSTS lookup and select the option to disable NetBIOS over TCP/IP

Note As the External network interface is public facing and connected to an untrusted network (public Internet or perimeter/DMZ network), it is recommended that all protocols and services other than IPv4 and IPv6 be disabled to reduce the attack surface of the DirectAccess server.

Back in the **Network Connections** window, click the **Organize** button, highlight **Layout**, and then select **Menu bar** (alternatively, you can simply press the Alt key to expose this menu). From the drop-down menu click **Advanced** and then **Advanced Settings**. Ensure that the Internal network interface is listed first. To adjust the connection order, highlight the Internal network adapter and then click the up arrow on the right side to move it to the top of the list (Figure 3-7).

CHAPTER 3 INSTALL DIRECTACCESS

Advanced Settings		×
Adapters and Bindings	Provider Order	
Connections are listed network services.	in the order in which they are accessed by	
Connections:		
		t
Remote Access	connections]	3
Bindings for Internal:		
File and Printe	er Sharing for Microsoft Networks	t
Internet P	Protocol Version 6 (TCP/IPv6)	
Client for Micr	rotocol Version 4 (TCP/IPv4)	÷.
	Protocol Version 4 (TCP/IPv4)	
✓ Internet P	Protocol Version 6 (TCP/IPv6)	
	ОК С	Cancel

Figure 3-7. Network connection ordering

Static Routes

As the Internal network interface does not have a default gateway, it will be necessary to configure static routes to remote internal subnets that will need to be reachable from the DirectAccess server and by DirectAccess clients. For example, if the DirectAccess server is on the 172.16.1.0/24 subnet, but there are systems on the 172.16.2.0/24 subnet that must be accessible from the DirectAccess server, a static route will be defined by entering the following commands in an elevated PowerShell command window:

```
New-NetRoute -InterfaceAlias <Interface Name> -DestinationPrefix <SubnetID/Mask>
-NextHop <Gateway_Address>
```

Using the preceding example, the command to create the static route would look like this:

```
New-NetRoute -InterfaceAlias Internal -DestinationPrefix 172.16.2.0/24 -NextHop 172.16.1.254
```

If there are multiple remote subnets on the Internal network, it is recommended that the route be summarized, if possible. For example, if there are additional subnets that are all in the 172.16.0.0/16 network, you can summarize them as follows:

```
New-NetRoute -InterfaceAlias Internal -DestinationPrefix 172.16.0.0/16 -NextHop 172.16.1.254
```

Note If you've read the first two chapters of this book you are no doubt keenly aware of the requirement for IPv6 to support DirectAccess. However, you'll notice that *no* IPv6 configuration is required when configuring network interfaces. That's by design. IPv6 configuration is performed automatically when DirectAccess is configured. If IPv6 is deployed on the Internal network, great! DirectAccess will make use of it, but there's no special IPv6 configuration required to support DirectAccess.

Join Domain and Apply Updates

The DirectAccess server must be joined to a domain. It is recommended that the server be renamed prior to doing this, but it can also be performed after being joined to the domain. Joining the server to the domain can be accomplished in the traditional way using the GUI, but I suggest using PowerShell so as to simplify and streamline the process. Using the **Add-Computer** PowerShell cmdlet, it is possible to rename the computer, join it to the domain, and place the server in a specific Organizational Unit (OU) with a single command:

Add-Computer -NewName <new_computer_name> -OUPath <OU_Path> -DomainName <domain_name>

For example:

Add-Computer -NewName EDGE1 -OUPath "OU=DirectAccess,DC=lab,DC=richardhicks,DC=net" -DomainName lab.richardhicks.net -Restart

Once the DirectAccess server has been joined to the domain, proceed with installing Windows operating updates as necessary using Windows Update (Window Key + I ➤ Update & Security ➤ Check for Updates), Windows Server Update Services (WSUS), System Center Configuration Manager (SCCM), or any other third-party patch-management solution.

Third-Party Software

There is a high propensity for third-party software to interfere with the proper operation of DirectAccess. This occurs because commonly these non-Microsoft services are not IPv6 aware, or otherwise block protocols and services necessary for DirectAccess to work. As such, it is generally recommended that no third-party software be installed on the DirectAccess server.

In many cases, the installation of additional software on the DirectAccess server is unavoidable. Frequently, organizations have strict guidelines that dictate that management agents or antivirus or firewall software be installed before production use. Here, it is suggested that DirectAccess be installed, configured, and completely tested prior to installing third-party software. This will reduce the troubleshooting burden if the third-party software prevents DirectAccess from functioning correctly.

Certificates

For most deployment scenarios it will be necessary to install certificates on the DirectAccess server. DirectAccess requires two different types of certificates—a computer (machine) certificate and an SSL certificate.

Computer (Machine) Certificates

For DirectAccess deployments that require them, computer certificates are used for IPsec authentication and encryption. They must be issued to the DirectAccess server by an internal PKI. The certificate must include the Client Authentication Enhanced Key Usage (EKU).

Best practice is to not use the default Computer certificate template. Instead, it is recommended that a dedicated certificate template for DirectAccess IPsec be configured and deployed specifically for this purpose. To create a certificate template, open the Certificate Services management console on the Active Directory Certificate Services (AD CS) server. In the navigation tree, expand the server and then right-click **Certificate Templates** and choose **Manage**. Optionally, you can press **Windows Key + R** and enter **certimpl.msc**.

Right-click the **Workstation Authentication** template and choose **Duplicate Template**. Select the **General** tab and provide a descriptive name for the new template. Specify an appropriate validity and renewal period based on your organization's security policy (Figure 3-8).

Prop	perties	of New	Template	×
Subject Name	Sen	ver	Issuance R	equirements
Superseded Templa	tes	Ext	ensions	Security
Compatibility General	Request	Handling	Cryptography	Key Attestation
Template display name:				
DirectAccess IPsec				
Template name: DirectAccessIPsec				
Validity period:]	Renew:	al period: weeks V	
Publish certificate in Do not automatic Directory	Active Dir ally reenro	rectory oll if a dup	licate certificate (exists in Active
ОК		Cancel	Apply	Help

Figure 3-8. Configure the DirectAccess computer certificate template

Select the Subject Name tab and choose DNS name for the Subject name format ((Figure <mark>3-9</mark>).
--	-----------------------------

Superseded Templa	ates	Exte	ensions	Security
Compatibility General	Request	Handling	Cryptography	Key Attestation
Subject Name	Ser	ver	Issuance F	Requirements
 Supply in the request Use subject information renewal request Build from this Activ Select this option to simplify certificate ad Subject name formation 	st ormation fro e Directory enforce co ministration	om existing y informatio onsistency n.	certificates for a n among subject r	autoenrollment
DNS name				~
Include this informati E-mail name V DNS name User principal na	me (UPN) name (SP	nate subjer N)	ct name:	

Figure 3-9. Configure the DirectAccess computer certificate template

Select the **Security** tab and click **Add**. Specify the names of the DirectAccess client security group and the name of each DirectAccess server. Optionally, a security group can be created for DirectAccess servers, and that group can be specified here. For the DirectAccess client group and the DirectAccess servers (or DirectAccess server group), check the **Allow** box for both **Enroll** and **Autoenroll**. Once complete, click **OK** (Figure 3-10).

CHAPTER 3 INSTALL DIRECTACCESS

omponenty	General	Request	Handling	Cryptography	Key Attestation
Subject N	Name	Serv	/er	Issuance R	equirements
Supersec	ded Templa	ates	Exte	ensions	Security
Group or use	er names:				
& Authen	ticated Use	ers			
Se Direct A	ccessClien	ts (LAB\Dir	rectAcces	ssClients)	
& DirectA	ccessServ	ers (LAB\D)irectAcce	essServers)	
& Richard	d Hicks (rhid	cks@lab.rid	chardhick	s.net)	
Se Domain	Admins (L	AB\Domair	n Admins)		
Se Domain	Computers	s (LAB\Dor	main Com	puters)	
Senterpri	ise Admins	(LAB\Ente	rprise Adr	nins)	
				A <u>d</u> d	Remove
		~			
Permissions	for DirectA	ccessClient	ts	Allow	Deny
Permissions Full Control	for DirectAr bl	ccessClient	ts	Allow	Deny
Permissions f Full Contro Read	for DirectA ol	ccessClient	ts	Allow	Deny
Permissions Full Contro Read Write	for DirectA	ccessClient	ts	Allow	Deny
Permissions Full Control Read Write Enroll	for DirectA	ccessClient	ts	Allow	Deny
Permissions f Full Contro Read Write Enroll Autoenroll	for DirectAr bl	ccessClient	ts	Allow	Deny
Permissions f Full Contro Read Write Enroll Autoenroll	for DirectAr	ccessClient	ts	Allow	Deny
Permissions f Full Contro Read Write Enroll Autoenroll	for DirectAr	ccessClient	ts	Allow	Deny
Permissions f Full Contro Read Write Enroll Autoenroll	for DirectAr	or advance	ed setting	Allow	Deny
Permissions i Full Contro Read Write Enroll Autoenroll For special p Advanced.	for DirectAr ol bermissions	or advance	ts ed setting	Allow	Deny
Permissions f Full Contro Read Write Enroll Autoenroll For special p Advanced.	for DirectAr ol	or advance	ed setting	Allow	Deny

Figure 3-10. Configure the DirectAccess computer certificate template

Note If certificate autoenrollment will be used (recommended, see next section), it is advisable to also remove Domain Computers from the list of groups and user names on the Security tab.

In the Certification Authority management console, right-click **Certificate Templates** and choose **New** and **Certificate Template to Issue**. Highlight the DirectAccess IPsec certificate template and choose **OK** (Figure 3-11).

CHAPTER 3 INSTALL DIRECTACCESS

Enable (Certificate Templates	
Select one Certificate Template to enable on this (lote: If a certificate template that was recently cre nformation about this template has been replicated If of the certificate templates in the organization n For more information, see <u>Certificate Templa</u>	Certification Authority. eated does not appear on this list, you may need to wait until d to all domain controllers. nay not be available to your CA. ate Concepts.	
Name	Intended Purpose	^
Ruthenticated Session	Client Authentication	
R CA Exchange	Private Key Archival	
CEP Encryption	Certificate Request Agent	=
🖳 Code Signing	Code Signing	
R Cross Certification Authority	<ali></ali>	
🚇 DirectAccess IPsec	Client Authentication	
🖳 Enrollment Agent	Certificate Request Agent	
Renrollment Agent (Computer)	Certificate Request Agent	
Rechange Enrollment Agent (Offline request)	Certificate Request Agent	
Rechange Signature Only	Secure Email	
R Exchange User	Secure Fmail	~
	OK Cance	el

Figure 3-11. Issue the DirectAccess computer certificate template

Computer certificates can be requested and installed manually on the DirectAccess server using the Certificates management console snap-in. To request a computer certificate, press **Window Key + R** on the DirectAccess server to bring up the **Run** command box and enter **certIm.msc**

Expand **Certificates (Local Computer)**, right-click **Personal**, and choose **All Tasks** and **Request New Certificate**. Click **Next** twice, select the DirectAccess IPsec certificate template, and click **Enroll** (Figure 3-12).

		-		×
Certificate Enrollment				
Request Certificates				
You can request the following types click Enroll.	of certificates. Select the certificates you wan	t to request, a	and then	
Active Directory Enrollment Poli	cy			
Computer	(i) STATUS: Available		Details	•
DirectAccess IPsec	i STATUS: Available		Details	•
Show all templates				
		Enroll	Can	cel

Figure 3-12. DirectAccess IPsec computer certificate request

Automatic Enrollment

To streamline the provisioning of certificates for DirectAccess servers and clients, and to ensure that certificates are automatically renewed before they expire, it is recommended that certificate auto-enrollment be configured. This is accomplished by creating and deploying a Group Policy Object (GPO) in Active Directory.

To create and deploy a computer certificate auto-enrollment GPO, open the Group Policy Management console, expand the **Forest**, **Domains**, and the domain where the DirectAccess server and clients are joined. Right-click **Group Policy Objects** and click **New**. Provide a descriptive name for the new GPO and click **OK**.

Right-click the newly created GPO and choose **Edit**. Expand **Computer Configuration**, **Policies**, **Windows Settings**, and **Security Settings**, and highlight **Public Key Policies**. Double-click **Certificate Services Client - Auto-Enrollment** and select **Enabled** for the **Configuration Model**. Select the option to **Renew expired certificates**, **update pending certificates**, **and remove revoked certificates** and **Update certificates that use certificate templates** and click **OK** (Figure 3-13).

Certificate Services Client - Auto-Enrollment Pr	?	x		
Enrollment Policy Configuration				
Enroll user and computer certificates automatically				
Configuration Model: Enabled		~		
Renew expired certificates, update pending certificates, and remove revoked certificates				
Update certificates that use certificate templates				
Log expiry events and show expiry notifications when the perce remaining certificate lifetime is	entage	e of		
10 ~ %				
Additional stores. Use "," to separate multiple stores. For exam "Store 1, Store 2, Store 3"	ple:			
OK Cancel	Ap	ply		

Figure 3-13. Configure computer certificate auto-enrollment

In the Group Policy Management Console, select the GPO and click **Add** under **Security Filtering**. Remove **Authenticated Users** and specify the DirectAccess client security group and all DirectAccess servers (or the DirectAccess servers security group; Figure 3-14).

Security Filtering

The settings in this GPO can only apply to the following groups, users, and computers:

Name			
👫 Direct Access Clie	nts (LAB\DirectAccessC	lients)	
Represent Access Ser	vers (LAB\DirectAccess	Servers)	
LLA	Permatura	Properties	
HOQ	Delluve	LIUUGIUGA	

Figure 3-14. Computer certificate auto-enrollment GPO security filtering

Finally, link the GPO to the domain. Optionally, the GPO can be linked directly to the DirectAccess servers and clients OU, if necessary.

SSL Certificate

An SSL certificate is required for the IP-HTTPS IPv6 transition protocol. It is recommended that the SSL certificate be obtained from a public certificate authority (CA), although the SSL certificate can be issued by the organization's internal PKI.napd

Note If an SSL certificate is issued by the organization's internal PKI and Windows 7 clients are to be supported, the Certificate Revocation List (CRL) must be publicly accessible.

The first step in requesting a public SSL certificate is to generate a Certificate Signing Request (CSR). This can be accomplished in a variety of ways, including using the Microsoft Management Console (MMC) Certificates snap-in, the certutil.exe command-line tool, and even the Internet Information Services (IIS) management tool. Another convenient method is to use the DigiCert Certificate Utility for Windows.¹ This handy free tool greatly simplifies the process of creating a CSR. Download and run the tool, highlight **SSL**, and then click **Create CSR**.

Choose **SSL** for the **Certificate Type** and enter the **Common Name**. The Common Name will be the public Fully Qualified Domain Name (FQDN) defined in the DirectAccess configuration (for example, da.richardhicks.net). If requesting a wildcard certificate, enter *.yourdomain.tld (for example *.richardhicks. net). Provide the remaining details as required and click **Generate** when finished (Figure 3-15).

^{&#}x27;The DigiCert Certificate Utility for Windows can be downloaded for free from https://www.digicert.com/util/.

CHAPTER 3 INSTALL DIRECTACCESS

Certificate Det	ails		Information
Certificate Type:	SSL Code Signing		Proce Generate to create the new key and CCC
Common Name:	*.richardhicks.net		Tiess delierate to deate the new key and CSI
Subject Alternative Names:		^	
		~	
Organization:	Richard M. Hicks Consulting		
Department:	Professional Services		
City:	Sports Santa Hargaria		
State:	CA	~	
Country:	USA	~	
Key Size:	2048	~	
Provider:	Microsoft RSA SChannel Cryptographic Provider	~	

Figure 3-15. Creating a Certificate Signing Request (CSR) using the Digicert Certificate Utility for Windows

A new certificate request will be created. Copy the CSR or save it to a file, then submit it to a public CA (Figure 3-16).





Once the CSR has been approved and processed by your CA, download the certificate and any additional intermediate certificates provided. Import any intermediate certificates using the Certificates MMC snap-in prior to importing the new certificate. Intermediate certificates should be imported into the Certificates (Local Computer) > Intermediate Certification Authority > Certificates store.

In the DigiCert utility click **Import** and specify the location of the certificate downloaded from the CA. Enter a new friendly name for the certificate and click **Finish** (Figure 3-17).

0	DigiCert Certi	ficate Utility for Windows©	×
	Certifica	ate Import	
	The following ce the certificate p	ertificate is ready to be imported. For more details of ress the View Certificate button.	View Certificate
	Serial Number:	*.richardhicks.net 00A473DA050997AC45	
	Thumbprint:	2DB86C910DAD6503FF0112BA3A3AFA56B38D4F60	
	Private Key:	Search for an existing private key match on the computer	r
	Enter a new frie	endly name or you can accept the default:	
	*.richardhicks.	net	
	Press the Finish	button to import the certificate and search for a matching	private key.
		< Back Finish	Cancel

Figure 3-17. Certificate Import using the DigiCert Certificate Utility for Windows

Once the certificate has been successfully imported, select the certificate and choose **Export Certificate**. Select the option to export the private key. Additionally, select the option to **Include all certificates in the certification path if possible** and click **Next**. Provide a password and click **Next**. Finally, specify the location to save the file and click **Finish**.

To import the SSL certificate on the DirectAccess server, press **Window Key + R** to bring up the **Run** command box. Enter **mmc.exe**, click **File**, and then choose **Add/Remove Snap-In**. Highlight **Certificates** and click **Add**. Select **Computer Account** and click **Finish**. Choose **Local Computer (the computer this console is running on)** and click **Finish** and **OK**.

Expand **Certificates (Local Computer)**, right-click **Personal**, and choose **Import**. Click **Next**, specify the file name of the exported certificate, and click **Next** again. Provide the password for the certificate file, click **Next** twice, and then click **Finish**.

Note If any intermediate certificates appear in the Personal/Certificates store after importing the SSL certificate, move them to the Intermediate Certification Authority/Certificates store as necessary.

Installing the DirectAccess-VPN Role

Installing the DirectAccess-VPN role can be accomplished using either the GUI or PowerShell. PowerShell is the preferred method for installing the role, as it takes only a single PowerShell command to install the role and management tools.

PowerShell

Installing the DirectAccess-VPN role using PowerShell is simple and straightforward. On the DirectAccess server, open an elevated PowerShell window and enter the following command:

Install-WindowsFeature DirectAccess-VPN -IncludeManagementTools

That's it!

GUI

Installing the DirectAccess-VPN role using the GUI is accomplished by opening **Server Manager** on the DirectAccess server, clicking **Manage** in the upper-right corner of the window, and then clicking **Add Roles and Features**. Click **Next**, choose **Role-based or feature-based installation**, and click **Next**. Choose **Select a server from the server pool** and click **Next**. Select the **Remote Access** server role and click **Next** (Figure 3-18).



Figure 3-18. Select the Remote Access server role

Role features are automatically selected. Click **Next** twice and then select the **DirectAccess and VPN** (**RAS**) role service (Figures 3-19 and 3-20).

CHAPTER 3 INSTALL DIRECTACCESS

Add Roles and Features Wizard	1	- 🗆 X
Select role service	es	DESTINATION SERVER edge1.lab.richardhicks.net
Before You Begin Installation Type Server Selection Server Roles Features Remote Access Role Services Confirmation Results	Select the role services to install for Remote Access Role services DirectAccess and VPN (RAS) Routing Web Application Proxy	Description DirectAccess gives users the experience of being seamlessly connected to their corporate network any time they have Internet access. With DirectAccess, mobile computers can be managed any time the computer has Internet connectivity, ensuring mobile users stay up-to-date with security and system health policies. VPN uses the connectivity of the Internet plus a combination of tunnelling and data encryption technologies to connect remote clients and remote offices.
	< Previous	Next > Install Cancel

Figure 3-19. Select the DirectAccess and VPN (RAS) role service

Add features that are required for DirectAcces	ss and
VPN (RAS)?	
The following tools are required to manage this feature, be have to be installed on the same server.	out do not
Remote Server Administration Tools	
Role Administration Tools	
A Remote Access Management Tools	
 Remote Access Management Tools [Tools] Remote Access module for Window 	vs PowerShe
 Remote Access Management Tools [Tools] Remote Access module for Window 	vs PowerShe
 Remote Access Management Tools [Tools] Remote Access module for Window 	vs PowerShe
 Remote Access Management Tools [Tools] Remote Access module for Window 	vs PowerShe
 Remote Access Management Tools [Tools] Remote Access module for Window 	vs PowerShe
Remote Access Management Tools [Tools] Remote Access module for Window	vs PowerShe
Remote Access Management Tools [Tools] Remote Access module for Window	vs PowerShe
 Remote Access Management Tools [Tools] Remote Access module for Window Include management tools (if applicable) 	vs PowerShe
 Remote Access Management Tools [Tools] Remote Access module for Window Include management tools (if applicable) 	vs PowerShe

Figure 3-20. Add features that are required for DirectAccess and VPN (RAS)

Confirm the installation selections and click Install (Figure 3-21).

CHAPTER 3 INSTALL DIRECTACCESS

Confirm installa	tion selections	DESTIN edge1.lab.r	ATION SER	RVER s.net
Before You Begin	To install the following roles, role services, or features on select	ted server, click Install.		
Installation Type	Restart the destination server automatically if required			
Server Selection Server Roles	Optional features (such as administration tools) might be displ been selected automatically. If you do not want to install these their check boxes.	ayed on this page because t optional features, click Prev	they have vious to c	e lea
Remote Access Role Services Confirmation	Remote Access DirectAccess and VPN (RAS) Remote Server Administration Tools Role Administration Tools			
	Remote Access Management Tools Remote Access module for Windows PowerShe	ell.		
	Export configuration settings Specify an alternate source path			

Figure 3-21. Confirm your installation selections

Configuring Additional Nodes

If multiple DirectAccess servers will be configured in a load-balanced cluster, each server must be prepared using the steps outlined in this chapter prior to joining the cluster. Each additional DirectAccess server will have to be provisioned and have network interface cards configured according to the chosen network topology. The servers must be joined to the domain, updated, and have all required certificates (computer and SSL) installed. Finally, the DirectAccess role can be configured.

Summary

Getting all of the pieces in place prior to installing the DirectAccess-VPN role is not a trivial task. Pay careful attention to network interface configuration, especially static route configuration for dual-NIC deployments. Use caution when deploying third-party software, as it often interferes with DirectAccess operation. Ensure that computer and SSL certificates are installed and configured properly too. Save yourself some time and use PowerShell to install the DirectAccess-VPN role, and don't forget that if you are planning to deploy multiple DirectAccess servers in a load-balanced cluster, all of the steps outlined in this chapter must be completed on each DirectAccess server prior to deployment.

CHAPTER 4

Configure DirectAccess with the Getting Started Wizard

There are two options for configuring DirectAccess using the Graphical User Interface (GUI). The first option is to use the Getting Started Wizard. The second is to use the Remote Access Setup Wizard. On the surface they would appear to perform the same function. However, the two options differ in subtle but important ways.

The Getting Started Wizard only requires the administrator to select a deployment option, choose a network topology, and provide a public hostname. It can be accomplished with as few as three mouse clicks. That's it! However, it configures DirectAccess in a highly simplified manner and with limited options that may not be suitable for many deployments.

Before We Begin

The Getting Started Wizard configures DirectAccess using default settings that are typically less than optimal. Its basic configuration lacks support for common requirements, such as support for Windows 7 clients, load balancing, strong user authentication, force tunneling, and geographic redundancy with multisite. As such, using the Remote Access Setup Wizard is often a better choice.

However, if the DirectAccess deployment is small and doesn't require Windows 7 client support or high availability, using the Getting Started Wizard to deploy DirectAccess is an acceptable option.

Getting Started Wizard

To launch the Getting Started Wizard, open the Remote Access Management Console on the DirectAccess server. The Remote Access Management Console can be found by clicking on the **Start** menu and navigating to **All Apps ➤ Windows Administrative Tools ➤ Remote Access Management Console**. Expand **Configuration**, highlight **DirectAccess and VPN**, and then click **Run the Getting Started Wizard** (Figure 4-1).

CHAPTER 4 CONFIGURE DIRECTACCESS WITH THE GETTING STARTED WIZARD



DirectAccess & VPN settings have not yet been configured. Select one of the wizard options.

Run the Getting Started Wizard

Use this wizard to configure DirectAccess and VPN quickly, with default recommended settings.

→ Run the Remote Access Setup Wizard

Use this wizard to configure DirectAccess and VPN with custom settings.

Figure 4-1. Run the Getting Started Wizard

Note The Getting Started Wizard and the Remote Access Setup Wizard will not appear if DirectAccess has already been configured.

Deployment Options

The Getting Started Wizard provides three options for configuring DirectAccess and VPN (Figure 4-2).



Figure 4-2. Configure Remote Access window

Deploy both DirectAccess and VPN (recommended)

Although the GUI suggests this option is "recommended," there are some very important reasons why VPN should not be installed on the DirectAccess server. The most critical reason is that it eliminates support for important scalability and performance features included in DirectAccess, namely null encryption for IP-HTTPS connections for Windows 8.x and Windows 10 clients. Having VPN and DirectAccess on the same server also makes the solution more complex, especially when configuring redundancy for DirectAccess (load balancing and multisite). As such, this configuration should be avoided if possible.¹

Deploy DirectAccess only

This option should be selected.

Deploy VPN only

This is a book about DirectAccess, so this option is not applicable for our purposes.

Installing DirectAccess

To install DirectAccess without VPN, select the option to **Deploy DirectAccess only**. The Getting Started Wizard will perform a prerequisites check to ensure essential supporting components are installed.

Note It is not uncommon to receive an error message at this point. Typical errors are IPv6 being disabled via Group Policy or the registry, WinRM not being configured, and IPv6 transition protocols being disabled. Resolve any issues before proceeding.

Network Topology

Select the desired network topology for the server (Figure 4-3). Options are **Edge**, **Behind an edge device** (with two network adapters), and **Behind an edge device** (with a single network adapter). Options that are not supported will be grayed out. For example, if the server has a private IPv4 address assigned to its External network interface, the **Edge** option will not be displayed. If the DirectAccess server has only one network interface, the **Edge** and **Behind an edge device** (with two network adapters) options will both be unavailable. In addition, enter the Fully Qualified Domain Name (FQDN) that will be used by DirectAccess clients to connect to the DirectAccess server. The FQDN must resolve to the public IPv4 address assigned to the DirectAccess server's External network interface, and it must match the subject name of the SSL certificate. For NAT deployments, it must resolve to the public IPv4 address assigned to the NAT device.

¹The Web Application Proxy (WAP) role can also be configured on the same server as DirectAccess. Although technically supported, it too should be avoided if possible. The same reasons why VPN should not be installed on the DirectAccess server also apply to WAP. Best practice is to install DirectAccess on a server dedicated to the WAP role.

CHAPTER 4 CONFIGURE DIRECTACCESS WITH THE GETTING STARTED WIZARD

Configure Remote Access	×
Remote Access Server Setup Configure DirectAccess and VPN settings.	
Select the network topology of the server.	
● Edge	
O Behind an edge device (with two network adapters)	
 Behind an edge device (with a single network adapter) 	
In this topology, the Remote Access server is deployed at the edge of the internal corporate netw and is configured with two adapters. One adapter is connected to the internal network. The othe connected to the Internet.	vork r is
Type the public name or IPv4 address used by clients to connect to the Remote Access server:	
da.richardhicks.net	

Figure 4-3. Remote Access Server Setup window

Apply Settings

Click **Finish** to apply the settings (Figure 4-4). Recall that the Getting Started Wizard uses predefined configuration settings that may not be applicable in all scenarios. In some cases, it may be necessary to make changes to the default settings created by the Getting Started Wizard. Click on the **Click here** link to review and edit settings, if necessary.
Si Configure Remote Access	×
Configure Remote Access	
Getting Started Wizard	
Remote Access settings will be applied.	
Click <u>here</u> to edit the wizard settings. Configuration settings that can be modified include GPO setting the DirectAccess client security group, server adapters, and DNS properties.	ngs,
To apply the configuration settings, click Finish.	
< Back Next > Finish	Cancel

Figure 4-4. Remote Access settings to be applied

Review and Edit Settings

It is possible to edit some, though not all, of the settings configured using the Getting Started Wizard. Settings available to edit are GPO settings, remote client settings, remote access server settings, and infrastructure server settings (Figure 4-5).

CHAPTER 4 CONFIGURE DIRECTACCESS WITH THE GETTING STARTED WIZARD

🦄 Remote A	Access Review	_		×
	Remote Access Review	,		
	Summary of Remote Access con	figuration settings.		
Review the	configuration settings.			^
📑 GPO	Settings Change			
LAB				
Dire	ctAccess server GPO name:	DirectAccess Server Settings		
Clier	nt GPO name:	DirectAccess Client Settings		
Sem Rem	ote Clients Change			
	 DirectAccess settings will be a 	applied to all mobile computers in security groups:		
	👫 LAB\Domain Computers			
	 Resource used to verify intern A default web probe to check DirectAccess connection name 	al network connectivity: corporate connectivity will be created automatically e: Workplace Connection		~
		Save to a file Prin	<u>t</u> 0	к

Figure 4-5. Remote Access Review window

GPO Settings

By default, the Getting Started Wizard will name the DirectAccess client and server settings' GPOs **DirectAccess Client Settings** and **DirectAccess Server Settings**, respectively (Figure 4-6). If different names are desired, click **Change** next to **GPO Settings** and provide new GPO names as required. If prestaged GPOs are to be used, click **Browse** and select them accordingly.

SPO N	ames		×
	GPO Name	s	1
1	GPOs that will b	e used for DirectAccess deployment.	
Review the settings if re	GPOs that will be applie quired.	d to the client computers security group and the DirectAccess server in the relevant domains. Modify GPO	
0	Direct Access clien	t GPO	
-	GPO containing Direct	Access client settings:	
	LAB	DirectAccess Client Settings Browse 🤡 *	
	DirectAccess serve	er GPO	
	GPO containing Direct	Access server settings:	
	LAB	DirectAccess Server Settings Browse	
* - A nev	v Group Policy Object (G	PO) will be created	
- Use ex	xisting Group Policy Obje	od .	
		OK	Cancel

Figure 4-6. Edit GPO settings

Remote Clients

The Getting Started Wizard will configure the DirectAccess Client Settings GPO to apply to the **Domain Computers** security group. Additionally, it will also configure the GPO with a Windows Management Instrumentation (WMI) filter that further restricts the application of this GPO to only those computers with a mobile processor. For a variety of reasons, either or both of these settings may not be desirable. Click **Change** next to **Remote Clients** to specify a different security group or to disable the application of DirectAccess client settings only to mobile computers (Figure 4-7).

CHAPTER 4 CONFIGURE DIRECTACCESS WITH THE GETTING STARTED WIZARD

Enable DirectAccess for	managed computers in specified security groups, and configure client settin	ngs.
elect Groups	Select one or more security groups containing client computers that wi	ill be enabled for DirectAccess.
letwork Connectivity Assistant	Representation Computers (LAB\Domain Computers)	Add
		Remove

Figure 4-7. DirectAccess Client Setup window

Clicking **Next** or highlighting **Network Connectivity Assistant** on the left allows the administrator to change the Network Connectivity Assistant (NCA) settings provided to DirectAccess client computers. In addition, a help desk email address can be provided, the DirectAccess connection name can be changed, and DirectAccess clients can be allowed to use local name resolution, if necessary (Figure 4-8).

Remote Access Setup			×
DirectAccess Client Enable DirectAccess for n	t Setup nanaged computers in specified securi	ty groups, and configure client settings.	
Select Groups Network Connectivity Assistant	The Network Connectivity Assist DirectAccess connectivity inform Resources that validate connectiv	int (NCA) runs on DirectAccess client computers to provide ation, diagnostics, and remediation support. ity to internal network:	
	Resource	Туре	
	Helederk email address		
	DirectAccess connection name:	admin@richardhicks.net	
	Allow DirectAccess clients to	use local name resolution	
		< Back Next > Finish	Cancel

Figure 4-8. DirectAccess Client Setup window

Note Providing a help desk email address is critically important for client-side troubleshooting. Without an email address specified here, it is not possible to collect diagnostic logs on the client.

Remote Access Server

If changes are to be made to the network topology, or perhaps if the public hostname requires editing, click **Change** next to **Remote Access Server** to access these settings. You can choose another network topology or make changes to the public hostname as required (Figure 4-9).

💐 Remote Access Setup		×
Remote Acces Configure DirectA	s Server Setup	1
Network Topology Network Adapters	Select the network topology of the server.	
	< Back Next > Finish C	Cancel

Figure 4-9. Remote Access Server Setup window

Clicking **Next** or highlighting **Network Adapters** on the left allows the administrator to make changes to the default network adapter selection (Figure 4-10). The Getting Started Wizard automatically chooses the option to use a self-signed certificate for IP-HTTPS connections. If a public SSL certificate is to be used, click **Browse** and choose the certificate accordingly.



Figure 4-10. Configure the network adapter and SSL certificate settings

Infrastructure Servers

Clicking **Change** next to **Infrastructure Servers** allows the administrator to make changes to DNS suffixes and internal DNS servers for DirectAccess clients (Figure 4-11). A DNS name or suffix with a corresponding DNS server entry will be available over the DirectAccess connection. A DNS name or suffix without a corresponding DNS server entry will not be available over the DirectAccess connection and is said to be exempted or excluded. By default, the Network Location Server (NLS) hostname is excluded because it must not be reachable over the DirectAccess connection. In addition, exclusions are often required to ensure that public-facing resources such as websites are not tunneled back over DirectAccess.

nem(
	Infrastructure Server Setup		
1	Configure infrastructure servers. Direct	Access clients access these servers before	connecting to resources o
Enter	DNS suffixes and internal DNS servers. Dire	ectAccess client queries that match a suffi	ix use
the s	pecified DNS server for name resolution. Na servers are treated as exemptions, and DNS	me suffixes that do not have correspondi settings on client computers are used for	ng name
resol	ution.		
-	Name Suffix	DNS Server Address	7
•	lab.richardhicks.net	2002:cb00:71f0:3333::1	
	DirectAccess-NLS.lab.richardhicks.net		
•			
	L		
		C Rack Next >	Finish Cancel

Figure 4-11. Enter DNS suffixes and internal DNS servers

Note Internal corporate DNS servers should NEVER be specified here. The DNS server used by DirectAccess clients should ALWAYS be a DNS64 IPv6 address, which notably always ends with 3333::1. If there is no entry for the DNS server for a given name suffix, this server or namespace will not be accessible over the DirectAccess connection.

Confirm Policy Application

Once the DirectAccess configuration is complete and the settings have been applied, highlight **Operations Status** in the navigation tree of the Remote Access Management Console to view the DirectAccess server's **Operations Status** (Figure 4-12). The **Operations Status** for all DirectAccess supporting services should indicate **Working** and have a green check next to it.

CHAPTER 4 CONFIGURE DIRECTACCESS WITH THE GETTING STARTED WIZARD

Operations Status	Status Working Working	Since 4 minutes, 02 seconds 4 minutes, 02 seconds	Operations State	Refresh Configure Refresh In Open Event Viewer	iterval
ne vdge1.lab.richardhicks.net Ø DirectAccess Ø 6to4	Status Working Working	Since 4 minutes, 02 seconds 4 minutes, 02 seconds	Operations State	Configure Refresh In Open Event Viewer	nterval
re dge 1.lab.richardhicks.net 0 GrectAccess 6 6to4 0 DNS	Working Working Working	4 minutes, 02 seconds 4 minutes, 02 seconds	Operations state	Open Event Viewer	
DirectAccess 6to4 DNS	 Working Working 	4 minutes, 02 seconds			
6to4	Westing	The second		View Performance Ci	ounters
DNS.	SACULATION OF A	4 minutes, 05 seconds		Disable Coopertivity	Chark (DING)
The second se	Working	4 minutes, 02 seconds		of pole connecting	cuter (ring)
ONS64	Working	4 minutes, 05 seconds			
🔮 Domain controller	Working	4 minutes, 05 seconds			
IP-HTTPS	Working	4 minutes, 05 seconds			
C IPsec	Working	4 minutes, 05 seconds			
C Kerberos	Working	4 minutes, 05 seconds			
National adapted	Working	4 minutes, 05 seconds			
Network location server	Working	4 minutes 02 seconds			
A Network security	Working	4 minutes 05 seconds			
Services	Working	4 minutes, 05 seconds			
	Domain controller JP-HTDS Pipec Korberos Natrod: Network adapters Network location server Network security Services Details	Domain controller Working IP-HTTPS Working Prec Working Network Sector Working NaT64 Working Nat764 Working Network location server Working Network security Working Services Working	Domain controller Working 4 minutes, 05 seconds IP-HTTS Working 4 minutes, 05 seconds IP-text Vorking 4 minutes, 05 seconds Kerberos Working 4 minutes, 05 seconds NaT64 Working 4 minutes, 05 seconds Network datapters Working 4 minutes, 05 seconds Network security Working 4 minutes, 05 seconds Sentices Working 4 minutes, 05 seconds	Domain controller Working 4 minutes, 05 seconds DiPHTPS Working 4 minutes, 05 seconds DiPace Working 4 minutes, 05 seconds	Domain controller Working 4 minutes, 05 seconds Di PATTPS Working 4 minutes, 05 seconds Di Pace Working 4 minutes, 05 seconds Di Pace Working 4 minutes, 05 seconds Di Natoria Natoria Di Natoria Minutes, 05 seconds Di Natoria Natoria Di Natoria Minutes, 05 seconds Di Natoria Natoria Di Natoria Minutes, 05 seconds Di Natoria Minutes, 05 seconds Di Natoria Minutes, 05 seconds

Figure 4-12. DirectAccess server Operations Status window

Note Settings for the DirectAccess server are applied using Active Directory Group Policy. As such, it may take a period of time before those settings have been replicated in AD and are available to the DirectAccess server. Also, if the operations status of any supporting service is "unknown" and has a blue question mark next to it, continue to hit Refresh until its status has been updated.

Limitations and Drawbacks

Although the Getting Started Wizard allows the administrator to quickly and easily configure DirectAccess, there are some limitations and drawbacks to using this method.

DirectAccess Client Targeting

By default, the Getting Started Wizard applies DirectAccess client policies to all computers in the domain and filters the policy to apply only to mobile computers using a WMI filter. This assumes that all mobile computers in the organization should receive DirectAccess client settings. It also assumes that any nonmobile PCs, such as desktops or virtual machines, will not receive DirectAccess client settings. Often this is not the case. The application of DirectAccess client settings to all computers in the domain that have a mobile processor is often too broad, and further it prevents an administrator from knowing exactly which machines the DirectAccess client settings have been applied to.

Using a dedicated security group is ideal, because DirectAccess client settings can be targeted at specific machines with much more granularity. It allows for the application of DirectAccess client settings to non-mobile processor devices, such as desktop workstations and virtual machines. Security groups are also self-documenting, enabling administrators to quickly determine which systems have been provisioned for DirectAccess.

Network Location Server

Using the Getting Started Wizard automatically configures the DirectAccess server as the Network Location Server (NLS). With the NLS collocated on the DirectAccess server, taking the DirectAccess server offline at any time may prevent DirectAccess clients on the Internal network from connecting to local resources. This occurs because the client, not being able to reach the NLS, will believe it is outside the network, and the Name Resolution Policy Table (NRPT) will be enabled, preventing access to local resources by hostname. Enabling load balancing and configuring multisite also require the NLS to be installed on a separate system.

Although collocating the NLS on the DirectAccess server is acceptable for very small deployments, in most cases it is recommended that the NLS be hosted on another system and be made highly available.

IP-HTTPS Certificate

When DirectAccess is configured using the Getting Started Wizard, a self-signed certificate is created and provisioned for use with the IP-HTTPS IPv6 transition technology. Self-signed certificates provide little in terms of security, and they provide no inherent trust. Self-signed certificates are not managed, cannot be revoked, and cannot be rekeyed later, if required.

Client Support

Windows 7 clients are not supported when configuring DirectAccess with the Getting Started Wizard. This simplified deployment does not require a Public Key Infrastructure (PKI) to manage computer certificates for IPsec authentication and encryption. Instead, DirectAccess uses a component called the Kerberos Proxy on the DirectAccess server to authenticate to Active Directory as well as for IPsec encryption. Kerberos Proxy is only supported for clients with Windows 8 and later.

Deployment Flexibility

Most advanced deployment options—such as load balancing, multisite, strong user authentication, and force tunneling—will all require significant design changes in order to implement them after using the Getting Started Wizard. Often these changes will be disruptive. They may also require clients to be brought back to the corporate network, or connected out-of-band using traditional client-based VPN to receive the updated configuration.

Summary

For many, the Getting Started Wizard looks like the intuitive choice for configuring DirectAccess. The simplified deployment with reduced infrastructure requirements looks enticing, but from experience I can tell you it often causes more problems than it solves.

In some cases, using the Getting Started Wizard may be sufficient. For small deployments with limited requirements, the simplified deployment can be used without issue.

To address some of the challenges and shortcomings imposed by the Getting Started Wizard's restrictive default option selections, it is possible to edit many of the defaults prior to deployment. However, the process is cumbersome and unintuitive. If more than a few of these settings have to be changed, it is recommended that the Remote Access Setup Wizard be used instead. It provides much more granular control of configuration settings, offers better deployment flexibility for the future, and with the use of PKI is fundamentally more secure.

CHAPTER 5

Configure DirectAccess with the Remote Access Setup Wizard

In this chapter, DirectAccess will be configured using the Graphical User Interface (GUI), this time leveraging the Remote Access Setup Wizard instead of the Getting Started Wizard, as outlined in Chapter 4.

Using the Remote Access Setup Wizard provides several key advantages. It gives the administrator much more granular control over the initial configuration of DirectAccess. It also allows for flexible deployment configuration using optimal settings, and it provides crucial support for popular deployment options, such as Windows 7 client support.

Additionally, the Remote Access Setup Wizard lets the administrator deploy DirectAccess using common implementation best practices, such as using a security group for applying DirectAccess client settings, specifying a public SSL certificate for IP-HTTPS, and hosting the Network Location Server (NLS) on another server, just to name a few. It also exposes several advanced configuration settings, such as force tunneling, strong user authentication, management server definition, and end-to-end encryption.

Remote Access Setup Wizard

To launch the Remote Access Setup Wizard, open the Remote Access Management Console on the DirectAccess server. The Remote Access Management Console can be found by clicking on the **Start** menu and navigating to **All Apps ➤ Windows Administrative Tools ➤ Remote Access Management Console**. Expand **Configuration**, highlight **DirectAccess and VPN**, and then click **Run the Remote Access Setup Wizard** (Figure 5-1).



DirectAccess & VPN settings have not yet been configured. Select one of the wizard options.

Run the Getting Started Wizard

Use this wizard to configure DirectAccess and VPN quickly, with default recommended settings.

A Run the Remote Access Setup Wizard

Use this wizard to configure DirectAccess and VPN with custom settings.

Figure 5-1. Run the Remote Access Setup Wizard

Note The Getting Started Wizard and the Remote Access Setup Wizard will not appear if DirectAccess has already been configured.

Deployment Options

The Remote Access Setup Wizard provides three options for configuring DirectAccess and VPN (Figure 5-2).



Figure 5-2. Configure Remote Access

Deploy both DirectAccess and VPN (recommended)

Although the GUI suggests this option is "recommended," there are some very important reasons why VPN should not be installed on the DirectAccess server. The most critical reason is that it eliminates support for important scalability and performance features included in DirectAccess, namely null encryption for IP-HTTPS connections. Having VPN and DirectAccess on the same server also makes the solution more complex, especially when configuring redundancy for DirectAccess (load balancing and multisite). As such, this configuration should be avoided if possible.¹

Deploy DirectAccess only

This option should be selected.

Deploy VPN only

This is a book about DirectAccess, so this option is not applicable for our purposes.

Installing DirectAccess

To install DirectAccess without VPN, select the option to **Deploy DirectAccess only**. The Remote Access Setup Wizard will perform a prerequisites check to ensure essential supporting components are installed.

Note It is not uncommon to receive an error message at this point. Typical errors are IPv6 being disabled via the registry, WinRM not being configured, and IPv6 transition technologies being disabled. Resolve any issues before proceeding.

Once the prerequisite check is complete, a four-step deployment wizard is displayed (Figure 5-3).

¹The Web Application Proxy (WAP) role can also be configured on the same server as DirectAccess. Although technically supported, this too should be avoided if possible. The same reasons why VPN should not be installed on the DirectAccess server also apply to WAP. Best practice is to install DirectAccess on a server dedicated to the DirectAccess role.



Figure 5-3. Remote Access Setup Wizard's step-by-step deployment wizard

Step 1: Remote Clients

Step 1 of the Remote Access Setup Wizard allows the administrator to select the DirectAccess deployment scenario, choose which security groups the DirectAccess client settings Group Policy Object (GPO) will be applied to, and define settings for the Network Connectivity Assistant for Windows 8.x and Windows 10 clients.

Deployment Scenario

Click **Configure** under **Remote Clients** on **Step 1** to select a deployment scenario (Figure 5-4). There are two options to choose from:

- **Deploy full DirectAccess for client access and remote management.** Select this option to grant DirectAccess computers and logged-on users full, unrestricted access to the Internal network when connected remotely.
- **Deploy DirectAccess for remote management only.** Select this option to grant DirectAccess computers limited access to the Internal network when connected remotely. Choosing this option restricts access only to infrastructure services, such as domain controllers and system-management servers. Users cannot access any other internal resources. However, administrators on the Internal network can still initiate connections outbound to connected DirectAccess clients.

Sa Remote Access Setup		×
DirectAccess Clier Enable DirectAccess for	nt Setup managed computers in specified security groups, and configure client settings.	
Deployment Scenario Select Groups Network Connectivity Assistant	 Deploy DirectAccess to allow DirectAccess client computers located on the Internet to connect to internal network resources, and remotely manage DirectAccess clients. Select a deployment scenario: Deploy full DirectAccess for client access and remote management With this option selected, DirectAccess client computers located on the Internet can connect to the internal network via the Remote Access server. Administrators can remotely manage these clients. Deploy DirectAccess for remote management only Administrators can remotely manage DirectAccess client computers located on the Internet. With this option selected, DirectAccess is not deployed for client access to the internal network. 	
	< Back Next > Finish	Cancel

Figure 5-4. Select a DirectAccess deployment scenario

Note When selecting the remote management only scenario, the Network Connectivity Assistant (NCA) will not be displayed in the Windows 8.x or Windows 10 GUI. In addition, the DirectAccess Connectivity Assistant (DCA) v2.0 should not be deployed to Windows 7 clients in this scenario.

Select Groups

Click **Next** to select groups. Click **Add** to specify a domain security group for DirectAccess clients (Figure 5-5). Two additional options are also available for the administrator to enable. They are:

- Enable DirectAccess for mobile computers only. Selecting this option will configure a WMI filter on the DirectAccess client settings GPO to apply the settings only to computers that have a mobile processor.
- **Use force tunneling.** DirectAccess clients are configured to use split tunneling by default. In split-tunneling mode, DirectAccess clients can access resources on both the corporate network and the public Internet at the same time. Selecting this option will configure DirectAccess clients to use only the corporate proxy server, forcing all Internet traffic over the DirectAccess connection.

💐 Remote Access Setup		×
DirectAccess Clien Enable DirectAccess for	t Setup managed computers in specified security groups, and configure client settings.	1
Deployment Scenario	Select one or more security groups containing client computers that will be enabled for DirectAccess.	
Select Groups	CirectAccessClients (LAB\DirectAccessClients)	
Network Connectivity Assistant	Remove	ĺ
	 Enable DirectAccess for mobile computers only With this setting enabled, all mobile computers in the specified security groups will be enabled as DirectAccess clients. Use force tunneling DirectAccess clients connect to the internal network and to the Internet via the Remote Access server. 	
	< Back Next > Finish C	Cancel

Figure 5-5. Highlight Select Groups and optionally enable DirectAccess for mobile computers only and/or to use force tunneling

Note The use of force tunneling comes with some potential negative side effects. When force tunneling is enabled, all client Internet traffic is backhauled over the DirectAccess connection. The advantage is that web-browsing policies can be enforced by the on-premise proxy server. The disadvantage is that the additional overhead imposed by sending all web traffic over an encrypted connection (especially for HTTPS-protected websites, which are already encrypted) can result in a poor web-browsing experience for DirectAccess clients. Additionally, the use of strong user authentication is not supported when force tunneling is enabled.

Network Connectivity Assistant

Click Next to configure the Network Connectivity Assistant (NCA) (Figure 5-6).

Sa Remote Access Setup			×
DirectAccess Client Enable DirectAccess for m	: Setup nanaged computers in specified security gr	roups, and configure client settings.	1
Deployment Scenario Select Groups Network Connectivity Assistant	The Network Connectivity Assistant (I DirectAccess connectivity information Resources that validate connectivity to	NCA) runs on DirectAccess client computers to provide n, diagnostics, and remediation support. o internal network:	
	*	Туре	
	Helpdesk email address: DirectAccess connection name:	admin@richardhicks.net Workplace Connection	
	Allow DirectAccess clients to use l	ocal name resolution	
		< Back Next > Finish	Cancel

Figure 5-6. Configure the Network Connectivity Assistant

Note NCA settings apply only to Windows 8.x and Windows 10 clients. These settings are not used by Windows 7 clients. The DirectAccess Connectivity Assistant (DCA) v2.0 can optionally be deployed to provide similar functionality for Windows 7 clients, but must be configured separately. See "Chapter 9: Supporting Windows 7 Clients" for more information.

The **Resources that validate connectivity to the internal network** field is initially blank. Intuitively, information should be supplied here. However, it is not necessary (or recommended) to do so at this time. Resource validation is performed by Windows 8.x and Windows 10 clients by checking connectivity to this URL after the DirectAccess connection is made. During initial configuration, the DirectAccess deployment wizard will automatically populate this field with the URL http://DirectAccess-WebProbeHost, which is hosted on the DirectAccess server (a corresponding host record in DNS resolving to the internal IPv4 address of the DirectAccess server is also configured). This setting can later be changed after the initial configuration has been completed.

Note If multiple resources are entered here, all must validate successfully for the remote client to indicate that a successful DirectAccess connection has been made.

A help desk email address should be provided. Optionally, the administrator can change the DirectAccess connection name as it appears in the Windows 8.x and Windows 10 GUI. Also, the option to allow DirectAccess clients to use local name resolution can be enabled. Click **Finish** to complete Step 1.

Note If a help desk email address is not provided, it will not be possible to generate and collect troubleshooting information from Windows 8.x and Windows 10 clients.

Also, selecting the option to allow DirectAccess clients to use local name resolution allows the user to effectively disconnect the DirectAccess connection by clicking **Disconnect** on the Network Connectivity Assistant (NCA) GUI. However, only the Name Resolution Policy Table (NRPT) is disabled, leaving existing DirectAccess IPsec connections unaffected (new DirectAccess IPsec connections cannot be established until the computer is restarted). Administrators can still remotely manage DirectAccess clients when a user chooses to disconnect because IPsec tunnels are still established.

Step 2: Remote Access Server

Step 2 of the Remote Access Setup Wizard allows the administrator to select a network topology and provide a public name for the DirectAccess server, assign network adapters and choose an SSL certificate for IP-HTTPS connections, and specify user authentication methods.

Network Topology

Click **Configure** under **Remote Access Server** on **Step 2** to select a network topology (Figure 5-7). There are three options to choose from:

- **Edge**. Choose this topology when the DirectAccess server is configured with two network adapters and has a public IPv4 address assigned to the External interface.
- **Behind an edge device (with two network adapters)**. Choose this topology when the DirectAccess server is configured with two network adapters and has a private IPv4 address assigned to the External interface.
- **Behind an edge device (with a single network adapter)**. Choose this topology when the DirectAccess server is configured with a single network adapter.

Sa Remote Access Setup		×
Remote Acces Configure DirectA	ss Server Setup .ccess and VPN settings.	
Network Topology Network Adapters Authentication	Select the network topology of the server.	
	< Back Next > Finish Cano	cel

Figure 5-7. Select the network topology of the server

In addition, provide the public name or IPv4 address used by clients to connect to the remote access server.

Note Although this field will accept an IPv4 address, it is strongly recommended that a fully qualified domain name (FQDN) be used instead. This FQDN must resolve to the public IPv4 address assigned to the DirectAccess server when configured with the Edge topology, or to the public IPv4 address assigned to the border router or edge firewall when the DirectAccess server is configured behind an edge device.

Network Adapters

Click **Next** to configure network adapters (Figure 5-8).

💐 Remote Access Setup				×
Remote Access Configure DirectAcce	Server Setup ess and VPN settings.			
Network Topology Network Adapters	Select the network adapters o	n the Remote Access	s server.	
Authentication	Adapter connected to the ext	ernal network:	Adapter connected to the int	ernal network:
	External ~	Details	Internal \sim	Details
	203.0.113.240		172.16.1.240	
	Select the certificate used to authenticate IP-HTTPS connections: Use a self-signed certificate created automatically by DirectAccess			
	CN=*.richardhicks.net, OU=0	Domain Control Valid	lated	Browse
	Transition technolog	ies are enabled for IP	v4 support.	
			< Back Next >	Finish Cancel

Figure 5-8. Configure network adapters and select the IP-HTTPS SSL certificate

The wizard automatically detects network adapters based on their configuration. Assuming they are configured correctly, no changes should be required. Also, if a public SSL certificate is available and matches the public name specified in the previous step, it will be automatically selected.

Note If no suitable SSL certificate is found, the option of creating a self-signed certificate is selected. However, this should be avoided whenever possible.

Authentication

Click Next to configure authentication (Figure 5-9).

💐 Remote Access Setup		×
Remote Access Configure DirectAcc	s Server Setup cess and VPN settings.	1
Network Topology Network Adapters Authentication	Specify how DirectAccess clients authenticate. If computer certificates are not used for authentication, DirectAccess acts as a Kerberos proxy on behalf of the client. Enable support for Windows 7 clients. User Authentication	
	< Back Next > Finish	Cancel

Figure 5-9. Configure DirectAccess authentication

Select the option to use Active Directory credentials (username/password).

Note If two-factor authentication is required, it is still recommended to use Active Directory (AD) credentials for now. Configuring two-factor authentication is not trivial and is difficult to troubleshoot. It is best to ensure that DirectAccess is working with AD authentication alone first, then enable two-factor authentication afterward.

In addition to Active Directory credentials, it is recommended that computer certificates also be used for authentication. This will provide an additional level of security and assurance for DirectAccess clients and ensures maximum deployment flexibility in the future when enabling features that require certificate authentication.

To enable certificate authentication, select the option to **Use computer certificates**. If an intermediate Certification Authority (CA) is used to issue certificates to the DirectAccess server and clients, select the option to **Use an intermediate certificate** and click **Browse**. Select the certificate belonging to the CA that will be issuing certificates to the DirectAccess server and clients (Figure 5-10).

Wi	ndows Security Remote Acc	cess Setup	×
	Select a certific	ate.	
	<u>.</u>	LAB-ISSUING-CA Issuer: LAB-ROOT-CA Valid From: 2/26/2016 to 2/26/2026 <u>Click here to view certificate</u> <u>properties</u>	^
	? =	LAB-ROOT-CA Issuer: LAB-ROOT-CA Valid From: 2/26/2016 to 2/26/2036	
	<u>r</u>	Starfield Secure Certificate Authority - G2 Issuer: Starfield Root Certificate Authority - G2 Valid From: 5/2/2011 to 5/2/2031	
	₽ ₹	Starfield Root Certificate Authority - G2 Issuer: Starfield Class 2 Certification Authority Valid From: 12/31/2013 to 5/29/2031	
	₽ ≣	Starfield Class 2 Certification Authority Issuer: Starfield Class 2 Certification Authority Valid From: 6/29/2004 to 6/29/2034	l
	?	www.verisign.com/CPS Incorp.by Ref. LIABILITY LTD.(c)97 VeriSign Issuer: Class 3 Public Primary Certification Authority	×
		ОК	ancel

Figure 5-10. Select a CA certificate

Note It is important to understand that this is not the certificate issued to the DirectAccess server. It is the certificate issued to the CA that will be used to issue computer certificates to DirectAccess servers and clients. If there is more than one certificate for a given CA, ensure that the exact certificate is chosen. To confirm, click the link below the certificate and view the properties. Click the Details tab and select **Thumbprint**. Confirm this thumbprint matches that of the CA server's certificate.

Finally, if Windows 7 clients are to be supported, select the option to **Enable Windows 7 client** computers to connect via DirectAccess and click Finish.

Note Selecting the option to enable support for Windows 7 clients even for deployments that are exclusively Windows 8.x and Windows 10 is recommended for optimum security. This option forces machine certificate authentication for all DirectAccess clients.

Step 3: Infrastructure Servers

Step 3 of the Remote Access Setup Wizard allows the administrator to define a Network Location Server (NLS), configure DNS servers, define the DNS suffix search list, and specify management servers for use by DirectAccess clients.

Network Location Server

Click **Configure** under **Infrastructure Servers** on **Step 3** to configure a Network Location Server (Figure 5-11). There are two options to choose from:

- The network location server is deployed on a remote web server (recommended). This is the preferred configuration option.
- The network location server is deployed on the Remote Access server. This option should be avoided whenever possible.

Sa Remote Access Setup	>
Infrastructure S Configure infrastruc	Server Setup ture servers. DirectAccess clients access these servers before connecting to resources on the internal network.
Network Location Server DNS DNS Suffix Search List Management	Specify settings for the network location server, used to determine the location of DirectAccess client computers. A client computer connecting successfully to the site is assumed to be on the internal network, and DirectAccess is not used. () The network location server is deployed on a remote web server (recommended) Type in the URL of the network location server:
	https://nls.lab.richardhicks.net/ Validate The network location server is deployed on the Remote Access server Select the certificate used to authenticate the network location server: Use a self-signed certificate
	Browse Connectivity to URL https://nls.lab.richardhicks.net/ was validated successfully.
	< Back Next > Finish Cancel

Figure 5-11. Configure the Network Location Server (NLS)

Select the option to deploy the network location server on a remote web server. Enter the URL (including HTTPS://) and click **Validate**. Ensure that connectivity to the URL validates successfully.

Note For the network location server to be properly validated, the name of the NLS entered must match the subject name on the SSL certificate installed on the NLS web server.

DNS

Click Next to configure DNS settings for DirectAccess clients (Figure 5-12).

Sa Remote Access Setup				×
Configure infrastructure	Server Set ture servers.	up DirectAccess clients access these se	vers before connecting to resources on the internal networ	k
Network Location Server DNS DNS Suffix Search List Management	Ente the s DNS reso	r DNS suffixes and internal DNS sen pecified DNS server for name resolu servers are treated as exemptions, a lution.	ers. DirectAccess client queries that match a suffix use tion. Name suffixes that do not have corresponding nd DNS settings on client computers are used for name	
		Name Suffix	DNS Server Address	
	•	lab.richardhicks.net	2002:cb00:71f0:3333::1	
		nls.lab.richardhicks.net		
	•			
		ct a local name resolution option: Jse local name resolution if the nam Jse local name resolution if the nam inreachable when the client compu Jse local name resolution for any ki	e does not exist in DNS (most restrictive) e does not exist in DNS or DNS servers are ter is on a private network (recommended) nd of DNS resolution error (least restrictive)	
			< Back Next > Finish	Cancel

Figure 5-12. Configure DNS and select local name-resolution options

The settings here specify the configuration of the Name Resolution Policy Table (NRPT) on DirectAccess clients. The NRPT defines which DNS servers DirectAccess clients will use to resolve names in a particular namespace. The DirectAccess server's DNS suffix is automatically added and assigned a DNS server address. In addition, the name of the NLS is added but is not assigned a DNS server address. A name suffix without a corresponding DNS server address is effectively excluded, and DirectAccess clients will not be able to access this host (or resources in this namespace) over the DirectAccess connection.

Note DNS configuration is simple and straightforward when the internal and external namespaces are distinct. However, when split DNS is employed and the internal and external namespaces are the same, additional configuration is required. Any resources that should be reachable externally and not over the DirectAccess connection will need to be excluded. NRPT exclusions are defined as table entries for which no DNS server is defined (blank), such as the Network Location Server (NLS). Examples would include public-facing websites, mail services, unified communications, and so forth. Also, the public name of the DirectAccess server must be excluded.

To add additional DNS suffixes, double-click an empty field, enter the DNS suffix name, and then click **Detect** (Figure 5-13). This will automatically populate the correct DNS server address. To exclude a specific server or an entire namespace from the NRPT, perform these steps without entering a DNS server address.

5	DNS Se	erver Addresses	×
	DNS su	uffix:	
	azure.ri	ichardhicks.net	
	Exampl	le: corp.contoso.com	
	DNS se	erver IPv4 addresses:	
		Detect	
	•	2002:cb00:71f0:3333::1	_
	*	Validate	
	Examp	de: 157.60.41.211	
	_		
		Apply Cancel	

Figure 5-13. Configure the DNS server addresses

Note This method automatically populates the field with an IPv6 address ending in 3333::1. This IPv6 address is assigned to the Internal network interface of the DirectAccess server and is used by the DNS64 service. This is the preferred method for configuring DNS servers and ensures that DirectAccess clients always use the DNS64 service running on the DirectAccess server for name resolution.

Local name-resolution behavior using IPv6 Link Local Multicast Name Resolution (LLMNR) and NetBIOS over TCP/IP can also be configured. There are three local name-resolution options to choose from. They are:

- Use local name resolution if the name does not exist in DNS (most restrictive). This option is the most secure. When this option is selected, DirectAccess clients will only use local name resolution for host names that can't be resolved by internal DNS servers. However, if a host name can be resolved, or the internal DNS servers are not available, local name resolution will not be used.
- Use local name resolution if the name does not exist in DNS or DNS servers are unreachable when the client computer is on a private network (recommended). This is the recommended option and provides reasonable security, as it only allows the use of local name resolution on a private network when internal DNS servers are unavailable.
- Use local name resolution for any kind of DNS resolution error (least restrictive). This option provides the least security. If internal DNS servers are unavailable, or if any type of DNS error is encountered, local name resolution will be used.

DNS Suffix Search List

Sa Remote Access Setup		X
Infrastructure Se Configure infrastructure	rver Setup re servers. DirectAccess clients access these server	s before connecting to resources on the internal network.
Network Location Server DNS DNS Suffix Search List Management	Add additional suffixes to search for short un suffix, the other suffixes are appended to the	nqualified name in multiple locations. If a query fails for a e name and the DNS query is repeated for the alternate FQDN.
	Configure DirectAccess clients with Divs	Domain suffixer to use
	Ada <- Re	d -> emove
	New	/ Suffix: Add
	(1) The primary domain DNS suffix app	eears first in the list.

Click Next to configure the DNS suffix search list (Figure 5-14).

Figure 5-14. Configure the DirectAccess client DNS suffix search list

The option to **Configure DirectAccess clients with DNS client suffix search list** is enabled by default. This is recommended to ensure that DirectAccess clients can properly resolve single-label hostnames using internal DNS servers. To include additional DNS suffixes, enter a new suffix name and click **Add**.

Management

Click **Next** to configure management servers (Figure 5-15). Management servers are reachable by the DirectAccess client without requiring a user to be logged on. These may include patch-management servers, remediation servers, or any other server that must be accessible to the DirectAccess server prior to user logon.



Figure 5-15. Configure the DirectAccess management servers

To add a management server, double-click a blank entry and provide the hostname or IPv4 address of the internal management server and click **OK** (Figure 5-16). Once complete, click **Finish**.

San Add a	a Management Server	×
Specify	fy the computer name or IPv4 address:	
Cor	omputer name (FQDN):	
	epo.lab.richardhicks.net	
	Example: engineeringcomputer1.contoso.com	
⊖ IPv	Pv4 address	
	Example:	
	157.60.79.2	
	ОК	Cancel

Figure 5-16. Add a management server

Note It is not necessary to enter names or IP addresses for management servers that register SRV records in DNS. For example, management servers running Windows Server Update Services (WSUS) or System Center Configuration Manager (SCCM) will automatically be discovered and added to the management servers list during initial DirectAccess configuration. This may apply to some third-party management platforms as well.

Finish and Apply Changes

At the completion of Step 3, configuration changes can be applied by clicking **Finish** in the lower-right corner of the Remote Access Management console. This brings up a window that provides a summary of the remote access configuration settings (Figure 5-17).

Sa Remote A	ccess Review			-		×
	Remote Access Review					
	Summary of Remote Access conf	iguration settings.				
Review the c	configuration settings.					^
📑 GPO	Settings Change					
LAB						
Direc	tAccess server GPO name:	DirectAccess Server Setting	s			
Client	t GPO name:	DirectAccess Client Settings				
Semo •	DirectAccess is deployed for c	lient access and remote clien	t management			
•	DirectAccess security groups:					
	KAB\DirectAccessClients					
:	Force tunneling is disabled Resource used to verify interna	al network connectivity:				~
			Save to a file Print	Apply	Cance	el

Figure 5-17. Summary of DirectAccess configuration settings

By default, the Remote Access Setup Wizard will name the DirectAccess client and server settings GPOs **DirectAccess Client Settings** and **DirectAccess Server Settings**, respectively. If different names are desired, click **Change** next to **GPO Settings** and provide new GPO names as required. If prestaged GPOs are to be used, click **Browse** and select them accordingly (Figure 5-18).

SPO Na	ames		×
	GPO Names		
	GPOs that will be used for Di	irectAccess deployment.	1
Review the settings if re	GPOs that will be applied to the client quired.	computers security group and the DirectAccess server in the relevant domains. Modify GPO	
0	DirectAccess client GPO		
-	GPO containing DirectAccess client	settings:	
	LAB	DirectAccess Client Settings Browse 🥑 *	
	Direct Access server GPO GPO containing Direct Access server	r settings:	
	LAB	DirectAccess Server Settings Browse	
• - A new •• - Use ex	v Group Policy Object (GPO) will be cre visting Group Policy Object	eated	
		OK Car	ncel

Figure 5-18. Edit the GPO settings

After reviewing the configuration settings, click **Apply**. Once the configuration has been applied successfully, click **More Details** to review warning messages, if any were raised (Figure 5-19).



Figure 5-19. Configuration status window

All of the changes made using the Remote Access Setup Wizard are implemented using PowerShell commands. These commands can be saved as a PowerShell script by right-clicking anywhere in the window and choosing **Copy script** (Figure 5-20).

oplying Remote Access Setup Wizard Settings		
Applying Remote Access Setup	Wizard Settings	
Remote Access will be updated with configur	ation settings.	
The configuration was applied success	sfully.	
 Less details 	Close	
Initializing operations before applying config Preparing to apply configuration change Racking up GPOs	guration	^
backing up on os		
- Configuring Remote Access settings	Сору	T
Configuring Remote Access settings Retrieving server GPO details	Copy Copy script	
Configuring Remote Access settings Clearing existing stale configuration Clearing existing stale configuration Checking the specified adapters Checking the network location server	Copy Copy script Auto scroll certificate	
Configuring Remote Access settings Q Configuring Remote Access settings Q Retrieving server GPO details Q Clearing existing stale configuration Q Checking the specified adapters Q Checking the network location server Q Checking the network location server	Copy Copy script Auto scroll centricate URL	
Configuring Remote Access settings Clearing existing stale configuration Clearing existing stale configuration Checking the specified adapters Checking the network location server Checking the network location server Checking the specified adapters	Copy Copy script Auto scroll certificate URL	
Configuring Remote Access settings Clearing existing stale configuration Clearing existing stale configuration Checking the specified adapters Checking the network location server Checking the network location server Checking the specified adapters Checking the specified adapters Checking the specified adapters	Copy Copy script Auto scroll centricate URL t	
Configuring Remote Access settings Clearing existing stale configuration Clearing existing stale configuration Checking the specified adapters Checking the network location server Checking the network location server Checking the specified adapters Checking the specified adapters Checking the specified adapters Checking for a native IPv6 deployment Verifying the IP-HTTPS certificate Retrieving internal network DNS settin	Copy Copy script Auto scroll certificate URL t	~

Figure 5-20. Generate the PowerShell script

Once the script has been copied, paste the contents of the clipboard into a new text file and save it (Figure 5-21).

🗐 da_config - Notepad	-		×
File Edit Format View Help			
Install-RemoteAccess -NoPrerequisite -Force -PassThru -ServerGpoName 'lab.richardhick	s.net	Direc	tA ^
Set-DAServer -IPsecRootCertificate ([System.Byte[]]@(48,130,3,217,48,130,2,193,160,3,	2,1,2	,2,19,	79
247, 5, 56, 109, 124, 223, 230, 150, 48, 68, 6, 3, 85, 29, 31, 4, 61, 48, 59, 48, 57, 160, 55, 160, 53, 134, 51	,104,	116,11	
45,61,152,159,8,196,149,240,201,207,154,58,0,132,20,255,18,216,239,178,251,244,30,44,	61,58	,89,11	.7,
Add-DAClientDnsConfiguration -DnsSuffix '.azure.richardhicks.net' -DnsIPAddress @('20	02:cb	00:71	0:
Add-DAClient -SecurityGroupNameList @('LAB\DirectAccessClients') -Verbose -ComputerNa	me 'e	dge1.]	lab
Remove-DAClient -SecurityGroupNameList @('lab.richardhicks.net\Domain Computers') -Ve	rbose	-Comp	out
Set-DAClient -Downlevel 'Enabled' -OnlyRemoteComputers 'Disabled' -Verbose -ComputerN	ame '	edge1.	la
Set-GPRegistryValue -Type 'String' -Value 'lab.richardhicks.net,azure.richardhicks.ne	t'-N	ame '[)ir
Set-GPRegistryValue -Type 'String' -Value 'lab.richardhicks.net,azure.richardhicks.ne	t'-N	ame '[)ir
Set-DAClientExperienceConfiguration -FriendlyName 'Workplace Connection' -PreferLocal	Names	Allowe	d
\$			>

Figure 5-21. Save the PowerShell script

Confirm Policy Application

Once the DirectAccess configuration is complete and the settings have been applied, highlight **Operations Status** in the navigation tree of the Remote Access Management Console to view the DirectAccess server's **Operations Status** (Figure 5-22). The **Operations Status** for all DirectAccess-supporting services should indicate **Working** and have a green check next to them.

Configuration DirectAccess and VPN	Operations Status					Tasks	^
Dashboard	Operations Status				^	Refresh	
M Operations Status	Name	Chabur	Save	Occupitors State		Configure Refresh interval	
Remote Client Status	edge1.lab.richardhicks.net DirectAccess	Working Working	16 minutes, 37 seconds 16 minutes, 37 seconds	operations state		View Performance Counters	
edge1	Services	Working Working Working Working Working Working Working Working Working	21 minutes, 37 seconds 21 minutes, 38 seconds 21 minutes, 38 seconds			Disable Connectivity Check (PING)	
	Details edge1.lab.richardhicks.ne	et: Working prope	erly		^		

Figure 5-22. DirectAccess server operation status

Step 4: Application Servers (Optional)

Step 4 of the Remote Access Setup Wizard is optional. By default, DirectAccess client communication is authenticated and encrypted only between the DirectAccess client and the server. Communication between the DirectAccess server and hosts on the Internal network is not authenticated or encrypted.

If full end-to-end authentication—and, optionally, encryption—from the DirectAccess server to specific application servers is required, click **Edit** under **Application Servers** on **Step 4**. Select the option to **Extend authentication to selected application servers**, click **Add**, and specify an Active Directory security group that includes servers requiring end-to-end authentication (Figure 5-23).

Si Remote	Access Setup	×
1	DirectAccess Application Server Setup Optionally configure authentication between DirectAccess clients and internal application servers.	
 Do no Extension Seletion 	ot extend authentication to application servers ad authentication to selected application servers set the security groups containing the servers:	^
28,	Application Servers (LAB\Application Servers) Add Remove	
With	Allow access only to servers included in the security groups th this option enabled, clients can only access application servers in the specified security groups. Clients can still access astructure servers, including domain controllers, DNS servers, and servers used for DirectAccess client management.	
Witi enc	Do not encrypt traffic. Use authentication only this setting encrypted. This option is less secure. Authentication without the this setting enabled, end to end traffic is authenticated but not encrypted. This option is less secure. Authentication without cryption is supported only for application servers running Windows Server 2008 R2 or a later operating system.	
4	IPv6 addressing is required to enable additional end to end authentication.	~
	Finish Cancel	

Figure 5-23. Extend authentication to selected application servers

Two additional configuration options are available to choose from. They are as follows:

- Allow access only to servers included in the security groups. Select this option to allow DirectAccess clients to access only the internal application servers included in the defined security groups. DirectAccess clients will still be able to access infrastructure and management servers.
- **Do not encrypt traffic. Use authentication only**. Select this option if only authentication is required and not encryption. Application servers must be running Windows Server 2008 R2 or later to support this option.

Note When configuring DirectAccess end-to-end authentication and encryption, application servers must be configured with an IPv6 address. If IPv6 has not been deployed on the Internal network, the ISATAP IPv6 transition protocol can be used for deployments where it is supported.

Summary

Using the Remote Access Setup Wizard is the recommended and preferred method for configuring DirectAccess. It allows more-granular configuration than the Getting Started Wizard does and, crucially, provides the ability to support more-advanced deployment scenarios. It is required for configuring DirectAccess to support Windows 7 clients, and to implement DirectAccess using configuration best practices, such as using security groups for deploying client settings, using a public SSL certificate for IP-HTTPS, and hosting the NLS on another server. Also, using the Remote Access Setup Wizard is necessary in order to configure advanced settings like force tunneling, strong user authentication, and end-to-end encryption.

CHAPTER 6

Configure DirectAccess Load Balancing

For many organizations, providing secure remote access is vital to the productivity of remote employees. Ensuring that the solution is highly available is critical, and eliminating single points of failure is crucial to making sure that planned or unplanned outages do not prevent mobile workers from accessing resources on the corporate network when they are outside the office.

In addition, many DirectAccess deployments require more than one server in order to adequately meet demands when supporting large numbers of connected DirectAccess clients.

To address both availability and scalability requirements, DirectAccess supports load balancing using either native Windows Network Load Balancing (NLB) or an external load balancer (ELB). With load balancing enabled and configured, single points of failure are eliminated and essential redundancy is provided. In addition, capacity can be added to support more DirectAccess clients, if required.

Load Balancing

In generic terms, load balancing is a concept where network traffic is distributed among multiple redundant systems for a variety of purposes. First is the obvious: improving availability. If multiple systems are available to process requests and one becomes unavailable for any reason (planned or unplanned), service is not interrupted, as other systems are available to handle the load. The second, and less obvious reason, is scalability. If one system does not have the capacity to handle all of the requests, additional capacity can be added by adding more servers.

DirectAccess Load Balancing

DirectAccess supports load balancing using either Windows Network Load Balancing (NLB) or a physical or virtual external load balancer (ELB).

Windows Network Load Balancing

Windows Network Load Balancing is a feature of the Windows Server 2016 operating system and is designed to distribute network traffic evenly to all hosts in the load-balanced cluster. It is a simple and cost-effective way to provide local redundancy for DirectAccess. A maximum of eight nodes are supported in a single DirectAccess server cluster with NLB.

NLB for DirectAccess supports two distinct operating modes: unicast (default) and multicast. Each has its own advantages and disadvantages.

Unicast Operating Mode

When NLB is enabled, the default operating mode is set to unicast. In this mode, the MAC address of each host in the cluster is overwritten with a common MAC address. Additionally, NLB prevents the network switch from learning this MAC address. By design, this induces switch flooding, which allows all hosts in the NLB cluster to "see" all traffic. The NLB driver then decides which host in the cluster will process the incoming request.

Multicast Operating Mode

NLB can also be configured in multicast operating mode. In this mode, each host in the cluster retains its original MAC address, and a multicast MAC address is assigned to the cluster's IPv4 address. In many environments, network routers will not deliver packets to a unicast IPv4 address associated with a *multicast* MAC address, so creating a static Address Resolution Protocol (ARP) entry on the router for the subnet where the DirectAccess servers reside is often required.

Note NLB in multicast operating mode is required when the DirectAccess server is hosted in a VMware virtual environment. Details about how to configure NLB in multicast operating mode are covered later in this chapter.

NLB Drawbacks

NLB is simple and effective, but it comes with some potential drawbacks. DirectAccess is limited to eight nodes when using NLB, but four nodes should be considered the practical limit. In addition, NLB operates at Layer 2 of the Open Systems Interconnection (OSI) model.¹ Cluster members communicate with each other via heartbeat messages. These heartbeats are broadcast by all nodes in the cluster once per second, and all hosts on the network segment receive this traffic, including those that are not part of the cluster. This results in a lot of noise on the network, which can degrade network performance. NLB also consumes valuable CPU cycles on the DirectAccess server, which can negatively impact performance. All of these problems become exponentially worse as more hosts are added to the cluster.

Note For more information about Windows Network Load Balancing, see **Overview of Network Load Balancing** on Microsoft TechNet (https://technet.microsoft.com/en-us/library/cc725691.aspx).

External Load Balancer

A better choice to provide load balancing for DirectAccess servers is to use a dedicated, purpose-built loadbalancing appliance. External load balancers operate at Layers 3–7 of the OSI model and provide better performance than NLB does. In addition, external load balancers offer more intelligent traffic distribution and provide better visibility compared to NLB. A maximum of 32 nodes are supported in a single DirectAccess server cluster with an external load balancer.

https://en.wikipedia.org/wiki/OSI_model.
The external load balancer can be physical or virtual. A physical appliance is recommended for optimum performance. Virtual appliances work well for smaller deployments.

Capacity Planning

When designing a load-balanced architecture, ensure that enough capacity exists, even in a failure state. For example, if two load-balanced servers are running at 70 percent capacity and one fails, the remaining server will not have enough reserve capacity to handle both its load and the failed server's load. The result will be a total outage, with the first server being overrun with requests.

Ideally, the load-balanced system should be designed such that a single server failure will not result in overloading the remaining servers. For example, if three servers are load-balanced, and each is running at 25 percent utilization, a failure of one server will result in increased utilization on the remaining servers, but they will still have enough reserve capacity to handle the additional load.

Preparing for Load Balancing

By definition, load balancing implies that there will be at least two servers. Before adding another DirectAccess server to create a cluster, the new server must be prepared as outlined in Chapter 3. It must have Windows Server 2016 installed and configured, it must be joined to the domain, and it must have the necessary certificates installed. It must also have the DirectAccess role installed.

Important DO NOT configure DirectAccess on the second server! Install the DirectAccess-VPN role only. The server will be added to the cluster and configured from the first server.

Add NLB Feature

Adding the NLB feature can be accomplished using either the GUI or PowerShell. PowerShell is the preferred method for installing the feature, as it takes only a single PowerShell command to install the role and management tools.

Note It is not necessary to install the NLB feature when using an external load balancer.

PowerShell

To install the NLB feature, open an elevated PowerShell window on the DirectAccess server and enter the following command:

Install-WindowsFeature NLB -IncludeManagementTools

Note Repeat this step on each DirectAccess server that will be joined to the cluster.

GUI

To install the NLB feature using the GUI, open the **Server Manager** on the DirectAccess server, click **Manage** in the upper-right corner of the window, and then click **Add Roles and Features**. Click **Next**, choose **Rolebased or feature-based installation**, and click **Next**. Choose **Select a server from the server pool** and click **Next** twice, then select the **Network Load Balancing** feature (Figure 6-1).



Figure 6-1. Select the Network Load Balancing feature

Click **Add Features** when prompted to add features that are required for Network Load Balancing (Figure 6-2) and click **Next**.

Add features that are requ Balancing?	ired for Network Load
he following tools are required t ave to be installed on the same s	o manage this feature, but do not server.
 Remote Server Administration Feature Administration To [Tools] Network Load 	n Tools ols Balancing Tools

Figure 6-2. Add features required for Network Load Balancing

Confirm installation selections and click Install (Figure 6-3).

Add Roles and Features Wiz	ard	-		Х
Confirm installa	tion selections	DESTIN. edge2.lab.ri	ATION SER ichardhicks	VER
Before You Begin Installation Type Server Selection Server Roles	To install the following roles, role services, or features on selected server, Restart the destination server automatically if required Optional features (such as administration tools) might be displayed on th been selected automatically. If you do not want to install these optional f their check boxes.	click Install. nis page because t features, click Prev	they have vious to c	lear
Features	Natural Land Palacian			
Confirmation Results	Remote Server Administration Tools Feature Administration Tools Network Load Balancing Tools			
	L Export configuration settings Specify an alternate source path			
	< Previous Next >	Install	Cance	el

Figure 6-3. Confirm your installation selections

Hyper-V and NLB

Special consideration is required when enabling NLB on DirectAccess servers hosted in a Hyper-V virtual environment. By default, Hyper-V virtual switches will not send or receive traffic for hosts where the MAC address has been changed in the operating system, which happens when NLB is configured in unicast operating mode. To resolve this issue, MAC address spoofing must be enabled on each DirectAccess server virtual network interface. To do this, open the Hyper-V manager and right-click **Settings** on the DirectAccess virtual server. Expand **Network Adapter** and highlight **Advanced Features**. Check the box next to **Enable MAC address spoofing** (Figure 6-4). Repeat this process for each network adapter on the DirectAccess server and on each DirectAccess server that will be part of the cluster.



Figure 6-4. Enable MAC address spoofing

Enable Network Load Balancing (NLB)

To enable load balancing using Windows Network Load Balancing, open the Remote Access Management console on the first DirectAccess server, highlight **DirectAccess and VPN** in the navigation tree, and click **Enable Load Balancing** under **Load Balanced Cluster** in the **Tasks** pane (Figure 6-5).



Figure 6-5. Enable load balancing

Note To enable load balancing on a multisite DirectAccess entry point, highlight the entry point in the navigation tree and click **Enable Load Balancing** under **Load Balanced Cluster** in the **Tasks** pane.

Click Next and choose Use Windows Network Load Balancing (NLBn (Figure 6-6).

Enable Load Balancing	>
Load Balancing M	lethod
Before You Begin	Select a load balancing method for this cluster.
Load Balancing Method	Use Windows Network Load Balancing (NLB)
External DIPs	O Use an external load balancer
	< Previous Next > Commit Cancel

Figure 6-6. Select a load-balancing method

The existing dedicated IP address (DIP) assigned to each network interface on the *first* DirectAccess server will become the virtual IP address (VIP) for the cluster.² A new dedicated IP address for the DirectAccess server must then be assigned (Figures 6-7 and 6-8). Provide new IP addresses to be assigned to this DirectAccess server and click **Next**.

²https://www.youtube.com/watch?v=3tdqgY9Y-uo

CHAPTER 6 CONFIGURE DIRECTACCESS LOAD BALANCING

Before You Begin	Configure dedi enabled, the cu	cated IP addresses (DIPs) for the server external adapter. With load balancing rrent primary DIPs of the network adapters will be used as the virtual IP
External DIPs	addresses (VIPs) for the load balanced cluster.
nternal DIPs	IPv4 address:	203.0.113.241
		Example: 203.0.113.18
	Subnet mask:	255.255.255.0
		Example: 255.255.0.0

Figure 6-7. Configure a new external dedicated IP address

CHAPTER 6 CONFIGURE DIRECTACCESS LOAD BALANCING

Sa Enable Load Balancing			×
Internal Dedicated	l IP Address	ses	
Before You Begin Load Balancing Method External DIPs	Configure dedic enabled, the cu addresses (VIPs	ated IP addresses (DIPs) for the server internal adapter. With load balancing rrent primary DIPs of the network adapters will be used as the virtual IP) for the load balanced cluster.	
Internal DIPs	IPv4 address:	172.16.1.241	
Summary		Example: 10.0.0.18	
Completion	Subnet mask:	255.255.255.0 Example: 255.255.0.0	
		< Previous Next > Commit Cancel	

Figure 6-8. Configure a new internal dedicated IP address

Confirm the load-balancing settings and click **Commit** (Figure 6-9).

Sa Enable Load Balancing			×
Summary			
Before You Begin Load Balancing Method	Confirm load balancing settings		
External DIPs	Load balancing method:	Windows Network Load Balancing (NLB)	
Internal DIPs	External DIPs:	203.0.113.241/255.255.255.0	
Summary	External VIPs:	203.0.113.240/255.255.255.0	
Completion	Internal DIPs:	172.16.1.241/255.255.255.0; 2002:cb00:71f0:3333::1/128	
	Internal VIPs:	172.16.1.240/255.255.255.0	
		< Previous Next > Commit (Cancel

Figure 6-9. Confirm load-balancing settings

Note Initial configuration of NLB for DirectAccess must ALWAYS be performed using the Remote Access Management console. NLB settings are managed exclusively by DirectAccess. Initial configuration of NLB should NEVER be performed using the native Network Load Balancing manager. Once NLB has been configured, viewing the NLB status and changing the cluster operation mode using the NLB manager is acceptable.

VMware and NLB

Special consideration is required when enabling NLB on DirectAccess servers hosted in a VMware virtual environment. NLB operates in unicast mode by default, and all nodes in the cluster share the same MAC address. In physical environments, the operating system masks the MAC address for outgoing traffic, preventing the switch from learning it. This induces switch flooding, which is by design and is crucial to the operation of NLB. However, the VMware hypervisor knows the virtual server's MAC address and proactively shares that information with the virtual switch when the virtual machine starts. Fundamentally, this breaks NLB and results in all cluster traffic being delivered to a single node in the cluster.

To resolve this issue, it will be necessary to change the default NLB operation mode from unicast to multicast. To do this, it will be necessary to install the Network Load Balancing Manager on a separate Windows system. The NLB manager can be installed on Windows client operating systems by installing the Remote Server Administration Tools (RSAT),³ or on any Windows Server 2012 R2 or Windows Server 2016 host by opening an elevated PowerShell command window and entering the following command:

Install-WindowsFeature RSAT-NLB

Once complete, open the Network Load Balancing manager, choose **Cluster** from the drop-down menu, and then choose **Connect to existing**. Enter the hostname of the DirectAccess server and click **Connect** (Figure 6-10). Select the **Internal DA cluster** and click **Finish**. For dual-NIC deployments, repeat these steps for the **Internet DA cluster**.

Connect t	o Existing : C	onnect				×
Connect	t to a host and	select a cluster on	that host			
Host:	edge1]	Connect	
Conne	ection status ected					
Clusters	r name	Cluster IP	Interface nar	ne		
Interna	al DA cluster	172.16.1.240	Internal			
Interne	et DA cluster	203.0.113.240	External			
		< Back	Finish	Cancel	Help	

Figure 6-10. Connect to thr DirectAccess NLB clusters

³The Remote Server Administration Tools for Windows 10 can be downloaded here: https://www.microsoft.com/ en-us/download/details.aspx?id=45520

CHAPTER 6 CONFIGURE DIRECTACCESS LOAD BALANCING

Expand **Network Load Balancing Clusters**, then right-click **Internal DA cluster** and choose **Cluster Properties**. Select the **Cluster Parameters** tab and choose **Multicast** for the cluster operation mode (Figure 6-11). For dual-NIC deployments, repeat these steps for the **Internet DA cluster**.

uster IP Addresses	Cluster Parameters	Port Rules
Cluster IP configur	ation	
IP address:	172.16.1	1.240 ~
Subnet mask:	255 . 2	255.255.0
Full Internet name	Internal D	DA cluster - {D6
Network address:	03-bf-ac-	-10-01.f0
Multicast		
IGMP multicas	t	
		OK Canad Hal

Figure 6-11. Enable the Multicast cluster operation mode

Note For detailed information about running NLB on VMware, visit https://kb.vmware.com/kb/1556.

Add DirectAccess Servers

Once load balancing has been enabled for DirectAccess, additional servers can be added to the cluster to increase capacity and provide redundancy. To add a DirectAccess server to the cluster, open the Remote Access Management console on the first DirectAccess server, highlight **DirectAccess and VPN** in the navigation tree, and click **Add or Remove Servers** under **Load Balanced Cluster** in the **Tasks** pane. Click **Add Server** and enter the hostname of the second DirectAccess server, then click **Next** (Figure 6-12).

Note To add a server to a multisite DirectAccess entry point, highlight the entry point in the navigation tree and click **Add or Remove Servers** under **Load Balanced Cluster** in the **Tasks** pane.

elect Server		
Select Server	Select the Remote Access server to be added to the	e load balanced cluster.
Network Adapters	Server name:	
Completion	edge2	Browse

Figure 6-12. Add a remote access server to a load-balanced cluster

Reminder Ensure that servers being added to the DirectAccess cluster are properly configured and meet all installation prerequisites prior to adding the. Most important, the DirectAccess-VPN and NLB roles must be installed but not configured. In addition, ensure that all required certificates (IPsec and IP-HTTPS) are in place before proceeding.

Review the network adapter and IP-HTTPS certificate settings and click Next (Figure 6-13).

Select Server	Select the network adapt	ers that connect to th	e external and internal netv	vork.
Network Adapters Summary	External adapter:		Internal adapter:	
Completion	External	v	Internal	v
	Select the certificate used	d to authenticate IP-H	TTPS connections.	Details
	CN=*.richardhicks.net, C	IU=Domain Control Va	lidated	Browse

Figure 6-13. Confirm network adapter and IP-HTTPS certificate settings

Confirm the server settings and then click **Add** and **Close**. To add more servers, click **Add Server** and repeat the process as necessary. Once finished, click **Commit** (Figure 6-14).

Add or Remove S	ervers				
dd or remove servers from a loa	d balanced cluster.	The cluster must c	contain at least	one server.	
Server Name	External Adapter	Internal Adapter	VPN Static Po	lool	
EDGE1.LAB.RICHARDHICKS.NET	External	Internal			
edge2.lab.richardhicks.net	External	Internal			
			Г	Add Server	Remove Server

Figure 6-14. Add or remove servers from a load-balanced cluster

Enable External Load Balancer (ELB)

Enabling load balancing for DirectAccess using an external load balancer (ELB) is similar to configuring NLB. However, the NLB role does not need to be installed when enabling ELB. To configure ELB, follow the steps outlined previously for enabling NLB, this time choosing the option to **Use an external load balancer** (Figure 6-15).

Sa Enable Load Balancing		×
Load Balancing M	ethod	
Before You Begin Load Balancing Method External DIPs Internal DIPs Summary Completion	Select a load balancing method for this cluster. O Use Windows Network Load Balancing (NLB) Use an external load balancer	
	< Previous Next > Commit C	ancel

Figure 6-15. Select a load-balancing method

VIP Assignment

As described earlier in this chapter, the DIPs on the first DirectAccess server become the VIPs for the cluster. However, unlike NLB, the ELB VIP is not actually assigned anywhere. Rather, it is reserved for use on the ELB device, if necessary.

Assigning the VIP to the ELB is optional. For example, a common DirectAccess network topology has the External network interfaces residing in a perimeter or DMZ network. The ELB has a public IPv4 address assigned as a VIP, with the perimeter/DMZ DIPs of the DirectAccess servers configured as pool members.

There is no need to load balance the *Internal* network interfaces when the DirectAccess servers are configured with two network interfaces, unless the web-probe host URL is being hosted on the DirectAccess servers. In this scenario, assign a different resource for the web-probe host (*DirectAccess and VPN configuration, Step 1n Network Connectivity Assistant*). Alternatively, the VIP can be assigned to the ELB, and TCP port 80 can be load balanced to the Internal network interface of each DirectAccess server.⁴

⁴https://directaccess.richardhicks.com/2014/08/12/directaccess-clients-in-connecting-statewhen-using-external-load-balancer/

Load Balancer Configuration

Prescriptive guidance for configuring the external load balancer itself differs greatly between vendors and is outside the scope of this book. However, in general terms, configuring an external load balancer for DirectAccess is fundamentally the same as load balancing a secure web server. The external load balancer should be configured to load balance HTTPS traffic on TCP port 443. It should also be configured to perform SSL bridging; SSL termination (offloading) is not supported.⁵ The external DIPs of each DirectAccess server are configured as pool members. Consult the load balancer vendor for detailed information.

Note Load balancing for Teredo traffic isn't recommended, because it is complex and prohibitively difficult to implement correctly. If load balancing for Teredo is required, configuration guidance can be found here: https://www.f5.com/pdf/deployment-guides/f5-uag-dg.pdf.

Summary

Enabling DirectAccess load balancing allows administrators to improve availability for the remote access solution by eliminating single points of failure in their architecture. It also provides important scalability to accommodate large deployments where many DirectAccess clients will be supported.

NLB can be deployed quickly and is a cost-effective way to improve reliability. However, NLB has some potentially serious drawbacks, especially for large deployments. In practice, NLB should be considered for small to mid-sized deployments only. An external load balancer should be deployed for the best overall experience.

⁵Some load balancers can be configured to provide SSL offload for DirectAccess IP-HTTPS traffic. Although not supported, it can be an effective way to improve performance and scalability on DirectAccess servers in some scenarios. More details can be found here: http://directaccess.richardhicks.com/2013/07/10/ssl-offload-for-ip-https-directaccess-traffic-from-windows-7-clients-using-f5-big-ip/.

CHAPTER 7

Configure DirectAccess Geographic Redundancy

Where load balancing provides local redundancy and high availability, multisite DirectAccess provides geographic redundancy and failover for DirectAccess clients across multiple locations. If an outage occurs that affects all DirectAccess servers in one location—for example, a datacenter's connection to the Internet fails—DirectAccess clients will still be able to connect to an entry point in another location.

Multisite DirectAccess also accommodates geographically dispersed clients. If an organization has DirectAccess clients connecting from many different regions, the DirectAccess experience is improved when those clients can connect to an entry point closer to their physical location.

Client Support

Multisite DirectAccess can be leveraged by all supported DirectAccess clients. However, not all multisite features are available to all of them.

Windows 8.x and Windows 10

Windows 8.x and Windows 10 clients are aware of all entry points in the organization. When a Windows 8.x/10 client initiates a DirectAccess connection, it will check the status of all entry points and connect to the closest one. "Closest" is defined as the entry point that responds the quickest to a probe sent automatically by the client.

Optionally, an administrator can allow Windows 8.x and Windows 10 clients to manually select an entry point to connect to, if required.

Windows 7

Windows 7 clients can be provisioned in a multisite deployment, but their functionality is limited. Windows 7 clients must be assigned to a specific entry point and are unaware of other entry points in the organization. They will always connect to their assigned entry point and will not fail over.

Note There's a common misconception that Windows 7 clients can transparently fail over to another entry point if a Global Server Load Balancer (GSLB) is used. A Windows 7 client can't establish a DirectAccess connection just because the entry point's public hostname can be resolved to another entry point. Using GSLB to point the client to another entry point only swings the IPv6 transition tunnel to the new entry point. However, the DirectAccess client still expects to connect to its assigned DirectAccess servers using specific IPv6 addresses. Although the Windows 7 client will successfully establish a transition tunnel, the tunnel endpoint IPv6 addresses inside the transition tunnel will be incorrect, and IPsec will fail. This will prevent access to internal resources.

Preparing for Multisite

A number of prerequisites must be in place prior to implementing multisite DirectAccess. Considerations for DirectAccess servers, Active Directory Security groups, and SSL certificates must be made.

DirectAccess Servers

Much like preparing a DirectAccess server for load balancing, DirectAccess servers that will be added to a multisite configuration must meet all installation prerequisites. Windows Server 2016 must be installed and joined to the domain, all necessary certificates must be installed, and the DirectAccess-VPN role must be installed. Again, it is not necessary to *configure* DirectAccess directly on these servers. All DirectAccess configuration will be performed from a previously deployed DirectAccess server.

Security Groups

If Windows 8.x and Windows 10 clients are to be supported exclusively, no additional security groups are required. However, if Windows 7 clients are to be supported as well, one additional security group per entry point is required. For example, a multisite DirectAccess deployment with two entry points will require three security groups in total. One security group will be dedicated to Windows 8.x and Windows 10 clients, with one security group for each entry point dedicated to Windows 7 clients.¹

Note It is crucial that DirectAccess clients belong to **only one** security group. Windows 8.x and Windows 10 clients must not reside in Windows 7 groups, and Windows 7 clients must not be included in the Windows 8.x/10 group. If a Windows 7 client is to be moved from one entry point to another, remove the client from its current security group first before placing it in another. When performing in-place upgrades from Windows 7 to Windows 8.x or Windows 10, it is recommended that the client be removed from the DirectAccess security group before being upgraded. Once the upgrade is complete, the client can be placed in the Windows 8.x/10 DirectAccess client security group.

¹This assumes that all DirectAccess clients are members of a single domain. Additional security groups may be required if DirectAccess clients reside in more than one domain.

DNS

Each additional entry point will require its own unique public hostname. This hostname must resolve in public DNS to the IPv4 address assigned to the DirectAccess server's External network interface, or to the IPv4 address assigned to the edge security device protecting the DirectAccess server.

IP-HTTPS Certificate

The IP-HTTPS certificate installed on the DirectAccess server(s) must match the public hostname for the entry point. Optionally, a wildcard certificate can be deployed.

Enable Multisite

The process of enabling multisite DirectAccess involves first converting the existing DirectAccess server(s) to an entry point, then creating additional entry points and adding servers as necessary.

Important Enabling multisite DirectAccess will disconnect clients that are connected remotely! They will not be able to reconnect until they perform a group policy update. This will require clients to be reconnected to the LAN or connect out-of-band via client-based VPN.

Create the First Entry Point

To enable multisite DirectAccess, open the Remote Access Management console, highlight **DirectAccess and VPN** in the navigation tree, and click **Enable Multisite** under **Multisite Deployment** in the **Tasks** pane (Figure 7-1).



Figure 7-1. Enabled multisite

Click **Next** and provide a descriptive name for the multisite DirectAccess deployment. The existing DirectAccess server(s) will become the first entry point, so also provide a name for the new entry point (Figure 7-2).

Before You Begin	Specify names to identify the multisite deployment, and the first entry point. This is used for
Deployment Name	configuration and monitoring purposes.
Entry Point Selection	Multicite denloyment name:
Global Load Balancing	Richard M. Hicks Consulting
Client Support	
Summary	First entry point name:
Completion	US West

Figure 7-2. Provide multisite deployment and first entry point names

Note The multisite deployment name and entry point name are purely administrative. They are not hostnames or Fully-Qualified Domain Names (FQDNs) and do not resolve in DNS.

Windows 8.x and Windows 10 clients will automatically select the best entry point to connect to. Optionally, the administrator can allow DirectAccess clients to manually select an entry point, if desired. Choose whether to allow DirectAccess clients to automatically and manually select, or to restrict them to using automatic entry-point selection only, and click **Next** (Figure 7-3).

Sa Enab	ble Multisite Deployment		×
En	try Point Select	ion	
BA G C SI C	efore You Begin eployment Name ntry Point Selection lobal Load Balancing lient Support ummary ompletion	Client computers are automatically routed to the most suitable entry point. Optionally, clients can manually select the entry point to which they connect. These settings are not applied to client computers running Windows 7. Configure support for these clients on the Client Support page in this wizard. Assign entry points automatically, and allow clients to select manually Assign entry points automatically only	
		< Previous Next > Commit Cancel	

Figure 7-3. Choose an entry-point selection option for Windows 8.x/10 clients

Select **No, do not use global load balancing** to allow Windows 8.x and Windows 10 clients to automatically select an entry point on their own (Figure 7-4).

Betore You Begin Deployment Name Entry Point Selection Global Load Balancing Client Support Summary Completion	You can optionally configure global load balancing to direct client computers to the closest entry point. No, do not use global load balancing Yes, use global load balancing Type the global load balancing FQDN to be used by all entry points: Example: corp.fabrikam.com
	Type the global load balancing IP address for this entry point:

Figure 7-4. Global load-balancing settings

Optionally, Select **Yes, use global load balancing** to integrate a Global Server Load Balancer (GSLB) solution to enhance entry-point selection for DirectAccess clients (Figure 7-5).

Sa Enable Multisite Deployment		×
Global Load Balan	cing Settings	
Before You Begin Deployment Name Entry Point Selection Global Load Balancing Client Support Summary Completion	You can optionally configure global load balancing to direct client computers to the closest entry point. No, do not use global load balancing Yes, use global load balancing Type the global load balancing FQDN to be used by all entry points: da-gslb.richardhicks.net Example: corp.fabrikam.com Type the global load balancing IP address for this entry point: 203.0.113.240 	
	Example: 203.0.113.20	
	< Previous Next > Commit Cancel	

Figure 7-5. Optionally, configure global load balancing

If Windows 8.x and Windows 10 clients are to be supported exclusively, select the option to **Limit** access to client computers running Windows 8 or a later operating system. If Windows 7 clients will connect to this entry point, select the option to **Allow client computers running Windows 7 to access this** entry point. Click Add, choose the appropriate security group, and then click Next (Figure 7-6).

CHAPTER 7 CONFIGURE DIRECTACCESS GEOGRAPHIC REDUNDANCY



Figure 7-6. Specify client support for this entry point

A new Active Directory Group Policy Object (GPO) will be created to apply settings to Windows 7 clients for this entry point. Review and optionally adjust the name of the GPO, then click **Next** (Figure 7-7).

CHAPTER 7 CONFIGURE DIRECTACCESS GEOGRAPHIC REDUNDANCY

Sa Enable Multisite Deployment		×
Client GPO Setting	S	
Before You Begin Deployment Name	Select a GPO for remote clients in each d	omain.
Entry Point Selection	lab.richardhicks.net	DirectAccess Windows 7 Client Settin Browse
Global Load Balancing		
Client Support		
Client GPO Settings		
Summary		
Completion		
		Validate GPOs
	< Prev	ious Next > Commit Cancel

Figure 7-7. Select a GPO for Windows 7 clients

Confirm the multisite deployment settings and click **Commit** (Figure 7-8).

🔄 Enable Multisite Deployment			>
Summary			
Before You Begin Deployment Name	Confirm multisite deployment sett	ings.	
Entry Point Selection Global Load Balancing Client Support Client GPO Settings Summary Completion	Multisite deployment name: Entry point name: Manual entry point selection: Global load balancing: Client support: Windows 7 security groups: Windows 7 GPOs:	Richard M. Hicks Consulting US West Enabled Disabled Allow client computers running Windows 7 to access this entry point Iab.richardhicks.net\DirectAccessClientsWin7USWest Iab.richardhicks.net\DirectAccess Windows 7 Client Settings - US West	
		< Previous Next > Commit Cancel	

Figure 7-8. Confirm the multisite deployment settings

Add Additional Entry Points

Once the first entry point is configured, a second entry point can be established by highlighting **DirectAccess and VPN** in the navigation tree, highlighting the root node of the enterprise, and then clicking **Add an Entry Point** under **Multisite Deployment** in the **Tasks** pane (Figure 7-9).



Figure 7-9. Add an entry point

Enter the name of the DirectAccess server, provide a name for the new entry point, and then click **Next** (Figure 7-10).

CHAPTER 7 CONFIGURE DIRECTACCESS GEOGRAPHIC REDUNDANCY

ntry Point Details letwork Topology	Select the Remote Access server associated with this entry point, and specify an entry po name.
letwork Name or IP Add	Remote Access server:
letwork Adapters	edge3.lab.richardhicks.net Brow
lient Support	Fatar point name:
	US East

Figure 7-10. Enter the name of the DirectAccess server and the entry point

If global load balancing is enabled, enter the public IPv4 address for this entry point (Figure 7-11).

Global Load Balancing	IP address for this entry point. Address	ses are used to direct clie	ent computers to the closest
Network Topology	citil) ponto		
Network Name or IP Add	Type the global load balancing IP addr	ress for this entry point:	
Network Adapters	192.0.2.240		
Client Support	Example: 203.0.113.20		
Server GPO Settings			
Completion			

Figure 7-11. Enter the global load-balancing IP address for this entry point

Select the appropriate network topology for the new entry point. If the DirectAccess server does not have two network adapters or a public IPv4 address assigned to the external adapter, some choices may be unavailable. Choose a network topology and click **Next** (Figure 7-12).



Figure 7-12. Select a network topology

Enter the public hostname for the new entry point and click Next (Figure 7-13).

Dia Add an Entry Point		×
Network Name or IF	2 address	
Entry Point Details Network Topology	Type in the public name or IP address used by clients to connect to the Remote Access server.	
Network Name or IP Add	da-eastrichardnickshet	
Network Adapters		
Client Support		
Server GPO Settings		
Summary		
Completion		
	< Previous Next > Commit Cancel	

Figure 7-13. Enter the public hostname for the entry point

Note Although the GUI suggests that an IP address can be provided here, it is strongly recommended that an FQDN be used instead.

Review the network adapter and IP-HTTPS certificate settings and click Next (Figure 7-14).

CHAPTER 7 CONFIGURE DIRECTACCESS GEOGRAPHIC REDUNDANCY

Network Name or IP Add	F			
	External adapter:		Internal adapter:	
Network Adapters	External	v	Internal	
Elient Support	192.0.2.240	Details	172.16.2.240	Details
	Colort the cost Costs	and the surth and install D. U.	TTDC	
Summary	Select the certificate used to authenticate IP-HTTPS connections.			
Completion	ert- incharametsinet		andated	browse

Figure 7-14. Configure network adapter and IP-HTTPS certificate settings

If this entry point will support only Windows 8.x and Windows 10 clients, select the option to Limit access to client computers running Windows 8 or a later operating system. If Windows 7 clients will connect to this entry point, select the option to Allow client computers running Windows 7 to access this entry point. Click Add, choose the appropriate security group, and then click Next (Figure 7-15).



Figure 7-15. Specify client support for this entry point

A new GPO will be created with which to apply settings to Windows 7 clients for this entry point. Review and optionally adjust the name of the GPO and click **Next** (Figure 7-16).

S Add an Entry Point		×
Client GPO Setting	S	
Entry Point Details Network Topology	Select a GPO for remote clients in	each domain.
Network Name or IP Add Network Adapters	lab.richardhicks.net	brecoccess windows / criefic securi
Client Support		
Client GPO Settings		
Server GPO Settings		
Summary		
Completion		
		Validate GPOs
	[< Previous Next > Commit Cancel

Figure 7-16. Select a GPO for Windows 7 clients

Another new GPO will be created, this time to apply settings to all DirectAccess servers belonging to this entry point. Review and optionally adjust the name of the GPO, then click **Next** (Figure 7-17).
Server GPO Settin	as	×
Entry Point Details Network Topology Network Name or IP Add Network Adapters Client Support Client GPO Settings Server GPO Settings Summary Completion	Remote Access server settings are server GPO. Iab.richardhicks.net	stored in an Active Directory GPO. Specify a name for the DirectAccess Server Settings - US Eas Browse
		< Previous Next > Commit Cancel

Figure 7-17. Select a GPO for the DirectAccess servers

Confirm the deployment settings for this entry point and then click **Commit** (Figure 7-18).

Summary		
Entry Point Details Network Topology	Confirm entry point settings.	
Network Name or IP Add Network Adapters Client Support	Server name: Entry point name: Network topology:	edge3.lab.richardhicks.net US East Edge
Client GPO Settings Server GPO Settings Summary	Network name/IP address: External adapter:	da-east.richardhicks.net External
Completion	Internal adapter: IP-HTTPS certificate:	Internal CN=*.richardhicks.net, OU=Domain Control Validated
	Client support:	Allow client computers running Windows 7 to access this entry point
	Windows 7 security groups:	lab.richardhicks.net\DirectAccessClientsWin7USEast
	Windows 7 GPOs:	lab.richardhicks.net\DirectAccess Windows 7 Client Settings - US East

Figure 7-18. Confirm the multisite deployment settings

Enable Load Balancing for an Entry Point

To enable load balancing for a newly provisioned entry point, or to add servers to an existing load-balanced entry point, follow the procedures outlined in Chapter 6.

Multisite and GSLB

Multisite DirectAccess can be enhanced using a Global Server Load Balancing (GSLB) solution. GSLB can be deployed using dedicated appliances or with Cloud-based services, such as Microsoft Azure Traffic Manager.²

GSLB Deployment Scenarios

Using a GSLB enables important new deployment scenarios, such as geolocation, weighted distribution, and active/passive failover.

²https://directaccess.richardhicks.com/2016/04/04/directaccess-multisite-geographic-redundancywith-microsoft-azure-traffic-manager/

Geolocation

GSLB solutions often incorporate geolocation with the use of client IP address information to more accurately identify the physical geography where a client request originates. This allows for more consistent geographic site selection than the native site-selection process provides.

Weighted Distribution

Weighted request distribution is helpful for scenarios in which an organization has multiple locations, each having a different capacity. For example, one location might have four DirectAccess servers, while another has just two. Here, the GSLB can be configured to distribute more connection requests to the datacenter that has additional capacity, while sending fewer requests to the location with less resources.

Active/Passive Failover

Native multisite DirectAccess allows any Windows 8.x/10 client to connect to any entry point in the enterprise. To support disaster recovery (DR) scenarios, GSLB can be configured to send all requests to a single entry point unless that entry point is unavailable. If the primary location is offline, the GSLB will direct all requests to a secondary location.

GSLB Configuration

GSLB configuration is unique to each vendor's platform and is outside the scope of this book. Consult the solution vendor's documentation for detailed configuration guidance.

Enable GSLB Post-Deployment

To enable GSLB after multisite DirectAccess has been configured, highlight **DirectAccess and VPN** in the navigation tree, highlight the root node of the enterprise, and then click **Configure Multisite Settings** under **Multisite Deployment** in the **Tasks** pane (Figure 7-19).



Figure 7-19. Configure multisite settings

Click **Global Load Balancing** and select the option **Yes, use global load balancing**, then click **Next** (Figure 7-20) .

Sconfigure Multisite Settings		×
Global Load Balar	ncing Settings	
Deployment Name Entry Point Selection	You can optionally configure global load balancing to direct client computers to the closest entry point.	
Global Load Balancing Summary Completion	 No, do not use global load balancing Yes, use global load balancing Type the global load balancing FQDN to be used by all entry points: 	
	da-gslb.richardhicks.net	1
	Example: corp.fabrikam.com	
	< Previous Next > Commit Cancel	

Figure 7-20. Configure global load balancing

Confirm the multisite deployment settings and click **Commit** (Figure 7-21).

Sconfigure Multisite Settings			×
Summary			
Deployment Name Entry Point Selection	Confirm multisite deployment sett	ings.	
Global Load Balancing	Multisite deployment name:	Richard M. Hicks Consulting	
Summary	Manual entry point selection:	True	
	Global load balancing:	True	
	Global load balancing FQDN:	da-gslb.richardhicks.net	
	L	< Previous Next > Co	mmit Cancel

Figure 7-21. Confirm your multisite deployment settings

After the settings have been applied, the global load-balancing IP address must be set for each entry point in the organization. Highlight **DirectAccess and VPN** in the navigation tree, highlight an entry point, and then click **Configure Entry Point Settings** (Figure 7-22).



Figure 7-22. Configure the entry point settings

Click **Global Load Balancing** and enter the public IPv4 address that corresponds to this entry point (Figure 7-23).

	5 5
Entry Point Name	Global load balancing is enabled in the multisite deployment. Specify a global load balancing IP address for this entry point. Addresses are used to direct client computers to the closest
Network Name or IP Add	entry point.
Client Support	Type the global load balancing IP address for this entry point:
Client GPO Settings	192.0.2.240
Summary	Example: 203.0.113.20

Figure 7-23. Enter the global load-balancing IP address for this entry point

Click **Next** four times, then click **Commit** (Figure 7-24). Repeat these steps for each entry point in the enterprise.

CHAPTER 7 CONFIGURE DIRECTACCESS GEOGRAPHIC REDUNDANCY

Sa Configure Entry Point Settings			Х
Summary			
Global Load Balancing	Confirm entry point settings.		
Client Support Client GPO Settings Summary Completion	Entry point name: Global load balancing IP address: Network name/IP address: Client support: Windows 7 security groups: Windows 7 GPOs:	US East 192.0.2.240 da-east.richardhicks.net Allow client computers running Windows 7 to access this entry point lab.richardhicks.net\DirectAccessClientsWin7USEast lab.richardhicks.net\DirectAccess Windows 7 Client Settings - US East	
	<	Previous Next > Commit Cancel	

Figure 7-24. Confirm your entry point settings

The global load-balancing IP address for each entry point can also be configured using PowerShell and the Set-DAEntryPoint cmdlet. Run this command on any DirectAccess server in the enterprise. The syntax is as follows:

```
Set-DAEntryPoint -Name [entry_point_name] -GslbIP [ip_address]
```

For example:

```
Set-DAEntryPoint -Name "US West" -GslbIP 203.0.113.240
Set-DAEntryPoint -Name "US East" -GslbIP 192.0.2.240
```

GSLB Operation

When a Windows 8.x or Windows 10 client establishes a DirectAccess connection, it will attempt to resolve the GSLB FQDN to an IP address. The GSLB will respond, based on its configuration, with an IP address corresponding to a preferred entry point. The client does not connect directly to this IP address, however. Instead, it looks up the IP address in its entry point table and chooses the IPHTTPS profile that matches the IP address returned by the GSLB. The client then connects to the URL defined in that profile. You can view the DirectAccess entry point table on a Windows 8.x or Windows 10 client by using the following PowerShell command (Figure 7-25):

```
Get-DAEntryPointTableItem
```

```
Machinistrator: Windows PowerShell
                                                                                                                                                       X
PS C:\> Get-DAEntryPointTableItem
                             ActiveStore
PolicyStore
                           :
                             US East
NotSelected
EntryPointName
State
ADSite
                             LabNet
TeredoServerIP : 0.0.0.0
EntryPointRange : {2002:cb00:71f0:3333::1/128, fd2d:d773:1f5a:2223::1/128, fd2d:d773:1f5a:2223::2/128,
fd2d:d773:1f5a:7777::ac10:2f0/128}
EntryPointIPAddress : fd2d:d773:1f5a:2223::1
IPHttpsProfile
                             US East
                           : 192.0.2.240
GslbIP
PolicyStore
EntryPointName
                           :
                             ActiveStore
                             US West
NotSelected
State
                             LabNet
ADSite
                             0.0.0.0
TeredoServerIP
EntryPointRange
                             2002:cb00:71f0:3333::1/128, fd2d:d773:1f5a:2222::1/128, fd2d:d773:1f5a:2222::2/128,
fd2d:d773:1f5a:7777::ac10:1f0/128}
EntryPointIPAddress :
                             fd2d:d773:1f5a:2222::1
IPHttpsProfile
GslbIP
                           : US West
: 203.0.113.240
PS C:\> _
```

Figure 7-25. Display the DirectAccess entry point table

Summary

Multisite DirectAccess can be deployed to eliminate the datacenter itself as a potential single point of failure. In addition, multisite configuration can be used to ensure that geographically disperse clients connect to an entry point close to their physical location.

Full support for multisite DirectAccess is available with Windows 8.x and Windows 10 clients. Windows 7 clients can still be deployed, but they must be assigned to a single site and will not fail over.

Load balancing and multisite DirectAccess are not mutually exclusive. In fact, they work together to provide the most highly available solution, ensuring that a server failure in a single location, or even the failure of an entire datacenter, does not prevent remote users from connecting remotely.

GSLB can be used to enhance the multisite experience and enable new deployment scenarios not natively supported in Windows Server 2016, such as weighted distribution, proximity-based access, and active/passive failover.

CHAPTER 8

Enable Two-Factor Authentication

By default, users log in to DirectAccess client machines using only their username and password. To improve the overall security of the solution and to provide a higher level of assurance for remote users, two-factor authentication can be enabled.

DirectAccess supports multifactor user authentication using either smart cards (physical or virtual) or RADIUS-based one-time password (OTP) solutions. Each has its own unique advantages and disadvantages.

Smart Cards

Smart cards are an effective way of providing a high level of assurance for the logged-on user. To gain access to corporate resources over the DirectAccess connection, the user must have their physical smart card and know the personal identification number (PIN) associated with the card. This makes credential theft much more difficult. In addition, requiring a physical card to log in ensures that a user cannot log on to more than one device at a time.

Physical Smart Cards

Smart cards are most commonly physical, requiring the user to have them in their possession to log on to their device. Along with having the card, they must also know their PIN to gain access to the card itself. Physical smart cards provide enhanced protection for encryption keys, secure processing for cryptographic operations, and anti-hammering capabilities to prevent brute-force attacks on the card.

Virtual Smart Cards

Virtual smart cards replicate the security and functionality of physical smart cards without requiring additional hardware to support them. Instead of using proprietary hardware, virtual smart cards leverage the Trusted Platform Module (TPM)¹ that is already included with most modern computers. The TPM provides enhanced protection for encryption keys, secure processing for cryptographic operations, and anti-hammering capabilities to prevent brute-force attacks, just as physical smart cards do. Virtual smart cards stored on the TPM essentially make the client computer the second factor of authentication for the user.

https://en.wikipedia.org/wiki/Trusted_Platform_Module

One-Time Passwords

OTP is another effective way to provide a higher level of assurance for DirectAccess users. To gain access to corporate resources over the DirectAccess connection, the user must provide their PIN plus their OTP. OTPs are generated in a variety of ways. Commonly, the OTP can be obtained from a physical token or be generated using an application running on a PC or a smartphone.

Supported OTP Solutions

Any OTP solution that uses RADIUS will work with DirectAccess. However, DirectAccess does not support the use of OTP solutions that implement challenge/response. The user must be able to provide their PIN and OTP when signing on to DirectAccess.

Note Microsoft Azure Multifactor Authentication (MFA) is an example of a popular OTP solution that does not work with DirectAccess. Azure MFA challenges the user by calling their phone number after receiving an authentication request from the server. The user must respond by answering the call and pressing a number on their keypad, and optionally providing a PIN, to be successfully authenticated. Azure MFA is not supported for use with DirectAccess because the user cannot provide their PIN and OTP when prompted by the Windows 8.x/10 DirectAccess Network Connectivity Assistant (NCA) or the Windows 7 DirectAccess Connectivity Assistant (DCA).

Prerequisites

The following topics describe the requirements for enabling and configuring DirectAccess to support multifactor authentication.

Client Authentication

DirectAccess must be configured to use computer certificates for client authentication when enabling multifactor authentication using smart cards or OTP. The use of Kerberos Proxy is not supported.

Note Kerberos Proxy is used for authentication when DirectAccess is configured using the Getting Started Wizard or when certificate authentication is enabled and the option to enable Windows 7 client computers to connect via DirectAccess is not selected *(Remote Access setup wizard, DirectAccess and VPN, Step 2, Authentication).*

Certification Authority

For smart cards, the certification authority requirements depend largely on the smart card implementation. For OTP, a Microsoft Enterprise Certification Authority (CA) is required. The CA can be running on Windows Server 2003 or later. A CA running on Windows Server 2008 R2 or later is recommended. The same CA used to issue IPsec certificates to DirectAccess clients can be used to issue OTP certificates. In addition, the CA must be included in the management computers list so that it is accessible over the infrastructure (first) IPsec tunnel. **Note** To add the CA to the DirectAccess management servers list, open the Remote Access management console and click **Edit** on **Step 3**. Click **Management** and then enter the hostname of the CA. Alternatively, the CA can be added to the management servers using the **Add-DAMgmtServer**² PowerShell cmdlet.

If OTP authentication is enabled in a multiforest environment, the CA used to issue OTP certificates should be located in the resource forest only. Certificate enrollment should then be configured across forest trusts.

OTP and Force Tunneling

OTP authentication cannot be enabled if DirectAccess is configured to use force tunneling. OTP authentication takes place outside of the DirectAccess IPsec tunnel. However, force tunneling disallows this, which causes the OTP authentication request to fail.

Windows 7 Clients

The DirectAccess Connectivity Assistant (DCA) v2.0 must be installed on Windows 7 clients to support OTP authentication. Detailed guidance for configuring the DCA on Windows 7 is covered in Chapter 9, "Supporting Windows 7 Clients."

DirectAccess Configuration

Strong user authentication should be enabled only after DirectAccess has been installed and configured, remote DirectAccess connectivity has been established, and validation testing has been performed to ensure that the solution is working correctly. This will streamline the troubleshooting process in the event that DirectAccess doesn't work correctly after enabling multifactor authentication.

Enable Smart Card Authentication

The following steps will describe the process of configuring DirectAccess to enforce multifactor authentication using physical or virtual smart cards.

Configure DirectAccess

To configure DirectAccess to require multifactor authentication using smart cards, open the Remote Access Management console and highlight **DirectAccess and VPN** under **Configuration** in the navigation tree. Click **Edit** on **Step 2**, click **Authentication**, and then select **Two-factor authentication (smart card or one-time password (OTP))** under **User Authentication** (Figure 8-1).

²https://technet.microsoft.com/en-us/library/hh918394.aspx

Sa Remote Access Setup	X
Remote Acce Configure DirectAc	ss Server Setup cess and VPN settings.
Network Topology Network Adapters Authentication	Specify how DirectAccess clients authenticate. If computer certificates are not used for authentication, DirectAccess acts as a Kerberos proxy on behalf of the client. Enable support for Windows 7 clients. User Authentication Active Directory credentials (username/password) Two-factor authentication (smart card or one-time password (OTP)) Use OTP Use computer certificates Select the root or intermediate certification authority (CA) that issues the certificates. Use an intermediate certificate CN=LAB-ISSUING-CA, DC=lab, DC=richardhicks, DC=net Enable Windows 7 client computers to connect via DirectAccess
	< Back Next > Finish Cancel

Figure 8-1. Enable two-factor authentication

Optionally, multifactor authentication can be enabled by opening an elevated PowerShell command window and executing the following command:

Set-DAServer -UserAuthentication TwoFactor

Smart Card End User Experience

With DirectAccess configured to require smart card authentication, the user will log on to their device using the Ctrl+Alt+Delete sequence as usual. After logging in, the user will not have access to any corporate resources without first supplying their smart card credentials.

Note If the user is unable to provide their multifactor authentication credentials, access will be restricted to infrastructure servers only.

To complete the authentication process on the DirectAccess client, press **Window Key + I**, click **Network & Internet**, and then highlight **DirectAccess**. The connectivity status indicator will show that action is needed (Figure 8-2).



Figure 8-2. Workplace connection action needed

Click Workplace Connection and then click Continue (Figure 8-3).



Figure 8-3. Workplace connection sign-in info needed

Enter the PIN for the smart card and click OK (Figure 8-4).

DirectAccess	
DirectAccess Enter your credentials Richard Hicks rhicks@lab.richardhicks.net Security device credential	
•••••	
	OK Cancel

Figure 8-4. Enter your smart card PIN

Once the authentication process is successful, the user will have full access to all corporate resources.

Enable OTP Authentication

DirectAccess OTP authentication uses short-lived certificates for user authentication. Changes to the internal Public Key Infrastructure (PKI) will be required before configuring DirectAccess OTP.

Configure Certificate Templates

An OTP Certificate Request Signing certificate template and an OTP Certificate template must be prepared on the CA server to support OTP authentication with DirectAccess. The following topics will outline the steps required to prepare these certificate templates.

OTP Certificate Request Signing Template

On the CA server, open the Certification Authority management console, right-click **Certificate Templates**, and then choose **Manage**. Right-click the **Computer** template and choose **Duplicate Template**. On a Windows Server 2008 or 2008 R2 CA, select **Windows Server 2008 Enterprise** when prompted for the duplicate certificate template version. On a Windows Server 2012, 2012 R2, or 2016 CA, select the **Compatibility** tab and then select **Windows Server 2008 R2** for the **Certification Authority** and **Windows 7/Server 2008 R2** for the **Certificate recipient** (Figure 8-5).

		perties	ornen	remplate	
Subject I	upgect Name Server Issuance Requirements		equirements		
Superse	ded Templa	ates	es Extensions Secur		Security
Compatibility	General	Request	Handling	Cryptography	Key Attestation
The templat versions set	e options a in Compati sulting char ity Settings ion Authorit is Server 20 e recipient is 7 / Serve	vailable an bility Settin nges y 008 R2 rr 2008 R2	e based or igs.	v	rating system
These settin template.	igs may not	prevent e	arlier opera	ating systems from	m using this

Figure 8-5. Configure the certificate template compatability

Select the **General** tab and provide a descriptive name for the **Template Display Name**. Specify a **Validity period** of two days and a **Renewal period** of one day (Figure 8-6).

Proj	perties	of New	Template)
Subject Name	Ser	ver	Issuance Requirements	
Superseded Templa	tes	Ext	ensions	Security
Compatibility General	Request	Handling	Cryptography	Key Attestation
Template display name:				
DirectAccess OTP Reg	gistration /	Authority		
DirectAccessOTPRegi Validity period:	stration.Au	Renewa	al period:	
2 days V		1	days 🗸	
Publish certificate in Do not automatic Directory	Active Di cally reenro	rectory oll if a dup	licate certificate	exists in Active
ОК		Cancel	Apply	Help

Figure 8-6. Enter the template display name

Select the **Security** tab and click **Add**. Click **Object Types** and then select **Computers** and click **OK**. Enter the names of each DirectAccess server. Click **OK** when finished. For each DirectAccess server, grant **Read**, **Enroll**, and **Autoenroll** permissions. Select **Authenticated Users** and remove any permissions other than **Read**. Select **Domain Computers** and remove the **Enroll** permission. Select **Domain Admins** and grant **Full Control** permission. Do the same for **Enterprise Admins** (Figure 8-7).

Subject Name	Ser	ver	Issuance Requirements		
Compatibility Gener	ral Request	Handling	Cryptography	Key Attestation	
Superseded Ter	mplates	Exte	nsions	Security	
Group or user name	s:				
& Authenticated	Users				
& Richard Hicks	(rhicks@lab.ri	ichardhicks	s.net)		
Se Domain Admin	s (LAB\Domai	in Admins)			
Se Domain Compu	uters (LAB\Do	main Comp	outers)		
EDGE1 (LAB\	EDGE1\$)				
EDGE2 (LAB	EDGE2\$)				
Enterprise Adm	nins (LAB\Ente	erprise Adm	nins)		
			A <u>d</u> d	Remove	
Permissions for EDO	GE1		Allow	Denv	
Full Control					
Read			~	H I	
Write					
Enroll					
Autoenroll					
East and a similar in the		and antition	atala 🗖		
Advanced.	oris or advanc	eu settings		Ad <u>v</u> anced	

Figure 8-7. Configure the security permissions

Select the **Subject Name** tab and choose the option to **Build from this Active Directory information**. Select **DNS name** in the **Subject name format** drop-down list and confirm that DNS name is checked under **Include this information in alternate subject name** (Figure 8-8).

	General	request	Handling	Cryptography	Key Attestation
Supersec	ded Templa	ates	Exte	ensions	Security
Subject N	lame	Ser	ver	Issuance	Requirements
O Supply in Use	the request subject info wal request	st ormation fro s	om existing	certificates for	autoenrollment
 Build from Select this simplify ce Subject n 	this Active option to rtificate ad ame format	e Directory enforce co ministratio	y informatio onsistency n.	n among subject	names and to
DNS nan	ne				~
Include th	is informati name name	on in alter	nate subjec	d name:	
Servic	e principal e principal	name (SP	N)		

Figure 8-8. Enable the DNS name subject name format

Select the **Extensions** tab, highlight **Application Policies**, and click **Edit**. Remove all existing application policies and then click **Add** and then **New**. Provide a descriptive name for the new application policy and enter **1.3.6.1.4.1.311.81.1.1** for the **Object Identifier**. Click **OK** for all remaining dialog boxes (Figure 8-9).

New Ap	oplication Policy
Type a name for the new application object identifier.	ation policy, and if necessary change the
Name:	
DirectAccess OTP Registration	Authority
Object identifier:	
1.3.6.1.4.1.311.81.1.1	

Figure 8-9. Create a new application policy

OTP Certificate Template

Right-click the **Smartcard Logon** certificate template and choose **Duplicate Template**. On a Windows Server 2008 or 2008 R2 CA, select **Windows Server 2008 Enterprise** when prompted for the duplicate certificate template version. On a Windows Server 2012, 2012 R2, or 2016 CA, select the **Compatibility** tab and then select **Windows Server 2008 R2** for the **Certification Authority** and **Windows 7/Server 2008 R2** for the **Certificate recipient** (Figure 8-10).

	Prop	perties	of New	Template	×
Subject N	lame	Ser	ver	Issuance Requirements	
Supersed	ed Templa	ites	Exte	insions	Security
Compatibility	General	Request	Handling	Cryptography	Key Attestation
The template versions set	e options a in Compati ulting char ty Settings on Authority s Server 20 e recipient s 7 / Serve gs may not	vailable ar bility Settin nges y 008 R2 r 2008 R2 r 2008 R2	e based or igs.	the earliest ope	m using this
Г	ОК		Cancel	Apply	Help

Figure 8-10. Configure the certificate template compatability

Select the **General** tab and provide a descriptive name for the **Template Display Name**. Specify a validity period of one hour and a renewal period of zero hours (Figure 8-11).

	Name	Sen	rver Issuance Re		quirements	
Superse	ded Templa	stes	Exte	ensions	Security	
Compatibility	General	Request	Handling	Cryptography	Key Attestation	
Template dis	olav name					
Direct Access OTP Logon						
Template na	me:					
DirectAcces	soTPLogo	n				
Validity perio	d:	-	Renewa	l period:		
1 hou	urs v	'	0	hours 🗸		
Dublish a	artificanta in	Active Dir	actory.			
Fublishic	enuicate in	Active Di	ectory all if a dupli	onto continento a	wiete in Active	
Den	a automatic	ally reening	n i a dupi	cate centricate e	SUSLS IN ACTIVE	
Do no Direct	tory					
Do no Direct	tory					
Do no Direct	tory					
Do no Direct	tory					
Do no Direct	tory					
Do no Direct	tory					
Do no Direct	tory					

Figure 8-11. Enter the template display name

Note It is not possible to set the validity period to hours on a Windows Server 2003 Certificate Authority (CA). As a workaround, use the Certificate Templates snap-in on another system running Windows 7 or Windows Server 2008 R2 or later. Also, if the CA is running Windows Server 2008 R2, the template must be configured to use a Renewal Period of one or two hours and a Validity Period that is no more than four hours.

Select the **Security** tab, then highlight **Authenticated Users** and grant **Read** and **Enroll** permissions. Select **Domain Admins** and grant **Full Control** permission. Do the same for **Enterprise Admins** (Figure 8-12).

	Vame	Sen	ver	Issuance R	equirements	
Compatibility	General	Request	Handling	Cryptography	Key Attestation	
Superse	ded Templa	ates Extensions			Security	
Group or user names:						
& Authen	ticated Use	rs				
🔏 Richard	d Hicks (rhid	cks@lab.ri	ichardhicks	s.net)		
St. Domain	n Admins (L	AB\Domai	in Admins)			
Senterpr	ise Admins	(LAB\Ente	erprise Adm	nins)		
				Add	Remove	
Demissions	for A doort	anted Lie		Aller	Demu	
remissions	for Authent	icated Use	ers	MIOW	Deny	
Full Contro	ol					
Full Contro Read	ol					
Full Contro Read Write	ol					
Full Contro Read Write Enroll	ol					
Full Contro Read Write Enroll Autoenrol	ol I			_ \ _ \ _		
Full Contro Read Write Enroll Autoenrol	ol			 		
Full Contro Read Write Enroll Autoenrol	ol					
Full Contro Read Write Enroll Autoenrol	ol I permissions	or advanc	ced settings	S. dlick		
Full Contro Read Write Enroll Autoenrol	ol I Deemissions	or advanc	ced settings	s, click	Advanced	
Full Contro Read Write Enroll Autoenrol For special p Advanced.	ol I Deemissions	or advanc	ced settings	s, click	Advanced	

Figure 8-12. Configure the security permissions

Select the **Subject Name** tab and choose the option to **Build from this Active Directory information**. Select **Fully distinguished name** in the **Subject name format** drop-down list and confirm that **User principal name (UPN)** is checked under **Include this information in alternate subject name** (Figure 8-13).

Compatibility	General	Request	Handling	Cryptography	Key Attestation
Superse	Superseded Template		Exte	ensions	Security
Subject Name			ver	Issuance R	equirements
O Supply in	the reques subject info wal request	st ormation fr ts (*)	om existing	certificates for a	utoenrollment
Build from	n this Activ	e Directory	y informatio	n	
Select this simplify ce	s option to entificate ad	enforce co ministratio	n.	among subject n	ames and to
Fully dist	inquished r	name			~
	e e-mail na	me in subj	ject name	t name:	
E-mail	name	off all dates		a nome.	
DNS	name				
User p	nincipal na	me (UPN)			
Servic	e principal	name (SP	N)		
* Control is	licabled du		stibility oott	inge	

Figure 8-13. Enable the Fully distinguished name subject name format

Select the **Server** tab and choose the option **Do not store certificates and requests in the CA database**. Unselect the checkbox next to **Do not include revocation information issued in certificates** (Figure 8-14).

Properties of New Template X						
Compatibility	General	Request	Handling	Cryptography	Key Attestation	
Superse	ded Templa	ates	Exte	ensions	Security	
Subject 1	Name	Sen	ver	Issuance F	Requirements	
☑ Do not store certificates and requests in the CA database						
[OK		Cancel	Apply	Help	

Figure 8-14. Do not store certificates and requests in the CA database

Select the **Issuance Requirements** tab and set .the value for **This number of authorized signatures** to 1. Confirm that **Application Policy** is selected from the **Policy type required in signature** drop-down list and choose the OTP certificate request signing template created previously (Figure 8-15).

Compatibility	General	Request	Handling	Cryptography	Key Attestation
Superse	ded Templa	ates	Exte	ensions	Security
Subject N	Name	Sen	ver	Issuance Re	equirements
Require the CA certifi This num If you re Policy ty	following fo cate mana ber of auth quire more be required	or enrollmen ger approv orized sign than one s	nt: ral natures: signature, a re:	1 autoenrollment is	not allowed.
Applicat	tion policy				~
Applicati	on policy:				
DirectA	ccess OTP	Registrati	on Authorit	ty	~
Issuance	e policies:				
					Add
					Remove
Require the	following fo	or reenrollm	ent:		
 Same crit 	teria as for	enrollment			
Valid exis	ting certific	ate			
Allow	key based	renewal (")		
Requires request.	subject inf	formation t	o be provid	ded within the ce	rtificate

Figure 8-15. Configure the issuance requirements

Select the **Extensions** tab, highlight **Application Policies**, and click **Edit**. Highlight **Client Authentication** and click **Remove**. Ensure that the only application policy listed is **Smart Card Logon**. Click **OK** for all remaining dialog boxes (Figure 8-16).

Edit Application Policies Extension						
An application policy defines how a certificate can be used.						
Application policies:	Application policies:					
Smart Card Logon						
Add Edit Remove						
[ОК	Cancel				

Figure 8-16. Configure the application policies

Configure Certification Authority (CA)

In the Certificate Authority management console, right-click **Certificate Templates**, choose **New**, and then select **Certificate Template to Issue**. Highlight both of the certificate templates created previously and click **OK** (Figure 8-17).

lect one Certificate Template to enable on this (te: If a certificate template that was recently cre ormation about this template has been replicate	Certification Authority. sated does not appear on this list, you may need to wait until d to all domain controllers.	
or the certificate templates in the organization n r more information, see <u>Certificate Templa</u>	ay not be available to your CA. ate <u>Concepts.</u>	
lame	Intended Purpose	1
Code Signing	Code Signing	
Computer	Client Authentication, Server Authentication	
Cross Certification Authority	<al></al>	. 18
DirectAccess OTP Logon	Smart Card Logon	
DirectAccess OTP Registration Authority	DirectAccess OTP Registration Authority	L.
Directory Email Replication	Directory Service Email Replication	
Domain Controller	Client Authentication, Server Authentication	
EFS Recovery Agent	File Recovery	
Enrollment Agent	Certificate Request Agent	
Enrollment Agent (Computer)	Certificate Request Agent	
Exchange Enrollment Agent (Offline request)	Certificate Request Agent	1

Figure 8-17. Enable the new certificate templates

On the CA server, open an elevated PowerShell command window and execute the following command:

certutil.exe -setreg dbflags +DBFLAGS_ENABLEVOLATILEREQUESTS

Once complete, restart the CA by executing the following PowerShell command:

Restart-Service CertSvc

Configure RADIUS OTP

Configuring the RADIUS OTP server differs for each vendor and is outside the scope of this book. However, at a high level, the DirectAccess server should be configured as a RADIUS client on the RADIUS server, and users and tokens should be provisioned according to the vendor's guidance.

Note The DirectAccess server will probe the configured RADIUS server periodically to determine its health status and report it in the remote access management console. Failed authentication attempts for DAProbeUser on the RADIUS server are normal. It is not required to create this user on the RADIUS server or in Active Directory. These failed login attempts can be safely ignored.

Configure DirectAccess

To configure DirectAccess to require multifactor authentication using OTP, open the Remote Access Management console and highlight **DirectAccess and VPN** under **Configuration** in the navigation tree. Click **Edit** on **Step 2**, click **Authentication**, and then select **Two-factor authentication (smart card or onetime password (OTP))** under **User Authentication**. In addition, select the option to **Use OTP** and click **Next** (Figure 8-18).

Sa Remote Access Setup	X
Remote Access Se Configure DirectAccess	and VPN settings.
Network Topology Network Adapters Authentication OTP RADIUS Servers OTP CA Servers OTP Certificate Templates OTP Exemptions	Specify how DirectAccess clients authenticate. If computer certificates are not used for authentication, DirectAccess acts as a Kerberos proxy on behalf of the client. Enable support for Windows 7 clients. User Authentication Active Directory credentials (username/password) Two-factor authentication (smart card or one-time password (OTP)) Use OTP Use computer certificates Select the root or intermediate certification authority (CA) that issues the certificates. Use an intermediate certificate CN=LAB-ISSUING-CA, DC=lab, DC=richardhicks, DC=net Enable Windows 7 client computers to connect via DirectAccess
	< Back Next > Finish Cancel

Figure 8-18. Enable two-factor authentication and OTP

Add the RADIUS servers that will be used for OTP authentication. Provide the hostname, FQDN, or IP address of the server, the shared secret, specify the service port, and click **OK** and then **Next** (Figure 8-19).

Server name:	otp.lab.richar	otp.lab.richardhicks.net		
	Examples: rad 157.60.79.2	diusserver.contoso.con		
Shared secret:	*****	Change		
Port:	1812 🜲			

Figure 8-19. Add a RADIUS server

Select the CA server that will be used to issue certificates to DirectAccess clients for OTP authentication, then click **Add** and **Next** (Figure 8-20).

Sa Remote Access Setup		×
Remote Access Se Configure DirectAccess	and VPN settings.	
Network Topology Network Adapters Authentication OTP RADIUS Servers OTP CA Servers OTP Certificate Templates OTP Exemptions	Select CA servers that will be used to issue certificate Detected CA Servers: Add -> <- Remove Refresh	es to DirectAccess clients for OTP authentication. OTP CA Servers:
		< Back Next > Finish Cancel

Figure 8-20. Select the CA servers

Select the certificate templates to be used for the enrollment of certificates that are issued for OTP authentication. Also, select a certificate template to be used for enrolling the certificate used by the DirectAccess server to sign OTP certificate enrollment requests; click **Next** (Figure 8-21).

Sa Remote Access Setup		×
Remote Access S Configure DirectAccess	Server Setup and VPN settings.	
Network Topology Network Adapters Authentication OTP RADIUS Servers OTP CA Servers OTP Certificate Templates OTP Exemptions	Select a certificate template used for the enrollment of certificates that are issued for OTP authentication. DirectAccessOTPLogon Browse Select a certificate template used to enroll the certificate used by the Remote Access server to sign OTP certificate enrollment requests. DirectAccessOTPRegistrationAuthority Browse	
	< Back Next > Finish	Cancel

Figure 8-21. Select certificate templates for OTP

All users are required to authenticate using OTP by default. If some users need to be exempt from using OTP, select the option **Do not require users in the specified security group to authenticate using two-factor authentication**, specify the appropriate security group, then click **Finish** (Figure 8-22).

Semote Access Setup	×
Remote Access S Configure DirectAccess	and VPN settings.
Network Topology Network Adapters Authentication OTP RADIUS Servers OTP CA Servers	Specify whether selected DirectAccess users can authenticate with a user name and password when OTP authentication is enabled. Require all users to authenticate using two-factor authentication Do not require users in the specified security group to authenticate using two-factor authentication
OTP Certificate Templates	Security Group
	< Back Next > Finish Cancel

Figure 8-22. Specify users who can authenticate without OTP (optional)

Click **Edit** on **Step 3**, select **Management**, add the CA server used for OTP authentication to the list of management servers, then click **OK** and **Finish** twice. Now click **Apply** and **Close** (Figure 8-23).

Add	a Management Server		
Spec	cify the computer name or IPv4 address:		
0	Computer name (FQDN):		
	ca1.lab.richardhicks.net		
	Example: engineeringcomputer1.contoso.com		
0	IPv4 address		
	Example:		
	157.60.79.2		
		OK	Creat
		UK	Cancel

Figure 8-23. Add a CA server to the management servers list

OTP End User Experience

With DirectAccess configured to require OTP authentication, the user will log on to their device using the Ctrl+Alt+Delete sequence as usual. After logging in, the user will not have access to any corporate resources without first supplying their PIN and OTP.

Note If the user is unable to provide their multifactor authentication credentials, access will be restricted to infrastructure servers only.

To complete the authentication process on the DirectAccess client, press **Window Key + I**, click **Network & Internet**, and then highlight **DirectAccess**. The connectivity status indicator will show that action is needed (Figure 8-24).



Figure 8-24. Workpalce connection action needed

Click Workplace Connection and then click Continue (Figure 8-25).

ng			2
Your sign-in info is needed.			
\rightarrow	Co	ontinue	
e-site DirectAc	cess.		
admin			
	e-site DirectAc admin	e-site DirectAccess. admin	Continue Continue c-site DirectAccess. admin

Figure 8-25. Workplace connection sign-in info needed

The user will be prompted to press Ctrl+Alt+Delete to enter their credentials (Figure 8-26).



Figure 8-26. Press Ctrl+Alt+Delte to enter credentials

After pressing Ctrl+Alt+Delete, the user is prompted to enter their OTP credentials (PIN+OTP) (Figure 8-27).



Figure 8-27. Enter OTP credentials (PIN + OTP)

Once the authentication process is successful, the user will have full access to all corporate resources.

Deployment Considerations

There are a number of important considerations to be made when enabling strong user authentication using smart cards or OTP. The following topics will describe some of the potential negative side effects of multifactor authentication with DirectAccess.

Increased Complexity

Strong user authentication with smart cards or OTP solutions add to the complexity of a DirectAccess deployment, making it more difficult to support and troubleshoot.

Added Expense

Multifactor authentication solutions can add to the expense of implementing DirectAccess. Typically, there are hardware, licensing, and support costs associated with most smart card and OTP solutions. Smart cards and OTP tokens can be expensive, although this can be mitigated with the use of virtual smart cards or soft tokens.

Limited Flexibility

OTP and force tunneling cannot be enabled at the same time. These deployment options are mutually exclusive, forcing the administrator to choose between one option and the other.

Incomplete OTP Functionality

DirectAccess does not support new PIN or next token modes. Further, there is no support for an OTP PIN change on a DirectAccess client.

Reduced Scalability and Performance

When OTP is enabled, the number of concurrent DirectAccess connections supported by each DirectAccess server is reduced significantly. This happens because enabling OTP disables support for null encryption with the IP-HTTPS IPv6 transition technology. This results in IPsec-encrypted communications being encrypted again, which increases the load on the DirectAccess server.

Diminished User Experience

When a DirectAccess client connects remotely, there is no visible cue or any intuitive indication that the user needs to provide additional credentials to access corporate resources. This can be frustrating to end users and has the potential to generate calls to the help desk when applications and data aren't accessible over the DirectAccess connection.

Summary

Enabling strong user authentication using smart cards or one-time passwords is an effective way to improve the overall security posture of the DirectAccess implementation, but it comes at a price.

Multifactor authentication fundamentally breaks the seamless and transparent nature of DirectAccess. The added complexity also makes the solution more difficult to support. Smart cards and OTP solutions increase costs and degrade the user experience. Additionally, OTP limits scalability and reduces performance on the DirectAccess server.
CHAPTER 9

Support Windows 7 Clients

Windows 10 clients are recommended in order to get the best DirectAccess experience, both from the administrator's perspective as well as the end user's. Performance is better in Windows 10, and administration and troubleshooting are easier as well. Windows 7 clients are still supported with DirectAccess in Windows Server 2016, but with some important limitations and unique requirements.

Deployment Considerations

The following topics will highlight some important deployment considerations for supporting Windows 7 clients.

Multisite Support

Windows 7 clients do not perform automatic site selection when they are provisioned in a DirectAccess multisite deployment. Windows 7 clients must be assigned to a single entry point in the enterprise. They are not aware of any other entry points and cannot transparently fail over to another if their assigned entry point is unavailable.

Note There's a common misconception that Windows 7 clients can transparently fail over to another entry point if a Global Server Load Balancer (GSLB) is used. A Windows 7 client can't establish a DirectAccess connection just because the entry point's public hostname can be resolved to another entry point. Using GSLB to point the client to another entry point only swings the IPv6 transition tunnel to the new entry point. However, the DirectAccess client still expects to connect to its assigned DirectAccess servers using specific IPv6 addresses. Although the Windows 7 client will successfully establish a transition tunnel, the tunnel endpoint IPv6 addresses inside the transition tunnel will be incorrect, and IPsec will fail. This will prevent access to internal resources.

Degraded Performance

Windows 7 clients incur a performance penalty when the DirectAccess server is deployed behind a networking device performing Network Address Translation (NAT). IP-HTTPS is the only supported IPv6 transition technology in this deployment scenario. 6to4 and Teredo are not supported.

Crucially, Windows 7 clients support only encrypted SSL/TLS cipher suites when using IP-HTTPS. DirectAccess communication is already encrypted, so this double encryption increases CPU utilization by the client.

Reduced Scalability

Supporting Windows 7 clients also reduces the number of concurrent connections a DirectAccess server can support at one time. Since the server must perform double encryption for many clients at once, the added protocol overhead greatly increases CPU utilization by the DirectAccess server, limiting the number of active DirectAccess connections the server can efficiently handle.

Note Some load balancers can be configured to provide SSL offload for DirectAccess IP-HTTPS traffic. Although not supported, it can be an effective way to improve performance and scalability on the DirectAccess servers in some scenarios. More details can be found here: http://directaccess.richardhicks.com/ 2013/07/10/ssl-offload-for-ip-https-directaccess-traffic-from-windows-7-clients-using-f5-big-ip/.

DirectAccess Connectivity Assistant (DCA) v2.0

The Network Connectivity Assistant (NCA), included in the Windows 8.x and Windows 10 client operating systems, validates remote corporate network connectivity via the DirectAccess connection and provides a visual indication of the current status of the connection. It also provides a facility to generate and view diagnostic logs and to email them to an administrator.

Windows 7 does not include the NCA, but it can be configured with the optional DirectAccess Connectivity Assistant (DCA) v2.0,¹ which provides functionality similar to that of the NCA.

Note DCA 2.0 *must* be installed on Windows 7 clients when the deployment requires one-time password (OTP) authentication.

Configuring DCA 2.0

DCA configuration settings are managed exclusively with the Active Directory group policy. It will be necessary to deploy custom group policy templates prior to configuring the DCA. Once complete, a new Group Policy Object (GPO) will be created that contains the DCA settings. In addition, a Windows Management Instrumentation (WMI) filter will be created to ensure that only Windows 7 clients receive the DCA settings.

¹https://support.microsoft.com/en-us/kb/2666914.

Deploy Group Policy Templates

The group policy template files required for DCA 2.0 configuration are included in the downloaded .zip file. Extract the contents of the .zip file and copy the .ADMX and .ADML files contained therein to a domain controller. The **DirectAccess_Connectivity_Assistant_2_0_GP.admx** file should be copied to the **%WINDIR%\PolicyDefinitions** folder, and the **DirectAccess_Connectivity_Assistant_2_0_GP.adml** file should be copied to the **%WINDIR%\PolicyDefinitions**\enterlines\en

Create Group Policy Object

Open the Group Policy Management Console (GPMC), right-click **Group Policy Objects**, and click **New**. Provide a descriptive name for the new GPO and click **OK** (Figure 9-1).

	New GPO
Name:	
DirectAccess Client Sett	ings - Windows 7 DCA
Source Starter GPO:	
(none)	~
	OK Cancel

Figure 9-1. Create a new GPO

Note Some DCA settings are unique for each entry point in a multisite deployment. Separate GPOs for DCA settings for each entry site in the enterprise will be required.

Right-click the new GPO and choose **Edit**. Expand **Computer Configuration**, **Policies**, and then **Administrative Templates**. Highlight **DirectAccess Connectivity Assistant** and then double-click **Support Email**. Select **Enabled** and enter a support email address. Click **Next Setting** when finished (Figure 9-2).

CHAPTER 9 SUPPORT WINDOWS 7 CLIENTS

		Support Email	x
5 Support Email		Previous Setting Next Setting	
Not Configured Enabled	Comment:		^
 Disabled 			~
	Supported on:	At least Windows Server 2008 R2 or Windows 7	^ >
Options:		Help:	
Support Email admin@richardhicks	.net	Specifies the e-mail address to be used when the user starts Advanced Diagnostics and selects the option to transmit log to the DirectAccess administrator. When the user clicks Emai Logs, the default e-mail client opens a new message with the specified address in the To: field of the message, and attache the generated log files as a .cab file. The user can review the mail and add additional information before clicking Send.	files I is e-
		OK Cancel A	oply

Figure 9-2. Enter a support email address

Note The Support Email configuration is optional but recommended. It is not possible to generate diagnostic logs on the client using the DCA without defining a support email address.

Select **Enabled** and then click **Show** next to **DTEs**. Double-click a blank field and enter the Dynamic Tunnel Endpoint (DTE) IPv6 addresses using the format **PING:<DTE>**. Click **Next Setting** when finished (Figure 9-3).

	Show Contents	_ D X
DTEs		
	Value	
۶.	PING:2002:cb00:71f0::cb00:71f0	
	PING:2002:cb00:71f0:5::1	
*		
	OK	Cancel

Figure 9-3. Configure the DTEs

Note To obtain the IPv6 DTE addresses, open an elevated PowerShell command window on the DirectAccess server and execute the following command:

Get-Item –Path HKLM:\\SYSTEM\CurrentControlSet\Services\RaMgmtSvc\Config\Parameters

The **LocalNamesOn** setting is an optional setting that effectively allows the end user to disconnect the DirectAccess connection. It does this by disabling the Name Resolution Policy Table (NRPT), allowing all name-resolution requests to be sent to the DNS server that is configured on the DirectAccess client's local network adapter. Choose an option and click **Next Setting** (Figure 9-4).

CHAPTER 9 SUPPORT WINDOWS 7 CLIENTS

9		Lo	calNames	On			-		x
E LocalNamesOn				Previous Set	tting	Next Setting			
Not Configured Secondard	Comment:								^
Enabled Disabled									~
	Supported on:	At least Window	vs Server 200	8 R2 or Windo	ws 7				<u>^</u>
Options:			Help:						
			Specifies w Names", ar and instead right-click this setting DCA menu If the user : sending na servers. Ins available to configurati	whether the use and can disable d use local nar the DCA icon is disabled, th selects Prefer I ime resolution tead, the client tead, the client on.	er sees thi corporat me resolu and then ne menu Local Nar requests it uses wh mputer ir	e menu option " e resolution of fl tion. If enabled, click Prefer Loca option does not nes, DirectAcces to the internal c latever local nam its current netw	Use Lo at host the use appear orpora the reso ork	cal : name :r can es. If : on th te DN: lution	e S is
				[OK	Cancel		Арр	ly

Figure 9-4. Enable local name resolution (optional)

Select **Enabled** and click **Show** next to **Corporate Resources**. Double-click a blank field and enter the URL of an internal web resource using the format **HTTP:**<**URI**> (Figure 9-5).

	Show Contents ×
Corros	rate Pasauraan
Corpo	Tate Resources
	Value
•	HTTP:http://directaccess-webprobehost.lab.richardhicks.net/
*	
	OK Cancel

Figure 9-5. Enter the URL of an internal web resource

Note DirectAccess creates an entry in DNS for DirectAccess-WebProbeHost, which resolves to the internal IPv4 address of the DirectAccess server by default. For load-balanced configurations, it resolves to the Virtual IP Address (VIP) of the load-balanced cluster. This URL can be used, but any internal web server, with the exception of the NLS, can also be specified here. It is recommended that only one resource be entered. It is not required or recommended that multiple resources be provided. In addition, the use of HTTP resources is encouraged over Internet Control Message Protocol (ICMP) as ICMP is not always a reliable indicator of network connectivity status and may cause issues with one-time password (OTP) authentication.

The **Admin Script** setting is an optional setting that allows the administrator to define a script to be executed on the client during the diagnostic log-generation process. The output of the script will be included in the .cab file that is created when **Advanced Diagnostics** is initiated by the user. The script file can be any file that can be run at a command prompt and that sends output to the console as text. The script must not take longer than 45 seconds to run. In addition, the script file must be local to the computer and stored in a location that cannot be modified by a standard user account, as the DCA runs the script with elevated permissions. Click **Next Setting** when finished (Figure 9-6).

CHAPTER 9 SUPPORT WINDOWS 7 CLIENTS

9		Admin Script	:
Admin Script		Previous Setting Next Setting	
Not Configured Enabled Disabled	Comment:		
	Supported on:	At least Windows Server 2008 R2 or Windows 7	
Options:		Help:	
Admin Script Location	in_script.cmd	Specifies the path and file name of a script that is provided by the administrator and is run as part of the Advanced Diagnostic log generation process. The output of the script is included in the .cab file that is created as part of the collection of the logs that is initiated when the user opens the Advanced Diagnostics dialog box. The script can be a .cmd file, .bat file, or any other command that can be run at a command prompt and that prints output to the console as text. The script must complete its actions within 45 seconds. Scripts that take longer have their logs truncated. Caution This script should be installed on the client computer in a location that cannot be modified by a standard user account. The DCA runs the script with elevated permissions.	< >
		OK Cancel Apply	

Figure 9-6. Enable an admin script (optional)

Create WMI Filter

Note This step is optional for multisite deployments. In a multisite scenario, Windows 7 clients are members of a dedicated security group. The GPO can be targeted at the Windows 7 client group for the entry point without requiring a WMI filter.

In the Group Policy Management Console (GPMC) right-click **WMI Filters** and choose **New**. Provide a descriptive name and click **Add**. Enter the following WMI query and click **OK**, and then click **Save** (Figure 9-7):

select *	from	Win32	_Operatir	ngSystem	where	Version	like	"6.1%"
----------	------	-------	-----------	----------	-------	---------	------	--------

DirectAccess - W	indows 7 Clients	
Description:		
Queries:		
Namespace root\CIMv2	select * from Win32 OperatingSystem where	Add
NON TRIVITE	Version like "6.1%"	Remove
		Edit

Figure 9-7. Create a new WMI filter

Note A warning message may appear after creating the WMI filter stating that the namespace entered is not a valid namespace on the local computer or that you do not have access to this namespace on this computer. This warning message can be safely ignored.

Deploy Group Policy Object

In the GPMC, select the newly created GPO and click **Scope**. Under **Security Filtering** click **Add** and specify the DirectAccess client security group. Highlight **Authenticated Users** and click **Remove**. Finally, select the drop-down list under **WMI Filtering** and choose the WMI filter created previously (Figure 9-8).

ame		^	
Direct Access Clie	nts (LAB\DirectAccessC	ients)	
Add	Remove	Properties	
Add	Remove	Properties	

Figure 9-8. Configure security and WMI filtering

Once complete, link the GPO to the domain that the DirectAccess clients are joined to.

Installing DCA 2.0

On a 64-bit Windows 7 client, double-click **Microsoft_DirectAccess_Connectivity_Assistant_2_0_x64.msi**. On a 32-bit Windows 7 client, double-click **Microsoft_DirectAccess_Connectivity_Assistant_2_0_x86.msi**. When prompted to install the **Update for Windows (KB2666914)**, click **Yes** (Figure 9-9).

Windows Update Standalone Installer	83
Do you want to install the following Windows software update? Update for Windows (KB2666914)	
Yes No	

Figure 9-9. Install update KB2666914

Once the installation is complete, click Restart Now (Figure 9-10).

🗳 Downl	oad and Install Updates
1	Installation complete You must restart your computer for the updates to take effect.
	Restart Now Close

Figure 9-10. Restart is required after installing DCA

Note Software deployment mechanisms such as Active Directory software installation policies, System Center Configuration Manager (SCCM), or any third-party software distribution solution can be used to automate the distribution of the DCA to Windows 7 clients.

DCA Operation

The following topics will describe the operation of the DCA on a Windows 7 client.

Connectivity Status

To view corporate network connectivity status, click the DCA icon in the system tray. When the client is connected to the corporate network, or if the client has successfully connected remotely via DirectAccess or VPN, the DCA will report that corporate network connectivity is working.



Figure 9-11. DCA corporate network connectivity status

Advanced Diagnostics

To perform advanced diagnostics, right-click the DCA icon in the system tray and choose **Advanced Diagnostics** (Figure 9-12).



Figure 9-12. Launch advanced diagnostics

The DCA will automatically generate and collect diagnostic log data for review by an administrator. To view collected log data, click **Open logs directory** (Figure 9-13).

Si Microsoft DirectAccess Connectivity Assistan	t 🔀
Advanced Diagnostics	
Corporate connectivity is	working
Advanced Log File	
Email Logs About	Close

Figure 9-13. Open the log file directory

The DCA automatically generates an HTML report, which is also contained in the .cab file. The report includes connectivity status reports and diagnostic information collected from the client. If an admin script was configured, its output is recorded in a text file included here (Figure 9-14).



Figure 9-14. DCA diagnostic log files

Local DNS Resolution

To temporarily disconnect from DirectAccess and use local DNS resolution, right-click the DCA icon in the system tray and choose **Use local DNS resolution** (Figure 9-15).



Figure 9-15. Use local DNS resolution

Note Enabling local DNS resolution does not completely disable DirectAccess; it only disables the NRPT. The DirectAccess IPsec connections remain established, allowing for the full use of outbound management for DirectAccess clients even if the user has chosen to use local DNS resolution.

Summary

For the best experience, it is recommended that Windows 10 clients be used exclusively for DirectAccess. Windows 10 provides full support for all enterprise DirectAccess features, including automatic site selection and transparent failover in multisite deployments, IP-HTTPS IPv6 transition technology performance enhancements, and an integrated network connectivity status indicator.

Windows 7 clients can still be deployed with DirectAccess in Windows Server 2016, but they don't perform as well, fewer clients are supported concurrently, and in some scenarios they may require additional software (the DCA) to be deployed.

CHAPTER 10

Monitor and Report

Once DirectAccess is installed and configured, the Remote Access Management console can be used to monitor the health and status of the DirectAccess server and supporting infrastructure. If a problem is detected, its status will be indicated and helpful information for resolving the issue will be provided.

All DirectAccess connections, along with user information and details about internal resources accessed over the connection, can be logged. Log data can be stored in a local Windows Internal Database (WID), a local or remote Remote Access Dial-In User Service (RADIUS) server, or both. With logging configured, the Remote Access Management console can be used to view currently connected clients and to generate usage reports of historical user activity for compliance and auditing purposes.

System Monitoring

DirectAccess relies on supporting infrastructure services such as Active Directory, DNS, PKI, and others to provide remote access for clients. Issues or outages with any of these services can prevent access to internal resources via DirectAccess. DirectAccess constantly monitors the status and health of these dependent services with the Remote Access Management console to ensure they are accessible.

Dashboard

Select **Dashboard** in the Remote Access Management console to display an overview of the current configuration and operation status along with summary information for DirectAccess client connections (Figure 10-1).

Server Status			
 Operations Status edge1.lab.richardhicks.net DirectAccess 6to4 DNS DNS64 Domain controller IP-HTTPS IPsec NAT64 Network adapters Network location server Network security Services Operations Status page 		 Configuration Statu 5/20/2016 8:30:13 AM The configuration was distribute 	IS ^
DirectAccess and VPN Client Status			
Total active clients:	5	Total transferred data:	4.6 MB in/4.43 MB out
Total active DirectAccess clients:	2	Maximum client connections:	5
Total cumulative connections:	11		

Figure 10-1. Remote access dashboard

Note For load-balanced clusters, operations status information for all nodes in the cluster is displayed. For multisite deployments, the operations status summary information for all entry points is shown. Expanding the load-balanced cluster or entry point and selecting individual servers displays status information for the server selected.

Green checkmarks next to individual supporting services and technologies indicate they are online and healthy. These marks will change to a warning or error status for services that are degraded or unavailable. To view detailed information for any service, click the **Operations Status** page link or click **Operations Status** in the navigation tree (Figure 10-2).



Figure 10-2. Remote access dashboard displaying warning and error status

Operations Status

Select **Operations Status** to view detailed information on the status and health of supporting services and technologies. Select an individual service to view information pertaining to its current state (Figure 10-3).

		Charles			
		Status	Since	Operations State	
b.richardhicks.net	^	Working	3 seconds		
tAccess	^	Working	3 seconds		
to4		Working	26 seconds		
NS		Working	3 seconds		
NS64		Working	26 seconds		
omain controller		Working	26 seconds		
P-HTTPS		Working	26 seconds		
Osec		Working	26 seconds		
IAT64		Working	26 seconds		
letwork adapters		Working	26 seconds		
letwork location server		Working	3 seconds		
letwork security		Working	26 seconds		
ervices		Working	3 seconds		
	b.richardhicks.net tAccess to4 NS64 omain controller -HTTPS 'sec AT64 etwork adapters etwork location server etwork security ervices	b.richardhicks.net tAccess to4 NS NS64 omain controllerHTPS 'sec AT64 etwork adapters etwork location server etwork security ervices	b.richardhicks.net A Working tAccess A Working tod Working NS Working NS64 Working -HTPS Working Sec Working AT64 Working etwork adapters Working etwork location server Working etwork security Working etwork security Working	b.richardhicks.net Norking 3 seconds tAccess Norking 3 seconds tot Working 26 seconds Working 26 seconds Working 26 seconds Working 26 seconds Working 26 seconds Working 26 seconds Vorking 26 seconds Vorking 26 seconds tot working 26 seconds tot working 26 seconds tot working 26 seconds tot working 26 seconds tot work dapters Working 26 seconds twork location server Working 3 seconds tot work security Working 3 seconds tot work security Working 3 seconds	brichardhicks.net Working Seconds Working Seconds Working Seconds NS Working Z6 seconds NS64 Working 26 seconds Seconds Working 26 seconds Seconds Working 26 seconds Seconds Working 26 seconds Vorking 26 seconds Vorking 26 seconds Seconds Vorking 26 seconds Seconds Vorking 26 seconds Seconds Vorking 26 seconds Vorking 26 seconds Seconds Vorking 26 seconds Vorking 26 seconds Seconds Vorking Seconds Vorking Seconds Vorking Seconds Vorking Seconds Seconds Seconds

Figure 10-3. Operations status details

CHAPTER 10 MONITOR AND REPORT

If there is a problem with a monitored service or technology, it will be reported in the **Operations State** field. Details about the error, possible causes, and suggestions for resolving the issue are displayed on the bottom of the screen when the error is selected (Figure 10-4).

	Status	Since	Operations State
edge1.lab.richardhicks.net	▲ Critical	15 minutes 14 seconds	DirectAccess
	Critical	15 minutes, 14 seconds	DNS: Network location server
Ø 6to4	Working	15 minutes, 38 seconds	
A DNS	Warning	15 minutes, 06 seconds	Server responsiveness; Server availability
ONS64	Working	15 minutes, 38 seconds	
Oomain controller	Working	15 minutes, 38 seconds	
IP-HTTPS	Working	15 minutes, 38 seconds	
IPsec	Working	15 minutes, 38 seconds	
NAT64	Working	15 minutes, 38 seconds	
Network adapters	Working	15 minutes, 38 seconds	
Network location server	Critical	15 minutes, 14 seconds	URL availability; Server availability
Wetwork security	Working	15 minutes, 38 seconds	
Services	Working	15 minutes, 12 seconds	
DNS: Not working proper	У		
DNS: Not working proper	У		
DNS: Not working proper	У		
DNS: Not working proper rror: hterprise DNS servers (172.16.2.200) used	l by DirectAccess of	lients for name resolution ar	e not responding. This might affect
DNS: Not working proper rror: hterprise DNS servers (172.16.2.200) used rectAccess client connectivity to corpora	y I by DirectAccess of te resources.	lients for name resolution are	e not responding. This might affect
DNS: Not working proper rror: hterprise DNS servers (172.16.2.200) used rectAccess client connectivity to corpora aUSES:	y I by DirectAccess o te resources.	lients for name resolution are	e not responding. This might affect
DNS: Not working proper rror: hterprise DNS servers (172.16.2.200) used irectAccess client connectivity to corpora aUSES: One or more of the enterprise DNS serv	y I by DirectAccess of te resources.	lients for name resolution are	e not responding. This might affect
DNS: Not working proper rror: interprise DNS servers (172.16.2.200) used irectAccess client connectivity to corpora aUSES: One or more of the enterprise DNS serv Enterprise DNS servers (172.16.2.200) m	y I by DirectAccess of te resources. ers (172.16.2.200) ight be incorrectly	lients for name resolution are are not responding. configured or overloaded.	e not responding. This might affect
DNS: Not working proper FIFOT: Interprise DNS servers (172.16.2.200) used DirectAccess client connectivity to corpora CaUSES: . One or more of the enterprise DNS serv . Enterprise DNS servers (172.16.2.200) m	y I by DirectAccess of te resources. ers (172.16.2.200) ight be incorrectly	lients for name resolution are are not responding. configured or overloaded.	e not responding. This might affect

Figure 10-4. Operations status with detailed error message

Operations status information can also be viewed at the command line by opening an elevated PowerShell command window and entering the following command (Figure 10-5):

Get-RemoteAccessHealth

PS C:>> Get-RemoteAd	cessHealth					_	
Component	RemoteAccessServer	HealthState	TimeStamp	Id	OperationStatus		Î
Server 6to4 Vpn Addressing Network Security Dns IP-Https Nat64 IPsec Kerberos Domain Controller Management Servers Network Location Otp High Availability Isatap Vpn Connectivity Teredo Network Adapters Services	localhost localhost	OK OK Disabled OK OK OK Disabled OK Disabled Disabled Disabled Disabled Disabled Disabled Disabled OK OK	5/21/2016 2:37: 5/21/2016 2:37:	49 PM 26 PM			
PS C:\> _							

Figure 10-5. Get-RemoteAccessHealth PowerShell command

User Monitoring

The visibility of current client connections and which internal resources they are accessing is crucial to supporting DirectAccess. By using the Remote Access Management console, the administrator can quickly view connection status and activity for DirectAccess clients.

Remote Access Client Status

Select **Remote Client Status** to view the status for connected DirectAccess clients. Selecting an individual connection displays details about the connection and resources accessed (Figure 10-6).

nnected Clients	ss clients status				
Search	۶ پر Sear	ch 🗐 🕶 📵	•		۲
User Name	Host Name	ISP Addres	s Protocol/Tur	nnel Duration	
0	W10-1664517992.lab.richa	ardhicks.net -	IPHttps	00:00:12	
.AB\rdeckard	W10-1664517992.lab.richa	ardhicks.net -	IPHttps	17:49:19	
	W10-533712577.lab.richar	dhicks.net -	IPHttps	00:26:04	
.AB\jfsebastian	W10-1808175542.lab.richa	ardhicks.net -	IPHttps	17:49:38	
AB\rhicks	W10-1940532013.lab.richa	ardhicks.net -	IPHttps	17:50:08	
AB\etyrell	W10-1040150135.lab.richa	ardhicks.net -	IPHttps	17:50:08	
Access Details		⊙ Con	nection Det	tails	\odot
Protocol Port IP	Address	Conr	ect Using	DirectAccess	
6 88 17	2.16.1.200	Total	Bytes In	3152	
17 389 17	2.16.1.200	Total	Bytes Out	3392	
		Conr	ection start	5/22/2016 11:16:30 AM	
		Auth	antication	Machine Certificate & Llcer Ntlm	

Figure 10-6. Remote access client status

Note Some connections may not include username information. This is expected behavior that occurs when a DirectAccess client computer is connected but the user has not yet logged on. In addition, it is not uncommon to see multiple entries for the same computer. This can happen when a DirectAccess client drops its connection and reconnects—for example, when roaming between wireless access points.

Right-click on a column heading to include additional fields in the display (Figure 10-7).

P O Search	(11)	•	. ▼		
me 📍		ISP A	ddress Protocol/Tu	innel (Duration
	~	User	Name		
0150135.lab.richardhic	~	Host	Name	2	00:10:47
4517992.lab.richardhic	~	ISP A	ddress	1	0:10:43
8175542.lab.richardhic	~	Proto	col/Tunnel		0:07:47
0532013.lab.richardhic	~	Dura	tion		0:10:57
712577.lab.richardhick		IPv4	Address	3	0:10:48
		IPv6	Address		
		Туре			
		Serve	er N		
		Total	Bytes		
		Total	Bytes In		
		Total	Bytes Out		
		Conn	ection Start Time		
		Auth	entication Method		
		Activ	ity Status		
		Rate	105		
			Connect Using Total Bytes In Total Bytes Out	Direct/ 164130 143584	Access 5 4

Figure 10-7. Include additional fields to be displayed

Right-click an individual connection and choose **Details** to view detailed information and statistics about the connection (Figure 10-8).

🔄 Detailed client sta	itistics	×
Detailed c	lient statistics	
Detailed client stati	stics show all information for a specific connecti	on.
Property	Value	
User Name	LAB\rdeckard	^
Host Name	W10-1664517992.lab.richardhicks.net	
ISP Address	-	
Protocol/Tunnel	IPHttps	
Duration	00:21:34	
Activity Status	Active	
Rate	4.55 Mbps	
IPv4 Address	-	
IPv6 Address	2002:cb00:71f0:1000:54f8:ab20:2c88:56b7	
Туре	DirectAccess	
Server	edge1.lab.richardhicks.net	- 11
Total Bytes In	426848736	
Total Bytes Out	8082864	
		v
		Close

Figure 10-8. Detailed client connection information and statistics

Note The ISP address field is always blank when IP-HTTPS IPv6 transition technology is used to establish a DirectAccess connection.¹ This happens because the ISP address is derived from the IPv6 address used by the client to establish the IPsec security association with the DirectAccess server. For clients using the 6to4 or Teredo IPv6 transition technologies, their public IPv4 address is embedded in their IPv6 address. However, IP-HTTPS uses random IPv6 addresses, which prevents the DirectAccess server from collecting and displaying this information.

¹It is possible to gain much more detailed information about the DirectAccess connection, including the ISP address for IP-HTTPS connections, using Windows component event logging. More details can be found here: https://blogs.technet.microsoft.com/martin_j_solis/2015/03/20/additional-way-to-monitor-directaccess-machineuser-activity-on-windows-2012-and-2012r2-directaccess-with-component-event-logging/

Administrators can perform searches to narrow the list of displayed results. Enter text for which to search in the **Search** field and press Enter or click **Search** (Figure 10-9).

jfsebastian	×	₽ Search (Ⅲ	• 🖲 •	-		۲
Jser Name	Host Name		ISP Address	Protocol/Tunnel	Duration	
AB\jfsebastian	W10-180817554	2.lab.richardhicks.net	-	IPHttps	00:04:06	

Figure 10-9. Search connected clients

Click the **Save** icon to save the search query for future use (Figure 10-10).

ss Clients Status		
× 🔎 Search		
Host Name	ISP A	Query Name: Windows 10 Machines
W10-1664517992.lab.richardhick	s.net -	Overwrite the existing query, or type another name to save a new query. Each query consists of criteria, as well as sorting and column customizations.
W10-1808175542.lab.richardhick	cs.net -	
W10-1940532013.lab.richardhick W10-533712577.lab.richardhicks	s.net -	Save Cancel
	x p Search Host Name W10-1040150135.lab.richardhick W10-1808175542.lab.richardhick W10-1940532013.lab.richardhick W10-1940532013.lab.richardhick	x o Search (E) Host Name ISP A W10-1040150135.lab.richardhicks.net - W10-1808175542.lab.richardhicks.net - W10-1940532013.lab.richardhicks.net - W10-533712577.lab.richardhicks.net -

Figure 10-10. Save a search query

The Remote Access Management console does not allow the administrator to forcibly disconnect connected DirectAccess clients. To terminate a DirectAccess connection, open an elevated PowerShell command window and enter the following command:

```
Get-NetIPsecMainModeSA | Where-Object {$_.RemoteFirstId.Identity -like "*<computer_name>*"}
| Remove-NetIPsecMainModeSA
```

For example, to disconnect a computer named CLIENT1, the command would appear as follows:

```
Get-NetIPsecMainModeSA | Where-Object {$_.RemoteFirstId.Identity -like "*client1*"}
| Remove-NetIPsecMainModeSA
```

Note When a DirectAccess IPsec security association is terminated, the client will automatically attempt to reconnect. If the goal is to prevent a DirectAccess client from reconnecting, its computer account in Active Directory should first be disabled or deleted.

DirectAccess summary connection statistics can also be viewed at the command line by opening an elevated PowerShell command window and entering the following command (Figure 10-11):

Get-RemoteAccessConnectionStatisticsSummary



Figure 10-11. Get-RemoteAccessConnectionStatisticsSummary PowerShell command

In addition, detailed connection statistics can be viewed at the command line by entering the following command (Figure 10-12):

Get-RemoteAccessConnectionStatistics

Administrator: Windows PowerShell				-	×
PS C:\> Get-RemoteAccessConnectionS	tatistics				^
ClientIPAddress 2002:cb00:71f0:1000:7976:cff5:fc 2002:cb00:71f0:1000:54f8:ab20:2c 2002:cb00:71f0:1000:554:8392:f5 2002:cb00:71f0:1000:c92d:62db:78 2002:cb00:71f0:1000:e92d:62db:78	UserName [LAB\jfsebastian} {LAB\rdeckard} {LAB\rhicks} {LAB\rbicks} {LAB\rbity}	ConnectionDuration(s) 3398 6191 6205 6195 6195	ConnectionType DirectAccess DirectAccess DirectAccess DirectAccess DirectAccess		1
PS C:\> _					

Figure 10-12. Get-RemoteAccessConnectionStatistics PowerShell command

Accounting

DirectAccess can be configured to store log data using either Inbox or RADIUS accounting methods. Inbox accounting uses a local Windows Internal Database (WID) on each DirectAccess server to store log data. RADIUS accounting sends log data to a local or remote RADIUS server for storage. Both accounting methods can be configured at the same time, if necessary.

Note Inbox accounting must be configured in order to enable reporting functionality in the Remote Access Management console.

Inbox Accounting

Highlight **Reporting** in the Remote Access Management console and click **Configure Accounting**. Select the option to **Use inbox accounting**. Optionally, specify how long to store the account logs and click **Apply** (Figure 10-13).

Sa Configure Accounting			×
Configure Accounting Configure accounting settings for Remote A	access data logging.		
Configure settings for Remote Access account	inting.		
Select Accounting Method Use RADIUS accounting Select this setting to store logs and ge V Use inbox accounting Select this setting to store logs using to reports on this server.	enerate reports using a loca the Windows Internal Datab	I or remote RADIUS server. base (WID) and generate	
Configure Accounting Settings			
Accounting method: Inbox accounting			
Store accounting logs for last	months ~		
Used space: Free space:	0 bytes 0 bytes	0 MB 0 MB	
Mana	ge Accounting		
	O Delete all accounting	g logs	
	 Delete accounting lo 	gs for specified period	
Free (100%)	From:	5/21/2016	
	То:	5/21/2016	
	Empty		
		Apply Cance	el

Figure 10-13. Configure inbox accounting

Note After enabling inbox accounting, it is recommended that the database be optimized using guidance published by Microsoft, found here: https://technet.microsoft.com/en-us/library/mt693376.aspx.

RADIUS Accounting

Highlight **Reporting** in the Remote Access Management console and click **Configure Accounting**. If accounting is already configured, click **Configure Accounting** in the **Tasks** pane and select **Use RADIUS accounting**. Choose **RADIUS accounting** from the **Accounting Method** drop-down box, double-click the blank field, enter the RADIUS server name and shared secret, and click **Apply** (Figure 10-14).

Sa Configure Accounting			×
Configure Accoun	ting		
Configure accounting se	ettings for Remote Access data logging		
Configure settings for R	emote Access accounting.		
Select Accounting Met	thod		
✓ Use RADIUS accou	inting		
Select this setting	to store logs and generate reports usin	ng a local or remote RADIUS server.	
✓ Use inbox account	ting		
Select this setting reports on this ser	to store logs using the Windows Interr ver.	nal Database (WID) and generate	
Configure Accounting Accounting method:	RADIUS accounting ~		
RADIUS servers (queri	ed from highest to lowest score):		
	Server Name	Initial Score	
►.	radius.lab.richardhicks.net	30	
•			
l			
		Apply	Cancel

Figure 10-14. Configure RADIUS accounting

Note RADIUS server configuration and reporting options differ greatly by vendor and are outside the scope of this book. In addition, RADIUS accounting is limited and provides less detailed connection information than using Inbox accounting provides.

Reporting

To generate historical reports for DirectAccess connections, highlight **Reporting** in the Remote Access Management console, choose a **Start date** and **End date**, and click **Generate Report**. Select an entry for which to display access and connection details (Figure 10-15).

Remote A	ccess Rep	orting						
Start date: 5/2	1/2016 15	End date: 5/2	1/2016	15	Generate Report			
Usage Report								
Search		Q Q S	earch	(ii) •				۲
User Name	Host Name		ISI	P Address	Protocol/Tunnel	Duration		
-	W10-533712577	lab.richardhicks.r	et -		IPHttps	00:14:31		^
-	W10-533712577	lab.richardhicks.r	et -		IPHttps	00:13:04		
-	W10-180817554	2.lab.richardhicks	net -		IPHttps	00:05:01		
LAB\rdeckard	W10-166451799	2.lab.richardhicks	net -		IPHttps	00:05:33		
-	W10-104015013	5.lab.richardhicks	net -		IPHttos	00:05:01		~
				-				
Access Deta	ails			\odot	Connectio	n Details		\odot
Protocol Po	ort IP Address			^	Connect Using	g DirectAccess		
6 88	172.16.1.200)			Total Bytes In	18280		
6 13	5 172.16.1.200)		- 8	Total Bytes Ou	ut 16160		
6 44	5 172.16.1.200			- 8	Connection st	tart 5/21/2016 5:12:02 PM		
6 49	155 172.16.1.200)			Authentication	n Machine Certificate & U	ser Ntlm	
17 12	3 172.16.1.200)		~	ISP Address			
Server Load	Statistics							\odot
Total sessions	5:		102		Maximum concu	irrent sessions:	14	
Total DirectAd	ccess sessions:		102		Total unique use	rs:	5	
Total VPN ses	sions:		0		Unique DirectAc	cess clients:	5	
Average sessi	ions per day:		102					

Figure 10-15. Remote access reporting

Right-click on a column heading to include additional fields in the display (Figure 10-16).

77.lab.richardhicl 77.lab.richardhicl 542.lab.richardhi 992.lab.richardhi 135.lab.richardhi	× × × × × ×	ISP Address Protocol/Tunnel User Name Host Name ISP Address Protocol/Tunnel Duration IPv4 Address	Dur 00:1 00:0 00:0 00:0	14:31 13:04 05:01 05:01
		Type	De	etails
s 00 00 00 00 00 00		Server Total Bytes In Total Bytes Out Connection Start Time Health Status Authentication Method	rt	DirectAccess 18280 16160 5/21/2016 5:12 Machine Certif -

Figure 10-16. Include additional fields to be displayed

Double-click an entry to view additional detailed client statistics (Figure 10-17).

etailed client	ow all information for a specific connection.	
Property	Value	
User Name	LAB\rdeckard	^
Host Name	W10-1664517992.lab.richardhicks.net	
ISP Address	-	
Protocol/Tunnel	IPHttps	
Duration	00:05:33	
IPv4 Address	-	
IPv6 Address	2002:cb00:71f0:1000:54f8:ab20:2c88:56b7	
Туре	DirectAccess	
Server	edge1.lab.richardhicks.net	
Total Bytes In	12912	
Total Bytes Out	9352	
Total Bytes	22264	
Connection Start Time	5/21/2016 9:24:24 PM	

Figure 10-17. Detailed client statistics

Administrators can perform searches to narrow the list of displayed results. Enter text for which to search in the Search field and press Enter or click **Search** (Figure 10-18).

emote A	ccess Rep	porting					
rt date: 5/2	1/2016 15	End date:	5/21/2016	15	enerate Report		
age Report							
rdeckard		×	₽ Search	· · ·			۲
User Name	Host Name		IS	P Address	Protocol/Tunnel	Duration	
LAB\rdeckard	W10-16645179	92.lab.richard	hicks.net -		IPHttps	00:14:05	
AB\rdeckard	W10-16645179	92.lab.richard	hicks.net -		IPHttps	17:58:10	
LAB\rdeckard	W10-16645179	92.lab.richard	hicks.net -		IPHttps	00:05:33	
LAB\rdeckard	W10-16645179	92.lab.richard	hicks.net -		IPHttps	00:05:33	
LAB\rdeckard	W10-16645179	92.lab.richard	hicks.net -		IPHttos	00:05:33	
Access Det	ails			\odot	Connection	n Details	0
Protocol Po	ort IP Address				Connect Using	DirectAccess	
6 80	172.16.1.24	0			Total Bytes In	7376	
					Total Bytes Ou	t 8480	
					Connection sta	art 5/21/2016 5:12:28 PM	
					Authentication	Machine Certificate & User Kerberos	
					ISP Address	-	

Figure 10-18. Search the logged connections

Click the **Save** icon to save the search query for future use (Figure 10-19).

emote A	ccess Reporting						
rt date: 5/21	/2016 15 End date: 5	/21/2016	15	Senerate Report			
age Report							
- J							
rdeckard	م ×	Search	· · ·			\odot	
User Name	Host Name	ISP	Address	Pr Query Na	me: U	Jser - RDeckard	
LAB\rdeckard	ks.net -	IPI Overwrite	Overwrite the existing query, or type another name to save a new query. Each query consists of criteria, as well as sorting and				
LAB\rdeckard	ks.net -	IPI query. Ea					
LAB\rdeckard	W10-1664517992.lab.richardhic	ks.net -		IPI column c	ustomiz	zations.	
LAB\rdeckard	W10-1664517992.lab.richardhic	ks.net -		IPI			
LAB\rdeckard	W10-1664517992.lab.richardhic	ks.net -		IPI		Save Cancel	
Access Deta	ails		\odot	Connecti	on De	etails 📀	
Protocol Po	rt IP Address			Connect Usi	ng	DirectAccess	
6 80	172.16.1.240			Total Bytes I	1	7376	
				Total Bytes (ut	8480	
				Connection	start	5/21/2016 5:12:28 PM	
				ISP Address	211	-	

Figure 10-19. Save a search query

DirectAccess report details can also be viewed at the command line by opening an elevated PowerShell command window and entering the following command (Figure 10-20):

Get-RemoteAccessUserActivity -UserName <username> -StartDateTime <start date> -EndDateTime <end date>

🔀 Administrator: Windows Power	Shell		-	×
PS C:\> Get-RemoteAccessUser	Activity -UserNare lab\rdeckard -S	StartDateTire "5/20/2016" -EndDateTire	5/22/2016	^
ServerIpAddress 172.16.1.200 172.16.1.200 172.16.1.200 172.16.200 172.16.200	ProtocolID 6 6 6 6 6 6 6 6 6	ServerPort 135 49155 80 389 5001		
PS C:\> _				
				_

Figure 10-20. Get-RemoteAccessUserActivity PowerShell command

Summary

The DirectAccess Management Console can be used to monitor the health and status of DirectAccess and its various supporting infrastructure services. It can also be used to view near real-time DirectAccess connection statistics and user activity. DirectAccess accounting using inbox or RADIUS can be enabled to record connection and user activity, allowing for the generation of reports for compliance and auditing purposes.

CHAPTER 11

Troubleshoot

DirectAccess is a thing of beauty when it's working correctly. Typically, it *just works*, and there's little ongoing maintenance required once it is deployed. When it isn't working correctly, however, it can be quite frustrating. There are a lot of moving parts to DirectAccess, and knowing where to look first is often challenging.

DirectAccess is made up of Windows platform technologies, so many of the tools and procedures outlined in this chapter are likely to be familiar to the DirectAccess administrator. On the client side, Windows 8.x and Windows 10 make the troubleshooting effort easier with the native integration of many PowerShell commands to view DirectAccess settings and status information.

There are myriad factors that can prevent DirectAccess from working properly. By taking a systematic and methodical approach to the troubleshooting process, often the issue can be identified and resolved quickly.

It's important to understand that this chapter is not a comprehensive troubleshooting guide. It cannot cover all deployment options and every possible failure scenario. However, it will provide the administrator with details and information that can be applied to troubleshoot most common deployment scenarios. The tools and techniques described here can be used to troubleshoot more complex deployment scenarios when required.

DirectAccess Client Connection Process

The following outlines the process of a DirectAccess client making a successful connection to the DirectAccess server and accessing resources on the Internal network. Use this as a reference so as to understand where the connection process is failing and where it is best to focus troubleshooting efforts.

- 1. A DirectAccess client computer is added to a security group and receives DirectAccess client settings via group policy.
- 2. When the DirectAccess client is started, or after any network interface status change, the DirectAccess client enables the Public firewall profile and detects if it is inside or outside the network by attempting to contact the NLS.
- **3.** If the DirectAccess client computer can successfully connect to the NLS (receives a 200 OK response to an HTTP GET, the certificate is valid, trusted, and the subject name matches), the client enables the Domain firewall profile, and no attempt to establish a DirectAccess connection is made.
- 4. If the DirectAccess client computer cannot successfully connect to the NLS, the Name Resolution Policy Table (NRPT) is activated and the client will attempt to establish a DirectAccess connection.
- **5.** An IPv6 transition technology is selected, an entry point is selected, and a connection is made to the DirectAccess server.

- 6. The DirectAccess client attempts to connect to a domain controller to authenticate. Connection Security Rules (CSRs) in the Windows firewall are triggered, and IPsec security associations are established. In most deployment scenarios, there are two distinct connections made. The first is the infrastructure tunnel, authenticated using the computer certificate and its AD computer account (NTLM). The second is the user (intranet) tunnel, authenticated using the computer certificate and tkerberos).
- 7. If strong user authentication is enabled, the user must supply those credentials after logging on to their device.
- 8. Once the user has successfully authenticated, they will have full access to the Internal network.
- **9.** On Windows 8.x and Windows 10 clients, the client will attempt to resolve the name of the web-probe host URL and establish a connection. If successful, the connection status in the UI will indicate "Connected."

Server and Client Configuration

Before troubleshooting DirectAccess connectivity, the configuration of the DirectAccess server, client, and supporting infrastructure should be reviewed to ensure that all systems are capable of supporting DirectAccess communication.

DirectAccess Server

To support DirectAccess connectivity, the server must meet all installation prerequisites, be configured correctly, and have proper network connectivity both inbound and outbound.

Group Policy

DirectAccess server settings are applied via Active Directory Group Policy Objects (GPOs). Ensure that the DirectAccess Server Settings policy is applied to the DirectAccess server by opening an elevated PowerShell command window and entering **gpresult** /**r** /**scope:computer** (Figure 11-1).


Figure 11-1. Confirm DirectAccess Server GPO application

In addition, verify that the server has received the latest GPOs by entering **gpupdate** /**force** in an elevated PowerShell command window. Once complete, open the Remote Access Management console and highlight **Dashboard**. The configuration status should have a green checkmark and indicate that the configuration was distributed successfully (Figure 11-2).



Figure 11-2. Configuration distributed successfully

Note For multisite deployments, confirm the configuration status for each entry point by highlighting Operations Status in the Remote Access Management console and then selecting each entry point individually.

Server Health

In the Remote Access Management console, highlight **Operations Status** and ensure that the DirectAccess server and all supporting infrastructure services are healthy and operational (Figure 11-3). If any components or services are unhealthy or unavailable, resolve them before continuing.

Operations Status					
Name		Status	Since	Operations State	
edge1.lab.richardhicks.net	•	Working	21 minutes, 19 seconds		
OirectAccess	^	Working	21 minutes, 19 seconds		
🕑 6to4		Working	26 minutes, 19 seconds		
Ø DNS		Working	21 minutes, 19 seconds		
Ø DNS64		Working	26 minutes, 19 seconds		
Opmain controller		Working	26 minutes, 19 seconds		
IP-HTTPS		Working	26 minutes, 19 seconds		
IPsec		Working	26 minutes, 19 seconds		
NAT64		Working	26 minutes, 19 seconds		
Network adapters		Working	26 minutes, 19 seconds		
Network location server		Working	21 minutes, 19 seconds		
Network security		Working	26 minutes, 19 seconds		
Services		Working	21 minutes 19 seconds		

Figure 11-3. Verify DirectAccess operations status (GUI)

Optionally, the administrator can confirm DirectAccess health status by entering the following command in an elevated PowerShell command window (Figure 11-4):

Get-RemoteAccessHealth | Where-Object HealthState -NE Disabled | Format-Table -Autosize

🔀 Administrator: Windows	PowerShell					-	×
PS C:\> Get-RemoteAcces	sHealth Where-Obj	ect HealthSta	ate -NE Disable	ed Fo	ormat-Table -AutoSize		^
Component	RemoteAccessServer	Health State	TimeStamp		Id OperationStatus		
Server 6to4 Network Security Dns IP-Https Nat64 IPsec Domain Controller Network Location Server Network Adapters Services PS C:\>	localhost localhost localhost localhost localhost localhost localhost localhost localhost localhost localhost localhost localhost	0K 0K 0K 0K 0K 0K 0K 0K 0K 0K 0K	6/4/2016 4:01 6/4/2016 3:56 6/4/2016 3:56 6/4/2016 3:56 6/4/2016 3:56 6/4/2016 3:56 6/4/2016 3:56 6/4/2016 3:56 6/4/2016 3:56 6/4/2016 4:01	:34 PM :34 PM :34 PM :34 PM :34 PM :34 PM :34 PM :35 PM :34 PM :34 PM :34 PM			

Figure 11-4. Verify DirectAccess operations status (PowerShell)

Network Connectivity

The DirectAccess server must have the correct Windows firewall profiles assigned to its network interfaces. In addition, it is crucial that the DirectAccess server have network connectivity both inbound and outbound to allow DirectAccess clients to connect to the DirectAccess server, and to allow clients to connect to internal resources.

Firewall Profiles

When the DirectAccess server is configured with two network adapters, ensure that the Internal network adapter has been assigned the Domain firewall profile, and that the External network adapter has been assigned the Public profile. This can be confirmed by opening an elevated PowerShell command window and entering the following command:

```
Get-NetConnectionProfile | Select-Object Name, NetworkCategory
```

Alternatively, the firewall profile can be found by opening an elevated command prompt window and entering the following command:

```
Netsh advfirewall show currentprofile
```

Internal

The DirectAccess server must be able to connect to all internal networks and services. This includes domain controllers, internal DNS servers, systems-management servers, and any servers that will be accessed by remote DirectAccess clients. Verify that the DirectAccess server can reach all remote internal subnets and services, as necessary. For DirectAccess servers configured with two network adapters, incorrect or missing static routes are often the cause of internal network connectivity issues.¹

Internet

The DirectAccess server must be able to reach the public Internet. To verify outbound connectivity, open an elevated PowerShell command window and enter the **Test-NetConnection** command (Figure 11-5).

```
Administrator: Windows PowerShell – – – ×

PS C:\> Test-NetConnection 

ComputerName : internetbeacon.msedge.net

RemoteAddress : 13.107.4.52

InterfaceAlias : External

SourceAddress : 203.0.113.240

PingSucceeded : True

PingReplyDetails (RTT) : 14 ms

PS C:\>
```

Figure 11-5. Verify Internet connectivity using Test-NetConnection

The DirectAccess server itself must also be reachable from the public Internet. First, confirm that the DirectAccess server's public hostname resolves to the correct IP address by using the **Resolve-DnsName** PowerShell command (Figure 11-6).

¹https://directaccess.richardhicks.com/2013/06/19/network-interface-configuration-formultihomed-windows-server-2012-directaccess-servers/

Mathematical Administrator: Windows PowerShell					-	×
PS C:\> Resolve-DnsName da.richardhicks.net						^
Name	Туре	TTL	Section	IPAddress		
da.richardhicks.net	A	86400	Answer	203.0.113.240		
PS C:\> _						
						_

Figure 11-6. Verify public hostname resoultion using the Resolve-DnsName PowerShell command

If name resolution is working correctly, confirm that the DirectAccess server can accept incoming IP-HTTPS connections by entering the following PowerShell command on a Windows 8.x or Windows 10 client connected to the public Internet (Figure 11-7):

Test-NetConnection -Port 443 <FQDN>

```
Administrator: Windows PowerShell – C ×

PS C:\> Test-NetConnection -Port 443 da.richardhicks.net

ComputerName : da.richardhicks.net

RemoteAdress : 203.0.113.240

RemotePort : 443

InterfaceAlias : External

SourceAddress : 203.0.113.1

PingReplyDetails (RTT) : 0 ms

TcpTestSucceeded : True

PS C:\> _
```

Figure 11-7. Test IP-HTTPS connectivity using Test-NetConnection

Note The use of ICMP (PING) alone is not always a reliable indicator of network connectivity, as it can be (and often is) blocked by firewalls. Use **Test-NetConnection -Port** or the Nmap² tool (described later in this chapter) to positively confirm network connectivity whenever possible.

Name Resolution

The DirectAccess server must be able to resolve internal hostnames in order to support DirectAccess connections. Verify that the DirectAccess server can resolve names in all internal domains by entering the following command in an elevated PowerShell command window (Figure 11-8):

Resolve-DnsName <domain>



Figure 11-8. Verify internal name resolution using Resolve-DnsName

Authentication

Domain communication is vital for DirectAccess, as the machine and the user are both authenticated when connecting remotely. Ensure proper domain controller communication from the DirectAccess server by entering the following command in an elevated PowerShell command window (Figure 11-9):

nltest.exe /sc_verify:<domain>

²https://nmap.org/



Figure 11-9. Verfiy domain communication using nltest.exe

Certificates

DirectAccess uses an SSL certificate for the IP-HTTPS IPv6 transition technology and, optionally, a computer certificate for IPsec authentication and encryption.

SSL Certificate

Verify the SSL certificate is valid, trusted, and includes the Server Authentication Enhanced Key Usage (EKU). The certificate must be installed in the local computer certificate store and must include the private key. Also, the Subject field must match the public hostname defined in Step 2 of the Remote Access configuration setup on the DirectAccess server. When supporting Windows 7 clients, the Certificate Revocation List (CRL) must be publicly accessible.

Computer Certificate

For many deployment scenarios, the DirectAccess server must also have a computer certificate to support IPsec authentication and encryption. The certificate must be issued by a Public Key Infrastructure (PKI) with a minimum key length of 1024 bits. It must be signed using a minimum of Secure Hash Algorithm 1 (SHA1) and include the Client Authentication EKU. It must be valid (not expired), trusted, have a private key, and be installed in the local computer certificate store. The certificate must also share a common root Certification Authority (CA) with the DirectAccess clients.

IPv6

IPv6 must not be disabled on the DirectAccess server. This can be confirmed by checking the **HKLM\SYSTEM\ CurrentControlSet\Services\Tcpip6\Parameters\DisabledComponents** registry key. It should not exist. If it does, it must be set to 0. In addition, all IPv6 transition technologies on the DirectAccess server must be enabled.

Windows Firewall

The Windows firewall must be enabled for all profiles on the DirectAccess server. This can be verified by issuing the following command in an elevated PowerShell command window (Figure 11-10):

Get-NetFirewallProfile -PolicyStore ActiveStore | Format-Table Name, Enabled



Figure 11-10. Verify the Windows firewall is enabled for all profiles using the Get-NetFirewallProfile PowerShell command

Note Third-party firewalls can be installed on the DirectAccess server, but the Windows firewall must not be disabled. In addition, the Windows firewall must be registered for CSRs. This can be verified by entering the **netsh advfirewall show global** command in an elevated command prompt window and confirming that the Windows firewall is listed for the **ConSecRuleCategory** category.

Services

The following services must be running on the DirectAccess server in order to support DirectAccess connections:

- IP Helper (IPHlpSvc)
- Windows Firewall (Mpssvc)
- Base Filtering Engine (BFE)
- IPsec Policy Agent (PolicyAgent)
- IKE and AuthIP IPsec Keying Modules (IKEEXT)
- KDC Proxy Server Services (KPSSVC)³
- RemoteAccess Management Services (RaMgmtSvc)

These services can be viewed by using the Services management console (services.msc) or by using the **Get-Service** PowerShell command.

³This service is only required when the option to enable Windows 7 client computers to connect via DirectAccess is not selected.

Unsupported Configurations

There are a number of unsupported DirectAccess configurations that may also prevent DirectAccess from working correctly. When troubleshooting, it is recommended to consult Microsoft's DirectAccess Unsupported Configurations guide.⁴

DirectAccess Client

To support DirectAccess connectivity, the client must meet installation prerequisites, be configured correctly, and have proper network connectivity both inbound and outbound.

Operating System SKU

DirectAccess is only supported with the following Windows client operating systems:5

- Windows 10 Enterprise
- Windows 10 Education
- Windows 7 Enterprise
- Windows 7 Ultimate

DirectAccess will not function on any version of the Home or Professional editions. To confirm the client operating system version, open the **Control Panel** and navigate to **System and Security** and then **System** (Figure 11-11).

⁴https://technet.microsoft.com/en-us/library/dn464274(v=ws.11).aspx.

⁵Although not commonly used as client operating systems, the Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, and Windows Server 2016 server operating systems are also supported DirectAccess clients.

CHAPTER 11 ■ TROUBLESHOOT

	System				-		×
÷	- 🔶 👻 🛧 🔛 > Control Pan	nel > System and Security > Sys	stem 🗸 (Search C	Control Panel		,p
	Control Panel Home	View basic information	about your computer				0
🦻	Device Manager Remote settings	Windows edition Windows 10 Enterprise	—				_
♥♥	System protection Advanced system settings	© 2016 Microsoft Corporat	ion. All rights reserved.	Vinc	woc	'S 1	0
		System Processor: Installed memory (RAM): System type: Pen and Touch: Computer name, domain, and Computer name: Full computer name: Computer description: Domain:	Intel(R) Xeon(R) CPU E5-1660 v3 @ 3.00GHz 2.99 0 2.00 GB 64-bit Operating System, x64-based processor No Pen or Touch Input is available for this Display workgroup settings client1 client1.lab.richardhicks.net	SHz	⊜ Chz	inge sett	ings
See also Security and Maintenance		Windows activation Windows is activated Rea Product ID:	d the Microsoft Software License Terms		Change	e produc	t key

Figure 11-11. Confirm supported Windows SKU

Alternatively, the **systeminfo.exe** utility can be used to view the client operating system version (Figure 11-12).

🔀 Administrator: Windows Pow	verShell	-	×
PS C:\> systeminfo.exe			^
Host Name: OS Name: OS Version: DS Manufacturer: OS Configuration: OS Build Type: Registered Owner: Registered Organization:	CLIENT1 Microsoft Windows 10 Enterprise Nic.0.10386 N/A Build 10586 Microsoft Corporation Member Workstation Multiprocessor Free Setup		
Product ID: Original Install Date: System Boot Time: System Model: System Model: System Type: Processor(s): BIOS Version: Windows Directory: Bystem Directory: Boot Device: System Locale: Input Locale: Time Zone: Total Physical Memory:	6/4/2016, 10:02:22 AM 6/6/2016, 1:31:25 PM Microsoft Corporation Virtual Machine x64-based PC 1 Processor(s) Installed. [01]: Intel64 Family 6 Model 63 Stepping 2 GenuineIntel ~2993 Mhz Microsoft Corporation Hyper-V UEFI Release v1.0, 11/26/2012 C:\Windows C:\Windows\system32 (Device\HarddiskVolume2 en-us;English (United States) en-us;English (United States) (UTC-08:00) Pacific Time (US & Canada) 2.045 MB		
Available Physical Memory: Virtual Manual Memory: Virtual Manual Memory:	2,049 MB 689 MB 3,197 MB 		_

Figure 11-12. Confirm supported Windows SKU

Group Policy

DirectAccess server settings are applied via Active Directory Group Policy Objects (GPOs). Ensure that the server settings policy is applied to the DirectAccess server by entering **gpresult** /**r** /**scope:computer** in an elevated PowerShell command window (Figure 11-13):



Figure 11-13. Confirm the DirectAccess client GPO application

Additionally, the **Get-DAClientExperienceConfiguration** PowerShell command can be used to confirm that the client has received the DirectAccess settings via the group policy and that the IPv6 addresses listed for the **IPsecTunnelEndpoints** match the IPv6 addresses on the DirectAccess server (Figure 11-14).

Z Administrator: Windows PowerShell		-	×
PS C:\> Get-DAClientExperienceCor	figuration		^
Description CorporateResources IPsecTunnelEndpoints CustomCommands PreferLocalNamesAllowed UserInterface PassiveMode SupportEmail FriendlyName ManualEntryPointSelectionAllowed GslbFqdn ForceTunneling	: DA Client Settings : {HTTP:http://directaccess-WebProbeHost.lab.richardhicks.net} : {PING:2002:cb00:71f0::cb00:71f0, PING:2002:cb00:71f0:5::1} : True : True : False : admin@richardhicks.net : Workplace Connection : True : Default		
PS C:\> _			

Figure 11-14. Confirm the DirectAccess settings using PowerShell

Network Connectivity

The DirectAccess client must have connectivity to the public Internet and be able to successfully resolve the public hostname of the DirectAccess server—or of the entry point in a multisite deployment. Confirm that the client has Internet access by viewing the status of the network connection icon in the system notification area. It should indicate that Internet access is available (Figure 11-15).



Figure 11-15. Confirm Internet access

Alternatively, the **Test-NetConnection** and **Resolve-DnsName** PowerShell commands can be used to confirm that the client has an active Internet connection and that it can successfully resolve public hostnames.

Domain Connectivity

The DirectAccess client must have a valid computer account in Active Directory. Ensure proper domain controller communication from the DirectAccess client by entering **nltest.exe** /**sc_verify:**<**domain**> in an elevated command prompt window when the client is on the Internal network.

Certificates

For some deployment scenarios, the DirectAccess client must also have a computer certificate to support IPsec authentication and encryption. The certificate must be issued by a PKI with a minimum key length of 1024 bits. It must be signed using a minimum of SHA1 and include the Client Authentication EKU. It must be valid (not expired), trusted, have a private key, and be installed in the local computer certificate store. The certificate must also share a common root CA with the DirectAccess server.

IPv6

IPv6 must not be disabled on the DirectAccess client. This can be confirmed by checking the **HKLM**\ **SYSTEM\CurrentControlSet\Services\Tcpip6\Parameters\DisabledComponents** registry key. It should not exist. If it does, it must be set to 0.

IPv6 Transition Technologies

DirectAccess clients are commonly on the public IPv4 Internet and must use an IPv6 transition technology to establish a connection to the DirectAccess server. Not all IPv6 transition technologies are required to be enabled. The following sections provide details for ensuring they are configured correctly where enabled.

6to4

To view 6to4 configuration and state information, use the **Get-Net6to4Configuration** PowerShell command, or **netsh interface 6to4 show interface** or **show state**. If the 6to4 IPv6 transition technology is enabled, enter **ipconfig** in a command prompt window and confirm that a Global Unicast Address⁶ (GUA) is assigned to the 6to4 tunnel adapter (Figure 11-16).

Figure 11-16. 6to4 IPv6 transition tunnel adapter address assignment

[%]https://technet.microsoft.com/en-us/library/cc759208(v=ws.10).aspx

Teredo

To view Teredo configuration and state information, use the **Get-NetTeredoConfiguration** or **Get-NetTeredoState** PowerShell commands, or **netsh interface teredo show state**. If the Teredo IPv6 transition technology is supported, enter **ipconfig** in a command prompt window and confirm that a GUA IPv6 address is assigned to the Teredo tunnel adapter (Figure 11-17).

```
Administrator: Windows PowerShell
                                                                                                                                      X
PS C:\> ipconfig
                                                                                                                                                 ~
Windows IP Configuration
Ethernet adapter External:
  Connection-specific DNS Suffix :
Link-local IPv6 Address . . . : fe80::fc2b:ebbd:7fdc:7a9a%4
IPv4 Address . . . . . . : 203.0.113.1
Subnet Mask . . . . . . . : 255.255.255.0
Default Gateway . . . . . : 203.0.113.254
Tunnel adapter 6TO4 Adapter:
   Tunnel adapter Teredo Tunneling Pseudo-Interface:
   Connection-specific DNS Suffix . :
                                              2001:0:cb00:71f0:90:12d0:34ff:8efe
fe80::90:12d0:34ff:8efe%6
   :
   Default Gateway . . . .
                                            .
PS C:\> _
```

Figure 11-17. Teredo IPv6 transition tunnel adapter address assignment

IP-HTTPS

A DirectAccess client will always have an IP-HTTPS tunnel adapter. To view IP-HTTPS configuration and state information, use the **Get-NetIPHttpsConfiguration** or **Get-NetIPHttpsState** PowerShell commands, or **netsh interface httpstunnel show interfaces** or **show statistics**. If an IP-HTTPS connection cannot be made, the output of these commands often includes error codes that can be helpful in identifying the source of the problem.

Ensure that the IP-HTTPS tunnel adapter has a valid IPv6 address by entering **ipconfig** in a command prompt window and confirming that a GUA or Unique Local Address (ULA) IPv6 address is assigned to the IP-HTTPS tunnel adapter (Figures 11-18 and 11-19).



Figure 11-18. IP-HTTPS tunnel adapter with GUA IPv6 address



Figure 11-19. IP-HTTPS tunnel adapter with ULA IPv6 address

Note All network interfaces in Windows have link-local IPv6 addresses assigned to them. However, this is not enough to support DirectAccess connectivity. There must be at least one IPv6 transition tunnel adapter that has a GUA or ULA IPv6 address assigned to it.

Services

The following services must be running on the DirectAccess client to support a DirectAccess connection:

- IP Helper (IPHlpSvc)
- Windows Firewall (Mpssvc)
- Base Filtering Engine (BFE)
- IPsec Policy Agent (PolicyAgent)
- IKE and AuthIP IPsec Keying Modules (IKEEXT)

These services can be viewed by using the Services management console (services.msc) or by using the **Get-Service** PowerShell command.

Note The Network Connectivity Assistant (Ncasvc) must also be running in order to provide DirectAccess connection-status information in the GUI and via PowerShell, and to support smart card and one-time password (OTP) authentication.

Windows Firewall

The Windows firewall must be enabled for both the Public and Private profiles on the DirectAccess client. This can be verified by issuing the **Get-NetFirewallProfile –PolicyStore ActiveStore** command or the **netsh advfirewall show all** command and confirming that the Public and Private profiles are enabled (Figure 11-20).

CHAPTER 11 TROUBLESHOOT

🔁 Administrator: Windows PowerShell		-	×
PS C:\> Get-NetFirewallProfile -F	PolicyStore ActiveStore Format-Table Name. Enabled		^
Name Enabled			
Domain True Private True Public True			
PS C:\> netsh advfirewall show al	n		
Domain Profile Settings:			
State Firewall Policy LocalFirewallRules LocalConSecRules InboundUserNotification RemoteManagement UnicastResponseToMulticast	ON BlockInbound,AllowOutbound N/A (GPO-store only) N/A (GPO-store only) Enable Disable Enable		
Logging: LogAllowedConnections LogDroppedConnections FileName MaxFileSize	Disable Disable %systemroot%\system32\LogFiles\Firewall\pfirewall.log 4096		
Private Profile Settings:			
State Firewall Policy LocalFirewallRules LocalConSecRules InboundUserNotification RemoteManagement UnicastResponseToMulticast	ON BlockInbound,AllowOutbound N/A (GPO-store only) N/A (GPO-store only) Enable Disable Enable		
Logging: LogAllowedConnections LogDroppedConnections FileName MaxFileSize	Disable Disable %systemroot%\system32\LogFiles\Firewall\pfirewall.log 4096		
Public Profile Settings:			
State Firewall Policy LocalFirewallRules	ON BlockInbound,AllowOutbound N/A (GPO-store only)		~

Figure 11-20. Verfiy that the Public and Private Windows firewall profiles are enabled

DirectAccess connections can only be established if the *current* network connection is using either the Public or Private profile. To view the Windows firewall profile assigned to the current network connection, use the **Get-NetConnectionProfile** PowerShell command or the **netsh advfirewall monitor show currentprofile** command to ensure that either the Public or Private profile is active (Figure 11-21).

2 Administrator: Windows PowerShell		×
PS C:\> Get-NetConnectionProfile		^
Name : Network InterfaceAlias : External InterfaceIndex : 4 NetworkCategory : Public IPv4Connectivity : Internet IPv6Connectivity : NoTraffic		1
PS C:\> netsh advfirewall monitor show currentprofile		
Public Profile: Network Ok.		
PS C:\>		
		_

Figure 11-21. Verify the current network connection is using either the Public or Private Windows firewall profile

Note When the client is provisioned for DirectAccess, firewall rules to allow Teredo and IP-HTTPS IPv6 transition technology communication are automatically configured. Ensure these rules are not subsequently disabled or that other firewall rules don't prevent them from working correctly.

Connectivity Troubleshooting

When a DirectAccess client can't establish a connection or access internal resources remotely, the following steps can help you identify the root cause.

Connection Security Rules

If the DirectAccess server has received the DirectAccess Client Settings group policy, it should be configured with Connection Security Rules (CSRs) that establish IPsec Security Associations (SAs) between the client and server. Ensure that these rules are in place by opening the Windows firewall with Advanced Security (WFAS) management console (wf.msc) and highlighting **Connection Security Rules** (Figure 11-22).



Figure 11-22. Connection security rules in the Windows firewall

Double-click the **DirectAccess Policy-ClientToInfra** CSR, select the **Advanced** tab, and then click **Customize** in the IPsec tunneling section. Confirm that the remote tunnel endpoint IPv6 address is correct and assigned to the DirectAccess server (Figure 11-23).

Customize IPsec Tunneling Settings	×						
Connections from Endpoint 1 to Endpoint 2 will pass through the specified tunnel endpoints. Tunnel endpoints are generally gateway servers.							
Note: When IPsec tunneling is used, the authentication mode must be set to "Require inbound and outbound" or "Require inbound and clear outbound" (for gateway devices).							
Use IPsec tunneling							
Apply authorization							
Exempt IPsec protected connections							
Local tunnel endpoint (closest to Endpoint 1): IPv4: Any Edit IPv6: Any							
Remote tunnel endpoint (closest to Endpoint 2):							
IPv6: 2002:cb00:71f0::cb00:71f0							
0K Cancel							

Figure 11-23. Identify remote tunnel endpoint IPv6 address

Repeat these steps on the DirectAccess Policy-ClientToCorp CSR.

Ping Tunnel Endpoints

Attempt to ping the DirectAccess IPsec tunnel endpoint addresses from a DirectAccess client. In addition to the method described previously, the IPsec tunnel endpoint addresses can be found in Windows 8.x and Windows 10 using the **Get-DAClientExperienceConfiguration** PowerShell command (Figure 11-24).

Z Administrator: Windows PowerShell		-	×
PS C:\> Get-DAClientExperienceCor	figuration		^
Description CorporateResources IPsecTunnelEndpoints CustomCommands PreferLocalNamesAllowed UserInterface PassiveMode SupportEmail FriendlyName ManualEntryPointSelectionAllowed GslbFgdn ForceTunneling	: DA Client Settings : {HTTP:http://directaccess-WebProbeHost.lab.richardhicks.net} : {PING:2002:cb00:71f0::cb00:71f0, PING:2002:cb00:71f0:5::1} : True : True : False : False : admin@richardhicks.net : Workplace Connection : True : Default	-	
PS C:\> _			

Figure 11-24. Identify IPsec tunnel endpoint IPv6 addresses (Windows 8.x/10)

In Windows 7, enter **netsh advfirewall consec show rule name="DirectAccess Policy-ClientToCorp" type=dynamic** and **netsh advfirewall consec show rule name="DirectAccess Policy-ClientToInfra" type=dynamic** and then ping the **RemoteTunnelEndpoint** IPv6 addresses (Figure 11-25).

Administrator: Windows PowerShell	– 🗆 X
PS C:\> netsh advfirewall consec s	how rule name="DirectAccess Policy-ClientToCorp" type=dynamic
Rule Name:	DirectAccess Policy-ClientToCorp
Enabled:	Yes
Profiles:	Private, Public
Type:	Dynamic
Mode:	Tunnel
LocalTunnelEndpoint:	Any
RemoteTunnelEndpoint:	2002:cb00:71f0:5::1
Endpoint1:	Any
Endpoint2:	2002:cb00:71+0:1::/64,+da7:aa10:e7cd:7777::/96
Protocol:	Any
Action:	RequireInRequireOut
Auth1:	ComputerCert
Auth1CAName:	DC=net, DC=richardhicks, DC=Iab, CN=LAB-ISSUING-CA
Auth1CertMapping:	No
Auth1ExcludeCAName:	No
Auth1CertType:	Root
Auth1HealthCert:	No
Auth2:	UserKerb
MainModeSecMethods:	DHGroup2-AES128-SHA256,DHGroup2-AES128-SHA1,DHGroup2-3DES-SHA1
QuickModeSecMethods:	ESP:SHA1-AES192+60min+100000kb,ESP:SHA1-AES128+60min+100000kb
ExemptIPsecProtectedConnections:	No
ApplyAuthorization:	No
0k.	
PS C:\> netsh advfirewall consec s	how rule name="DirectAccess Policy-ClientToInfra" type=dynamic
Rule Name:	DirectAccess Policy-ClientToInfra
Enabled:	Vac
Enabled: Profiles:	Yes Private Public
Enabled: Profiles: Type:	Yes Private,Public Donamir
Enabled: Profiles: Type: Mode:	Yes Private,Public Dynamic Tunnel
Enabled: Profiles: Type: Mode: LocalTunnelEndpoint:	Yes Private,Public Dynamic Tunnel
Enabled: Profiles: Type: Node: LocalTunnelEndpoint: RemoteTunnelEndpoint:	Yes Private,Public Dynamic Tunnel Any 2002-ch00-71f0ch00-71f0
Enabled: Profiles: Type: Mode: LocalTunnelEndpoint: RemoteTunnelEndpoint:	Yes Private,Public Dynamic Tunnel Any 2002:cb00:71f0::cb00:71f0
Enabled: Profiles: Type: Node: LocalTunnelEndpoint: RemoteTunnelEndpoint: Endpoint1: Endpoint2:	Yes Private,Public Dynamic Tunnel Any 2002:cb00:71f0::cb00:71f0 Any fda7:aa10:e7cd:7777:ac10:1c8_2002:cb00:71f0.1:0:5ef
Enabled: Profiles: Type: Mode: LocalTunnelEndpoint: RemoteTunnelEndpoint: Endpoint1: Endpoint2: e:172 16 1 2002-2002-2000-7160-1-0	Yes Private,Public Dynamic Tunnel Any 2002:cb00:71f0::cb00:71f0 Any fda7:aa10:e7cd:7777::ac10:1c8,2002:cb00:71f0:1:0:5ef Sefe:172.156.1.200.2002:cb00:71f0:33331
Enabled: Profiles: Type: Mode: LocalTunnelEndpoint: RemoteTunnelEndpoint: Endpoint1: Endpoint2: e:172.16.1.200-2002:cb00:71f0:1:0: Protoro1	Yes Private,Public Dynamic Tunnel Any 2002:cb00:71f0::cb00:71f0 Any fda7:aa10:e7cd:7777::ac10:1c8,2002:cb00:71f0:1:0:5ef Sefe:172.16.1.200,2002:cb00:71f0:3333::1
Enabled: Profiles: Type: Mode: LocalTunnelEndpoint: RemoteTunnelEndpoint: Endpoint1: Endpoint2: er172.16.1.200-2002:cb00:71f0:1:0: Protocol: Action:	Yes Private,Public Dynamic Tunnel Any 2002:cb00:71f0::cb00:71f0 Any fda7:aa10:e7cd:7777::ac10:1c8,2002:cb00:71f0:1:0:5ef Sefe:172.16.1.200,2002:cb00:71f0:3333::1-2002:cb00:71f0:3333::1 Any RequireInPequireOut
Enabled: Profiles: Type: Mode: LocalTunnelEndpoint: RemoteTunnelEndpoint: Endpoint1: Endpoint2: e:172.16.1.200-2002:cb00:71f0:1:0: Protoco1: Action: Auth1:	Yes Private,Public Dynamic Tunnel Any 2002:cb00:71f0::cb00:71f0 fda7:aa10:e7cd:7777::ac10:1c8,2002:cb00:71f0:1:0:5ef Sefe:172.16.1.200,2002:cb00:71f0:3333::1-2002:cb00:71f0:3333::1 Any RequireInRequireOut ComputerCent
Enabled: Profiles: Type: Mode: LocalTunnelEndpoint: Endpoint1: Endpoint2: e:172.16.1.200-2002:cb00:71f0:1:0: Protocol: Auth1: Auth1: Auth2:	Yes Private,Public Dynamic Tunnel Any 2002:cb00:71f0::cb00:71f0 fda7:aa10:e7cd:7777::ac10:1c8,2002:cb00:71f0:1:0:5ef 5efe:172.16.1.200,2002:cb00:71f0:3333::1-2002:cb00:71f0:3333::1 Any RequireInRequireOut ComputerCert Denote Denotchardbicks Denote AB-ISSUINC-CA
Enabled: Profiles: Type: Mode: LocalTunnelEndpoint: RemoteTunnelEndpoint: Endpoint2: endpoint2: e:172.16.1.200-2002:cb00:71f0:1:0: Protocol: Action: Auth1: Auth1: Auth2GName: Auth2cetManning:	Yes Private,Public Dynamic Tunnel Any 2002:cb00:71f0::cb00:71f0 fda7:aa10:e7cd:7777::ac10:1c8,2002:cb00:71f0:1:0:5ef Sefe:172.16.1.200,2002:cb00:71f0:3333::1 Any RequireInRequireOut ComputerCert DC=net, DC=richardhicks, DC=lab, CN=LAB-ISSUING-CA
Enabled: Profiles: Type: Node: LocalTunnelEndpoint: Endpoint1: Endpoint2: e:172.16.1.200-2002:cb00:71f0:1:0: Protocol: Auth1CAName: Auth1CAName: Auth1CertMapping: Auth2CAName:	Yes Private,Public Dynamic Tunnel Any 2002:cb00:71f0::cb00:71f0 fd3:aa10:e7cd:7777::ac10:1c8,2002:cb00:71f0:1:0:5ef Sefe:172.16.1.200,2002:cb00:71f0:3333::1-2002:cb00:71f0:3333::1 Any RequireInRequireOut ComputerCert DC=richardhicks, DC=lab, CN=LAB-ISSUING-CA No
Enabled: Profiles: Type: Mode: LocalTunnelEndpoint: Endpoint1: Endpoint2: e:172.16.1.200-2002:cb00:71f0:1:0: Protocol: Action: Auth1: Auth1CAName: Auth1ExcludeCAName	Yes Private,Public Dynamic Tunnel Any 2002:cb00:71f0::cb00:71f0 fda7:aa10:e7cd:7777::ac10:1c8,2002:cb00:71f0:1:0:5ef Sefe:172.16.1.200,2002:cb00:71f0:3333::1-2002:cb00:71f0:3333::1 Any RequireInRequireOut ComputerCert DC=net, DC=richardhicks, DC=lab, CN=LAB-ISSUING-CA No Poot
Enabled: Profiles: Type: Mode: LocalTunnelEndpoint: Endpoint1: Endpoint2: e:172.16.1.200-2002:cb00:71f0:1:0: Protocol: Action: Auth1CertMapping: Auth1CertMapping: Auth2cetMapping: Auth2cetJudeCAName: Auth1CertType: Auth1ertType:	Yes Private,Public Dynamic Tunnel Any 2002:cb00:71f0::cb00:71f0 fd3:aa10:e7cd:7777::ac10:1c8,2002:cb00:71f0:1:0:5ef Sefe:172.16.1.200,2002:cb00:71f0:3333::1-2002:cb00:71f0:3333::1 Any RequireInRequireOut ComputerCert DC=met, DC=richardhicks, DC=lab, CN=LAB-ISSUING-CA No No Root No
Enabled: Profiles: Type: Mode: LocalTunnelEndpoint: Endpoint1: Endpoint2: ei72.16.1.200-2002:cb00:71f0:1:0: Protocol: Auth1: Auth1CAName: Auth1ExcludeCAName: Auth1ExcludeCAName: Auth1LextUdeCAName: Auth1Le	Yes Private,Public Dynamic Tunnel Any 2002:cb00:71f0::cb00:71f0 fda7:aa10:e7cd:7777::ac10:1c8,2002:cb00:71f0:1:0:5ef Sefe:172.16.1.200,2002:cb00:71f0:3333::1-2002:cb00:71f0:3333::1 Any RequireInRequireOut ComputerCert DC=net, DC=richardhicks, DC=lab, CN=LAB-ISSUING-CA No No Root No

Figure 11-25. Identify IPsec tunnel endpoint IPv6 addresses (Windows 7)

Note If the tunnel endpoint IPv6 addresses do not respond to ping requests, ensure that the Windows firewall on the DirectAccess server is configured to allow inbound ICMPv6 echo requests.

If the IPsec tunnel endpoint addresses are correct and cannot be reached, investigate issues related to the IPv6 transition technology as outlined previously in this chapter.

Ping Internal Servers

Attempt to ping an internal server by its hostname. The name should resolve to an IPv6 address and respond accordingly (Figure 11-26).



Figure 11-26. Ping internal server by hostname

If it does not respond to the ping, ensure that the internal server is configured to allow inbound ICMPv4 echo requests. If it does not resolve to an IPv6 address, verify IPsec connection establishment and name resolution.

IPsec Connections

To view current IPsec connections, open the WFAS management console, expand **Monitoring**, and then expand **Security Associations** and highlight **Main Mode** (Figure 11-27).

Windows Firewall with Advance File Action View Help	ed Security						- 0	×
Windows Firewall with Advance Connection Security Rules Connection Security Rules Firewall Connection Security Rules Conn	Main Mode Local Address 2001:0:cb00: 2001:0:cb00: 2001:0:cb00:	Remote Address 2002:cb00;71f0 2002:cb00;71f0 2002:cb00;71f0	1st Authentication Method Computer certificate Computer certificate Computer certificate Computer certificate	2nd Authentication Method User (NTLMv2) User (NTLMv2) User (Kerberos V5) User (Kerberos V5)	Encryption AES-CBC AES-CBC AES-CBC	Integrity SHA-256 SHA-256 SHA-256 SHA-256	Actions Main Mode View	•

Figure 11-27. View IPsec security associations

Connections shown with a **2nd Authentication Method** of **User (NTLMv2)** indicate a successful infrastructure tunnel connection. Connections shown with a **2nd Authentication Method** of **User (Kerberos V5)** indicate a successful intranet tunnel connection.

Note IPsec connections can also be viewed at the command line using the **Get-NetIPSecMainModeSA** and **Get-NetIPsecQuickModeSA** PowerShell commands. In addition, **netsh advfirewall monitor show mmsa** and **netsh advfirewall monitor show qmsa** can be used.

If there are no IPsec connections established to the first tunnel endpoint IPv6 address (the infrastructure tunnel), the cause is often related to certificate authentication. If there are no IPsec connections established to the second tunnel endpoint IPv6 address (the intranet tunnel), the cause is often related to user authentication. Refer to the appropriate sections earlier in this chapter for guidance on resolving issues with those technologies.

Name Resolution

If name resolution is not working, the DirectAccess client will fail to authenticate and will not be able to access internal resources. DirectAccess uses the Name Resolution Policy Table (NRPT) to ensure that only name-resolution requests for the Internal namespace are sent to the DNS64 service running on the DirectAccess server. Ensure that the NRPT is configured correctly and that only namespaces on the Internal network are defined in the NRPT.

In Windows 8.x and Windows 10, the NRPT can be viewed by entering **Get-DnsClientNrptPolicy** in an elevated PowerShell command window (Figure 11-28).

CHAPTER 11 I TROUBLESHOOT

Marinistrator: Windows PowerShell		-		×
PS C:\> Get-DnsClientNrptPolicy				^
Namespace QueryPolicy SecureNameQueryFallback DirectAccessIPsecCARestriction DirectAccessProxyName DirectAccessProxyType DirectAccessPoxyType DirectAccessQueryIPsecEncryption DirectAccessQueryIPsecRequired NameServers DnsSecIPsecCARestriction DnsSecQueryIPsecEncryption DnsSecQueryIPsecEncryption DnsSecQueryIPsecRequired DnsSecValidationRequired	nls.lab.richardhicks.net UseDefault False False False			
Namespace QueryPolicy SecureNameQueryFallback DirectAccessIPsecCARestriction DirectAccessIPsecCARestriction DirectAccessProxyType DirectAccessEnabled DirectAccessQueryIPsecEncryption DirectAccessQueryIPsecRequired NameServers DisSecIPsecCARestriction DnsSecQueryIPsecEncryption DnsSecQueryIPsecRequired DnsSecVallidationRequired NameEncoding	: .lab.richardhicks.net 2002:cb00:71f0:3333::1 NoProxy False False False Utf8WithoutMapping			
PS C:\> _				
			_	_

Figure 11-28. View the NRPT using PowerShell

In Windows 7, the NRPT can be viewed by entering **netsh namespace show effectivepolicy** in an elevated PowerShell command window (Figure 11-29).

```
Administrator: Windows PowerShell – C ×

PS C:\> netsh namespace show effectivepolicy

DNS Effective Name Resolution Policy Table Settings

Settings for nls.lab.richardhicks.net

DirectAccess (Certification Authority) :

DirectAccess (CPS Servers) :

DirectAccess (Proxy Settings) : Use default browser settings

Settings for .lab.richardhicks.net

DirectAccess (CPS Servers) :

DirectAccess (CPS Servers) :

DirectAccess (CPS Servers) :

DirectAccess (Proxy Settings) : 2002:cb00:71f0:3333::1

DirectAccess (Proxy Settings) : Bypass proxy

PS C:\> _
```

Figure 11-29. View the NRPT using Netsh

To test name resolution on the DirectAccess client, enter the **Resolve-DNSName** PowerShell command (Figure 11-30).

Administrator: Windows PowerShell					-	×
PS C:\> Resolve-DnsName app1 Name app1.lab.richardhicks.net	Туре АААА	TTL 600	Section	IPAddress fda7:aa10:e7cd:7777::ac10:1ca		^
PS C:\> _						
						_

Figure 11-30. Testing name resolution using the Resolve-DNSName PowerShell command

The Windows nslookup.exe utility will not work by default, because it is not NRPT-aware and will send all name-resolution requests to the DNS servers configured on the network adapter. However, nslookup will work by providing the address of the DNS server (the DNS64 service) to be used for the query (Figure 11-31).

```
Administrator: Windows PowerShell – – ×

PS C:\> nslookup appl 2002:cb00:71f0:3333::1

Server: UnKnown

Address: 2002:cb00:71f0:3333::1

Non-authoritative answer:

Name: appl.1ab.richardhicks.net

Addresses: fda7:aa10:e7cd:7777::ac10:1ca

172.16.1.202

PS C:\> _
```

Figure 11-31. Testing name resolution using the nslookup command

Helpful Tools and Commands

The following is a list of helpful tools and commands that can make DirectAccess connectivity troubleshooting easier.

DirectAccess Connection Status

The DirectAccess connection status can be viewed in the Windows 8.x and Windows 10 user interface. Click the network connection icon in the system notification area and then click **Workplace Connection**. Here, the current DirectAccess connection status will be displayed. If additional action is required or the connection failed, it will be indicated here (Figure 11-32).



Figure 11-32. DirectAccess connection status

Note It is possible that a DirectAccess connection can be established successfully while the status indicator still indicates a "Connecting" status. This can happen when the web-probe host URL is not reachable from the DirectAccess client. The web-probe host URL is defined in Step 1 of the Remote Access configuration setup. Ensure that this URL can be resolved correctly and that it is reachable over the DirectAccess connection. When an external load balancer is used, additional configuration on the load balancer is required if the web-probe host is hosted on the DirectAccess servers.⁷

Alternatively, DirectAccess connection status can be viewed using the **Get-DAConnectionStatus** PowerShell command. A successful connection will show the status as **Connected Remotely**. If the client cannot establish a connection, it will provide additional information about the failure.

Detailed logging and configuration information can also be gathered by clicking **Collect** in the Troubleshooting info section.

⁷https://directaccess.richardhicks.com/2014/08/12/directaccess-clients-in-connecting-statewhen-using-external-load-balancer/

Note To generate diagnostic logs on the DirectAccess client, a help desk email address must be specified in Step 1 of the Remote Access configuration setup. In addition, an email program must also be installed and configured on the client.

DirectAccess Connectivity Assistant

The DirectAccess Connectivity Assistant (DCA) v2.0 is an optional component that can be installed on Windows 7 clients to provide a visual indicator of DirectAccess connectivity status. It can also be used to automate the collection of diagnostic logging information. Configuration of the DCA is covered in Chapter 9, "Supporting Windows 7 Clients."

IPsec Auditing

Enabling IPsec auditing can help you identify issues related to authentication for DirectAccess connections. To enable IPsec auditing, enter the following commands in an elevated command prompt window on the DirectAccess client:

- auditpol.exe /set /subcategory:"IPsec Main Mode" /success:enable /failure:enable
- auditpol.exe /set /subcategory:"IPsec Quick Mode" /success:enable /failure:enable
- auditpol.exe /set /subcategory:"IPsec Extended Mode" /success:enable / failure:enable

After enabling IPsec auditing, restart the client computer and attempt to connect to resources on the Internal network. If unsuccessful, search the security event logs for event IDs between 4600 and 5500 for details about IPsec authentication and connection establishment.

Firewall Logging

The Windows firewall may be blocking connections inbound or outbound on the DirectAccess client. Disabling the firewall is not an option, as it is required for DirectAccess connectivity. Enabling firewall logging allows the administrator to see if any traffic is being denied. To enable firewall logging, enter the following commands in an elevated PowerShell command window:

```
Set-NetFirewallProfile -All -LogFileName c:\firewalllog.txt -LogMaxSizeKilobytes 32767
-LogAllowed True -LogBlocked True
```

Alternatively, firewall logging can be enabled by entering the following commands in an elevated command prompt window:

```
netsh advfirewall set allprofiles logging filename c:\firewalllog.txt
netsh advfirewall set allprofiles logging maxfilesize 32767
netsh advfirewall set allprofiles logging allowedconnections enable
netsh advfirewall set allprofiles logging droppedconnections enable
```

Note There is a known issue with Windows 8.1 and Windows Server 2012 R2, where enabling firewall logging can cause the firewall service to freeze and crash.⁸ Before enabling firewall logging on these operating systems, ensure that the May 2016 update rollup for Windows 8.1 and Windows Server 2012 R2 (KB3156418) has been installed.⁹

Message Analyzer

The Microsoft Message Analyzer¹⁰ is helpful for troubleshooting application connectivity over DirectAccess. The Message Analyzer allows the administrator to view network traffic *inside* the IPsec tunnels. After installation, run the Message Analyzer as an administrator. Click **Favorite Sessions** and choose **Loopback and Unencrypted IPSEC**. Attempt to connect to the internal resource and stop the trace when complete. Once finished, network trace information from inside the IPsec tunnel will be visible (Figure 11-33).



Figure 11-33. Viewing network communciation inside the DirectAccess IPsec tunnels using Message Analyzer

Common things to look for when troubleshooting application connectivity over DirectAccess are calls being made by the application directly to IPv4 addresses or name-resolution request failures.

⁸https://support.microsoft.com/en-us/kb/3155768

[%]https://support.microsoft.com/en-us/kb/3156418

¹⁰https://www.microsoft.com/en-us/download/details.aspx?id=44226

Nmap

The Network Mapper¹¹ (Nmap) tool can be helpful when validating the network communication path between the DirectAccess client and server. A discovery script¹² is also available that allows the administrator to query the DirectAccess server to ensure that the IP-HTTPS listener is responding (Figure 11-34).



Figure 11-34. Testing DirectAccess IP-HTTPS connectivity using Nmap

Tracing

Tracing can be performed to gather low-level information about the DirectAccess connection. It also includes detailed information about the DirectAccess configuration and environment that can be used in additional investigations by the administrator or a Microsoft support engineer. To enable tracing, enter the following commands in an elevated command prompt window:

```
netsh trace start scenario=directaccess report=yes capture=yes tracefile=c:\datrace.etl
netsh wfp capture start file=c:\wfpcap.cab
Get-NetAdapter | Restart-NetAdapter
```

Note On Windows 7 clients, disable and enable the network adapter in the GUI to force the client to restart the DirectAccess connection.

Reproduce the issue by attempting to connect to an internal resource. After attempting to connect, stop the capture and trace by entering the following commands:

netsh wfp capture stop netsh trace stop

"https://nmap.org/

¹²https://directaccess.richardhicks.com/2015/11/30/directaccess-ip-https-discovery-scriptfor-nmap/

DirectAccess Client Troubleshooting Tool

The Windows DirectAccess Client Troubleshooting Tool¹³ is a utility from Microsoft that automates the testing and evaluation of the DirectAccess connection. After downloading the tool, click **Run Tests** to begin. After the tests have been completed, click on a test to show detailed results and information about the specific test performed (Figure 11-35).

DirectAccess Client Troubleshooting Tool	-		×		
Run Tests					
1 Interface Test					
Network Location Tests					
IP Connectivity Tests					
Windows Firewall Tests					
Certificate Tests					
Found 1 machine certificates on this client compute	er.				
The certificate [5D0000004EE03287B0B13404C000	000000	0004] co	ontain		
The trust chain for the certificate [5D0000004EE0]	3287B0	3134040	0000		
Finished running certificate tests.					
Infrastructure Tunnel Tests					
User Tunnel Tests					
Successfully reached 2002:cb00:71f0::cb00:71f0, RT	T is 2 r	nsec.			
Successfully reached 2002:cb00:/ If0:5::1, RTT is T	msec.				
Successfully reached HTTP probe at http://directaccess-WebProbeHos					
Post-Checks Script					
• Post-cliecks script					
<			>		
Advanced Options					
Run a script: Browse					
Enable debug mode:					
Show the trace log file: Open					
		Versio	n: 1.4.4.0		
	Comp	eted	.:		

Figure 11-35. DirectAccess client connectivity troubleshooting tool

¹³https://www.microsoft.com/en-us/download/details.aspx?id=41938

Additionally, highly detailed information about the tests being performed and their results, along with client configuration information, is available by viewing the trace log file generated by the tool.

Summary

To effectively troubleshoot DirectAccess connectivity issues, it is essential to have a fundamental understanding of how DirectAccess works correctly. At its core, DirectAccess connectivity is nothing more than IPsec tunnels established by the client and server. DirectAccess client and server settings, distributed through the Active Directory Group Policy, configure the client and server to support secure, authenticated, and encrypted communication over the public Internet.

When troubleshooting DirectAccess connectivity, remain objective and focus on the basics. Start at the beginning and take it one step at a time. Don't be overwhelmed by the complexity of DirectAccess. By following the guidance in this chapter, the DirectAccess administrator should be able to resolve many of the most common issues that might prevent DirectAccess from working correctly.

CHAPTER 12

Migrate to Windows Server 2016 DirectAccess

For organizations that have previously deployed DirectAccess using Windows Server 2008 R2, Forefront Unified Access Gateway (UAG) 2010, Windows Server 2012, or Windows Server 2012 R2, migrating to DirectAccess in Windows Server 2016 can be accomplished in one of two ways.

If DirectAccess is deployed with Windows Server 2012 or 2012 R2, it is possible to perform an in-place upgrade of the operating system to Windows Server 2016. However, this is not generally recommended, as experience has shown limited success using this approach. A safer and much less disruptive way to upgrade is to create a parallel deployment of DirectAccess using Windows Server 2016 and then migrate users to the new infrastructure.

If DirectAccess is deployed with Windows Server 2008 R2 or UAG 2010, an in-place upgrade is not supported. In these scenarios, implementing DirectAccess using a parallel deployment and migrating users to the new infrastructure is the only available migration path.

Requirements

Much of the existing DirectAccess supporting infrastructure can be reused when configuring a parallel deployment of DirectAccess using Windows Server 2016. Services such as Active Directory, Public Key Infrastructure (PKI), and the Network Location Server (NLS) can be used by both implementations at the same time without conflict. However, a parallel deployment will require the following unique components.

IP Addresses

It probably goes without saying, but the new DirectAccess servers will require unique IP addresses. This includes public IP addresses assigned to the DirectAccess server, or to the edge firewall for perimeter/DMZ deployments.

Public Hostname

The public hostname for the new DirectAccess deployment must be unique. It must also have a corresponding entry in the public DNS, and an SSL certificate with a matching subject name must be used. Multi-SAN SSL certificates are not supported,¹ so a unique certificate will be required. Alternatively, a wildcard certificate can be used.

^{&#}x27;https://directaccess.richardhicks.com/2016/03/28/directaccess-and-multi-san-ssl-certificatesfor-ip-https/

Security Groups

Unique security groups for the new deployment must be configured. Once configured, DirectAccess clients from the original deployment will be moved to these new security groups, enabling them to receive settings for the new deployment and connect to the new infrastructure.

Group Policy Objects

Distinct Active Directory Group Policy Objects (GPOs) are required for the new deployment. These new GPOs will be applied to the security groups created previously. If the DirectAccess Connectivity Assistant (DCA) v2.0 has been deployed for Windows 7 clients, a new DCA GPO must be created for the new deployment.

Configuration

Prepare the first DirectAccess server for the new Windows Server 2016 deployment as outlined in Chapter 3. During the configuration, be sure to specify a unique security group when prompted by the Remote Access Setup Wizard (Figure 12-1).

Semote Access Setup	×
DirectAccess Clien Enable DirectAccess for r	t Setup managed computers in specified security groups, and configure client settings.
Deployment Scenario Select Groups Network Connectivity Assistant	Select one or more security groups containing client computers that will be enabled for DirectAccess. Image: Clients2016 (LAB\DirectAccessClients2016) Image: Add Remove Image: Clients2016 (LAB\DirectAccessClients2016) Image: Clients2016 (LAB\DirectAccessClients2016) Image: Clients2
	< Back Next > Finish Cancel

Figure 12-1. Select a unique Active Directory security group

Enter the unique public hostname for the new deployment (Figure 12-2).

Sa Remote Access Setup		×
Remote Acces	ss Server Setup ccess and VPN settings.	1
Network Adapters Authentication	Select the network topology of the server. Edge Behind an edge device (with two network adapters) Behind an edge device (with a single network adapter) In this topology, the Remote Access server is deployed at the edge of the internal corporate network and is configured with two adapters. One adapter is connected to the internal network. The other is connected to the Internet. Type the public name or IPv4 address used by clients to connect to the Remote Access server: da2.richardhicks.net	
	< Back Next > Finish	Cancel

Figure 12-2. Enter the unique public hostname
CHAPTER 12 MIGRATE TO WINDOWS SERVER 2016 DIRECTACCESS

Before applying the changes, review the configuration settings. Click **Change** next to **GPO settings** to specify unique names for the DirectAccess client and server settings GPOs (Figure 12-3). Click **OK** and **Apply** to finish.

SPO Na	ames	X
	GPO Names	
	GPOs that will be used for Di	rectAccess deployment.
Review the settings if re	GPOs that will be applied to the client or quired.	computers security group and the DirectAccess server in the relevant domains. Modify GPO
0	DirectAccess client GPO	
2	GPO containing DirectAccess client	settings:
	LAB	DirectAccess Client Settings 2016 Browse
	Direct Access server GPO	
	GPO containing DirectAccess server	settings:
	LAB	DirectAccess Server Settings 2016 Browse
* - A nev	v Group Policy Object (GPO) will be cre	ated
• Use ex	sisting Group Policy Object	
		OK Canad
		UK Cancel

Figure 12-3. Enter unique names for DirectAccess client and server settings GPOs

Client Migration

Once a new, parallel deployment of DirectAccess is in place, migrating existing clients from a previous version of DirectAccess to Windows Server 2016 only requires moving their AD computer account from their original DirectAccess security group to the security group designated for them for the new deployment. Once a DirectAccess client restarts, it will receive the DirectAccess client settings for the new deployment and automatically establish a connection to the new infrastructure. This also applies to DirectAccess clients that are currently outside the network.

Note Use caution to ensure that clients belong to only one DirectAccess client settings security group.

For testing purposes, it is possible to force a DirectAccess client to update its group membership status and apply new group policy settings without restarting. To accomplish this, open an elevated PowerShell command window and enter the following commands:

klist -lh 0 -li 0x3e7 purge
gpupdate /force

Note When performing these steps on a remotely connected DirectAccess client, it may be necessary to restart the network connection. Either disable and re-enable the network interface in the GUI, or enter the following command in an elevated PowerShell command window:

Get-NetAdapter | Restart-NetAdapter

Additional Use Cases

Creating a parallel deployment of DirectAccess is not only useful for migrating from previous versions of DirectAccess, but is also beneficial in the following scenarios.

QA and Testing

Having a parallel deployment to perform configuration testing and quality assurance can often be helpful. The QA/Test deployment can be used to validate configuration changes and verify updates without potential negative impact on the production environment.

Delegated Administration

DirectAccess lacks support for delegated administration. For organizations that are geographically dispersed, or that have multiple business units that operate autonomously, it may be beneficial to deploy multiple instances of DirectAccess and assign unique administrators to each deployment instead of enabling multisite.

Configuration Changes

Some configuration changes can be disruptive to remote DirectAccess clients. For example, making changes to PKI or enabling multisite can potentially cut off access for DirectAccess clients outside the network, requiring them to physically come back to the office or connect remotely using client-based VPN to update their group policy. Implementing a parallel deployment and migrating users over can reduce the impact and prevent service disruption for existing remote clients.

Unique Client Requirements

There are a few important DirectAccess settings that are global in scope and apply to all provisioned DirectAccess clients. For example, enforcing strong user authentication using smart cards or one-time passwords (OTP) usually applies to all clients. If the requirement for smart card authentication applies only to a subset of users, implementing a separate DirectAccess deployment will be required.

Summary

Deploying DirectAccess with Windows Server 2016 in parallel with a previous version of DirectAccess can greatly ease the pain of performing an in-place upgrade, while at the same time allowing for a measured and controlled rollout for existing DirectAccess clients.

In addition, having multiple individual DirectAccess deployments provides greater deployment flexibility for organizations with unique requirements based on geography or business units.

CHAPTER 13

Managing Out

One of the key differentiators of DirectAccess compared to traditional, client-based VPN is that the DirectAccess connection is bidirectional. Not only can remote users seamlessly access applications and data on the corporate network from anywhere, but IT administrators can also initiate outbound network connections to connected DirectAccess clients to perform remote administration, wherever they are, and even if a user is not logged on.

From a client perspective, DirectAccess is an IPv6-only solution. The DirectAccess client communicates with the DirectAccess server using IPv6 exclusively. Conversely, if an IT administrator on the internal network wants to connect to a remote DirectAccess client, the internal machine must also use IPv6.

IPv6

IPv6 must be used to support outbound connections to DirectAccess clients from internal management systems; for example, from a management workstation or server. Microsoft's formal guidance for outbound management with DirectAccess is to deploy IPv6 on the internal network natively. Unfortunately, that is easier said than done. Deploying IPv6 is non-trivial, and is a task that should not be taken lightly. Since most organizations do not have IPv6 deployed, an IPv6 transition technology can be used to enable managing out.

ISATAP

The Intrasite Automatic Tunnel Addressing Protocol (ISATAP)¹ is an IPv6 transition technology that allows IPv6 communication over an IPv4 network. Unlike 6to4, Teredo, and IP-HTTPS, which are used by the DirectAccess *client* to tunnel IPv6 traffic over the IPv4 Internet, ISATAP is used by systems on the internal network to initiate communication outbound to connected DirectAccess clients.

Supportability

Outbound management using the DirectAccess server as the ISATAP router is only supported for singleserver DirectAccess deployments.² Using ISATAP on the DirectAccess server is not supported when load balancing (NLB or external) is enabled or multisite is configured. For these deployment scenarios, an external ISATAP router must be configured.

http://www.ietf.org/rfc/rfc5214.txt

²https://technet.microsoft.com/en-us/library/dn464274(v=ws.11).aspx#bkmk_isa

ISATAP Router

The ISATAP router is automatically installed and configured when DirectAccess is enabled. No additional configuration is required by the administrator to enable managing out on the DirectAccess server.

Note If there is a firewall between the DirectAccess server and the internal network, it must be configured to allow inbound and outbound IP protocol 41 in order for ISATAP to work correctly.

ISATAP Client

To enable outbound management using ISATAP, a client machine (workstation or server) must be configured to use the DirectAccess server as its ISATAP router. This is accomplished in one of several ways.

Manual Configuration

A workstation or server can be manually configured to use the DirectAccess server as its ISATAP router by using PowerShell. Open an elevated PowerShell command window and enter the following commands:

```
Set-NetISATAPConfiguration -State Enabled
Set-NetISATAPConfiguration -Router <DirectAccess server IPv4 address or hostanme>
```

Alternatively, ISATAP can be configured manually by opening an elevated command prompt window and entering the following commands:

```
Netsh interface isatap set state enabled
Netsh interface isatap set router <DirectAccess server IPv4 address or hostname>
```

Note The drawback to using this method is that manual configuration is error prone and does not scale well. However, it can be effective for initial testing, or if only a small number of management workstations and/ or servers require outbound management functionality.

DNS

All supported versions of Windows, in addition to many other operating systems, will automatically enable and configure an ISATAP tunnel adapter after successfully resolving the hostname **ISATAP** to an IPv4 address. The quick and simple way to do this for DirectAccess is to add an A Host record in the internal DNS called ISATAP that resolves to the IPv4 address of the Internal network interface of the DirectAccess server (Figure 13-1).

🔲 nls	Host (A)	172.16.1.220
edge1	Host (A)	172 16 1 240
🗐 isatap	Host (A)	172.16.1.240
edge2	Host (A)	172.16.1.241
Client1	Host (A)	172.16.1.4

Figure 13-1. ISATAP DNS entry

For security reasons, most DNS servers will not respond to queries for ISATAP by default. On Windows DNS servers, for example, ISATAP is included in the DNS Global Query Block list.³ To configure a Windows DNS server to respond to queries for ISATAP, open an elevated PowerShell command window and enter the following command:

```
Set-DnsServerGlobalQueryBlockList -List wpad
```

Confirm that ISATAP has been removed from the Global Query Block List by entering the following PowerShell command:

Get-DnsServerGlobalQueryBlockList

Alternatively, the Global Query Block List can be updated by opening an elevated command prompt window and entering the following command:

```
dnscmd.exe /config /globalqueryblocklist wpad
```

The Global Query Block List can be viewed by entering the following command:

```
dnscmd.exe /info /globalqueryblocklist
```

Note The drawback to using this method is that every workstation and server in the enterprise that successfully resolves ISATAP to an IPv4 address will have an ISATAP tunnel adapter. This is often unnecessary and can produce unexpected results.

Group Policy

For many organizations, outbound management is required only for a few specific machines, commonly administrator workstations and systems-management servers. An Active Directory Group Policy Object (GPO) can be used to restrict the deployment of ISATAP settings to only those machines that specifically require manage-out functionality.

To do this, create a unique entry in DNS (*not* called ISATAP) that resolves to the internal IPv4 address of the DirectAccess server (Figure 13-2).

³https://technet.microsoft.com/en-us/library/cc794902(v=ws.10).aspx

🔲 nls	Host (A)	172.16.1.220
edge1	Hest (A)	172.16.1.240
isatap-da	Host (A)	172.16.1.240
edge2	Host (A)	172.16.1.241
client1	Host (A)	172.16.1.4

Figure 13-2. Custom ISATAP DNS entry

Open the Group Policy Management console, then right-click **Group Policy Objects** and choose **New**. Enter a descriptive name for the new GPO. Right-click the newly created GPO and choose **Edit**. Expand **Computer Configuration**, **Policies**, **Administrative Templates**, **Network**, and **TCP/IP Settings**. Highlight **IPv6 Transition Technologies** and double-click **Set ISATAP Router Name**. Choose **Enabled** and enter the unique DNS name created previously, then click **Next Setting** (Figure 13-3).

8		Set ISATAP Router Name	¢		
Set ISATAP Router Name		Previous Setting Next Setting			
 Not Configured Enabled Disabled 	Comment: Supported on:	n: At least Windows Server 2008 R2 or Windows 7			
Options:		Help:			
Options: Enter a router or relay name: isatap-da.lab.richardhicks.net		This policy setting allows you to specify a router name or Internet Protocol version 4 (IPv4) address for an ISATAP router. If you enable this policy setting, you can specify a router name or IPv4 address for an ISATAP router. If you enter an IPv4 address of the ISATAP router in the text box, DNS services are not required. If you disable or do not configure this policy setting, the local host setting is used.	<		
		OK Cancel Apply			

Figure 13-3. Set the ISATAP router name

9		Set ISATAP State
Set ISATAP State		Previous Setting Next Setting
O Not Configured	Comment:	<u>^</u>
Enabled		
○ Disabled	Supported on	V
	supported on:	At least Windows Server 2008 R2 or Windows 7
Options:		Help:
Options: Select from the following states: Enabled State v		This policy setting allows you to configure Intra-Site Automatic ^ Tunnel Addressing Protocol (ISATAP), an address-to-router and host-to-host, host-to-router and router-to-host automatic tunneling technology that is used to provide unicast IPv6 connectivity between IPv6 hosts across an IPv4 intranet. If you disable or do not configure this policy setting, the local host setting is used. ■ If you enable this policy setting, you can configure ISATAP with one of the following settings: ■ Policy Default State: If the ISATAP router name is resolved successfully, the host will have ISATAP configuration. If the ISATAP router through stateless address auto-configuration. If the ISATAP router name is not resolved successfully, ISATAP connectivity is not available on the host using the corresponding IPv4 address. Policy Enabled State: If the ISATAP name is resolved successfully. ■
		OK Cancel Apply

Choose Enabled, then select Enabled State from the drop-down list and click OK (Figure 13-4).

Figure 13-4. Set the ISATAP state

Link the GPO to an Organizational Unit (OU) that contains the workstations and servers that will require DirectAccess managing out. Alternatively, security filtering can be used to restrict the application of the GPO to individual machines or a security group that includes those machines, as required.

Connectivity Testing

Confirm that the management system configured to use ISATAP has an ISATAP tunnel adapter with a unicast IPv6 address assigned to it (Figure 13-5).

Administrator: Windows PowerShell	_	x
PS C:\> ipconfig		^
Windows IP Configuration		
Ethernet adapter Ethernet:		
Connection-specific DNS Suffix .: Link-local IPv6 Address : fe80::68a5:bfce:c44a:9183%12 IPv4 Address : 172.16.1.202 Subnet Mask : 255.255.255.0 Default Gateway : 172.16.1.254		
Tunnel adapter isatap.{2ED5E832-30FC-4F0A-B547-29F9E94B521D}:		
Connection-specific DNS Suffix .: IPv6 Address: 2002:cb00:71f0:1:0:5efe:172.16.1.202 Link-local IPv6 Address: fe80::5efe:172.16.1.202%14 Default Gateway: fe80::5efe:172.16.1.240%14 PS C:\> _		

Figure 13-5. ISATAP tunnel adapter with unicast IPv6 address

If an ISATAP tunnel adapter is present and is configured with a unicast IPv6 address, attempt to ping a remotely connected DirectAccess client by its hostname. The name should resolve to an IPv6 address. If the firewall on the DirectAccess client is configured to allow inbound ICMPv6 on the Public and Private profiles, it will respond accordingly (Figure 13-6).

Administrator: Windows PowerShell	_ D X
PS C:\> ping client1	^
Pinging client1.lab.richardhicks.net [2002:cb00:71f0:1000:80b1:a5b3:9552:53c1] with 32 bytes of data: Reply from 2002:cb00:71f0:1000:80b1:a5b3:9552:53c1: time=4ms Reply from 2002:cb00:71f0:1000:80b1:a5b3:9552:53c1: time=2ms Reply from 2002:cb00:71f0:1000:80b1:a5b3:9552:53c1: time=1ms Reply from 2002:cb00:71f0:1000:80b1:a5b3:9552:53c1: time=1ms	
<pre>Ping statistics for 2002:cb00:71f0:1000:80b1:a5b3:9552:53c1: Packets: Sent = 4, Received = 4, Lost = 0 (0% loss), Approximate round trip times in milli-seconds: Minimum = 1ms, Maximum = 4ms, Average = 2ms PS C:\>_</pre>	

Figure 13-6. Ping a remotely connected DirectAccess client by name

Note If the management workstation is unable to resolve the DirectAccess client's hostname to an IPv6 address, ensure that the client has successfully registered its IPv6 address in the internal DNS.

Remote Management

Once a management system has been configured to use ISATAP, it can be used to fully manage remotely connected DirectAccess clients. For example, on a management workstation or server, an administrator can initiate a Remote Desktop Protocol (RDP) session to a DirectAccess client, or use any number of popular management tools and techniques, such as Windows Remote Assistance, System Center Configuration Manager (SCCM) Remote Control, VNC, TeamViewer, PowerShell Remoting, and much more. In addition, file shares are accessible, and native Windows system-management tools like the Computer Management console and Performance Monitor function properly as well⁴ (assuming client firewall policy allows it; see later in this chapter for more details).

DirectAccess Management Computers

A user must be logged on to the DirectAccess client for an ISATAP-enabled management system to establish a connection. The management system must be added to the DirectAccess management servers list to allow it to connect to DirectAccess clients where the user has not yet logged on.

Open the Remote Access Management console, highlight **DirectAccess and VPN**, then go to **Step 3** and click **Edit**. Click **Management** and then double-click a blank field. Enter the Fully-Qualified Domain Name (FQDN) of the management workstation or server. Click **OK** and then **Finish** (Figure 13-7).

S Add a	Management Server		×
Specif	y the computer name or IPv4 address:		
Co	omputer name (FQDN):		
	sccm01.lab.richardhicks.net		
	Example: engineeringcomputer1.contoso.com		
O IP	v4 address		
	Example:		
	157.60.79.2		
		ОК	Cancel

Figure 13-7. Add a management server

⁴https://www.youtube.com/watch?v=T6ylfFi-5bQ

Alternatively, a system can be added to the management servers list by opening an elevated PowerShell command window and enter the following command:

Add-DAMgmtServer -MgmtServer [management server FQDN]

Windows Firewall

DirectAccess clients that are outside of the network have either the Public or Private Windows firewall profile enabled. These profiles are more restrictive than the Domain profile and often prevent remote-management tools from working correctly. To resolve this, a GPO will be created to configure the Windows firewall on DirectAccess clients to securely allow remote communication only from the DirectAccess management workstations and servers on the internal network.

GPO

Open the Group Policy Management console, right-click **Group Policy Objects**, and choose **New**. Enter a descriptive name for the new GPO and click **OK**. Right-click the new GPO and choose **Edit**. Expand **Computer Configuration**, **Policies**, **Windows Settings**, **Security Settings**, and **Windows Firewall with Advanced Security**. Right-click **Inbound Rules** and choose **New Rule**. As an example, if RDP is to be allowed, select **Predefined** and choose **Remote Desktop** from the drop-down list, then click **Next** (Figure 13-8).

2	New Inbound Rule Wizard	
Rule Type Select the type of firewall rule to c	zeate.	
Steps: Predefined Rules Action	What type of rule would you like to create? Program Rule that controls connections for a program. Prot Rule that controls connections for a TCP or UDP port. Predefined: Remote Desktop Rule that controls connections for a Windows experience. Outstom Ustom rule.	

Figure 13-8. Choose the predefined Remote Desktop rule

Select the Remote Desktop - User Mode (TCP-In) rule and click Next (Figure 13-9).

2	New Inbound Rule Wizard						
Predefined Rules Select the rules to be created for	this experience.						
Steps: Prule Type Predefined Rules Action	Which rules would you like to create? The following rules define network connectivity requirements for the selected predefined group. Rules that are checked will be created. If a rule already exists and is checked, the contents of the existing rule will be overwritten.						
	Name Remote Desktop - Shadow (TCP-In) Remote Desktop - User Mode (UDP-In) Image: Comparison of the state of the	Rule Exists No No No	Profile All All All	Desc Inbou Inbou Inbou			
		< Back	Next >	Cancel			

Figure 13-9. Choose the firewall rules to create

Choose Allow the connection and click Finish (Figure 13-10).

New Inbound Rule Wizard	x
en a connection matches the conditions specified in the rule.	
What action should be taken when a connection matches the specified conditions?	
 What action should be taken when a connection matches the specified conditions? Allow the connection This includes connections that are protected with IPsec as well as those are not. Allow the connection if it is secure This includes only connections that have been authenticated by using IPsec. Connections will be secured using the settings in IPsec properties and rules in the Connection Security Rule node. Customize Block the connection 	
< Back Finish Cancel	
	en a connection matches the conditions specified in the nule. what action should be taken when a connection matches the specified conditions? • Alow the connection This includes connections that are protected with IPsec as well as those are not. • Alow the connection if it is secure This includes only connections that have been authenticated by using IPsec. Connections sule secured using the settings in IPsec properties and rules in the Connection Security rule node. Customize Back the connection

Figure 13-10. Choose the rule action

Right-click the **Remote Desktop - User Mode (TCP-In)** rule and choose **Properties**. Select the **Advanced** tab and then uncheck **Domain** (Figure 13-11).

F	Remote	Desktop	- Shadow	(TCP	-In) Prope	erties ×
Genera	al	Program	s and Services		Remote	Computers
Protocols a	and Ports	Scope	Advanced	Loca	l Principals	Remote Users
Profiles	Profiles Specify profiles to which this rule applies. Domain Private Public Interface types Specify the interface types to which this Customize					
Edge tra	eversal Edge trav inbound p such as a firewall.	ersal allows ackets that Network A	the computer t thave passed t ddress Translat	to acce hrough ion (N	ept unsolicited an edge der AT) router or	d vice
	Defer to	application			~	ן ו
	Let each traffic fro	application m the Interr	determine whe net through a N	ther to AT edg	allow unsolic ge device.	ited
			ОК		Cancel	Apply

Figure 13-11. Uncheck the Domain profile

Select the **Scope** tab and select **These IP addresses**. Click **Add** and enter the organization's ISATAP IPv6 prefix, then click **OK** twice (Figure 13-12).

	IP Address	x
Specify the IP	addresses to match:	
This IP ad	dress or subnet:	
2002:cb0	0:71f0:1:0:5efe::/96	
Examples:	192.168.0.12 192.168.1.0/24 2002:9d3b:1a31:4:208:74ff.fe39:6c43 2002:9d3b:1a31:4:208:74ff.fe39:0/112	
O This IP ad	dress range:	
From:]
To:		
	set of computers:	
Default ga	steway 🗸	-
	OK Cancel	

Figure 13-12. Enter the organziation's ISATAP IPv6 prefix

Note The ISATAP prefix is the first 96 bits of the IPv6 address assigned to the ISATAP tunnel adapter on the DirectAccess server.

Finally, link this GPO to the domain and use security filtering to apply it only to DirectAccess client computers. Alternatively, link the GPO to an OU that includes DirectAccess client computers.

Additional Services

The steps outlined previously to allow RDP can also be used to deploy additional firewall rules for other management services. Common WFAS rules to allow remote systems management for DirectAccess clients using popular Windows management tools include the following:

- COM+ Network Access (DCOM-In)
- COM+ Remote Administration (DCOM-In)
- File and Printer Sharing (Echo Request ICMPv6-In)
- File and Printer Sharing (SMB-In)
- Performance Logs and Alerts (DCOM-In)
- Performance Logs and Alerts (TCP-In)

- Remote Desktop User Mode (TCP-In)
- Remote Event Log Management (NP-In)
- Remote Event Log Management (RPC)
- Remote Event Log Management (RPC-EPMAP)
- Remote Scheduled Tasks Management (RPC)
- Remote Scheduled Tasks Management (RPC-EPMAP)
- Remote Service Management (NP-In)
- Remote Service Management (RPC)
- Remote Service Management (RPC-EPMAP)
- Remote Volume Management Virtual Disk Service (RPC)
- Remote Volume Management Virtual Disk Service Loader (RPC)
- Remote Volume Management (RPC-EPMAP)
- Windows Firewall Remote Management (RPC)
- Windows Firewall Remote Management (RPC-EPMAP)
- Windows Remote Management (HTTP-In)

Summary

Configuring DirectAccess for managing out allows administrators to realize the full potential of the DirectAccess solution. Using the same familiar administration tools and procedures, remote DirectAccess clients can be managed easily and effectively regardless of where they are. Managing out enables compelling uses cases, such as remote help desk support, proactive software and configuration installation, proactive vulnerability scans, and much more.

The best way to take advantage of DirectAccess' managing-out capabilities is to deploy IPv6 on the corporate network. If IPv6 is not yet deployed, the ISATAP IPv6 transition technology can be used in the interim.

APPENDIX A

DirectAccess with Native IPv6

Throughout this book, the configuration of DirectAccess assumes that IPv6 is not natively deployed on the internal network. This is the most common deployment scenario at the time of this writing.

Configuring DirectAccess differs only slightly when IPv6 is deployed natively on the internal network. The Remote Access Setup Wizard automatically detects when IPv6 is in use on the internal network and presents some additional dialog boxes during configuration.

There are some changes that must be made to internal IPv6 network routing to support DirectAccess client connections. There are also important implications for the use of IPv6 transition technologies when IPv6 has been deployed on the intranet.

A big advantage of having IPv6 deployed natively on the internal network is that managing out is fully supported in all deployment scenarios without requiring an IPv6 transition technology.

IPv6 Readiness

It is recommended that DirectAccess be installed and configured after IPv6 has been deployed on the internal network. If DirectAccess is installed and configured in an IPv4-only network, and later IPv6 is deployed, DirectAccess will continue to work without issue using IPv4. However, to enable DirectAccess clients to connect to corporate resources using their native internal IPv6 address, the configuration must be removed and reinstalled, or a parallel deployment must be configured and clients be migrated to the new deployment.

If IPv6 is not yet deployed on the internal network, but the organization has already obtained IPv6 addressing, IPv6 addresses can be assigned to the DirectAccess server prior to configuration in preparation for the eventual deployment of IPv6 internally. This will eliminate the need to rebuild the environment after IPv6 is deployed.

In this scenario, DNS64 must be configured to use IPv4 only after the initial configuration is complete. Open an elevated PowerShell command window on the DirectAccess server and enter the following command:

Set-NetDNSTransitionConfiguration -OnlySendAQuery \$True

After IPv6 has been deployed on the internal network, the DirectAccess server can be configured to return native IPv6 addresses for internal resources by entering the following PowerShell command:

```
Set-NetDNSTransitionConfiguration -OnlySendAQuery $False
```

APPENDIX A DIRECTACCESS WITH NATIVE IPV6

Remote Access Setup Wizard

On **Step 2** of the Remote Access Setup Wizard, the user interface (UI) will automatically select IPv6 addresses assigned to the Internal and External network adapters (Figure A-1).

lagence Access Setup			×
Remote Access S Configure DirectAcces	s and VPN settings.		
Network Topology Network Adapters	Select the network adapters on the Remote Access server.		
Authentication	Adapter connected to the external network: External V Details 2001:db8:2112:867:5309:1843:6572:1	Adapter connected to the internal net Internal V 2001:db8:2112:150c:79df:7ac8:c0c1:88c	work: ils :9
	Select the certificate used to authenticate IP-HTTI Use a self-signed certificate created automatic CN=*.richardhicks.net, OU=Domain Control Valic	PS connections: cally by DirectAccess dated Brow	se
	Transition technologies are enabled for IF	₽v4 support.	
		< Back Next > Finish	Cancel

Figure A-1. Network adapter selection with native IPv6

The Remote Access Setup Wizard automatically supplies the **Internal network IPv6 prefix** and the **IPv6 prefix assigned to DirectAccess client computers** based on the IPv6 address assigned to the Internal network interface of the DirectAccess server. The UI assumes a standard /48 IPv6 site prefix. In addition, the IPv6 prefix assigned to clients is designated from this same /48 prefix. These details can be updated if they do not accurately reflect internal IPv6 network prefix assignments (Figure A-2).

Sa Remote Access Setup		×	
Remote Access S Configure DirectAcces	server Setup ss and VPN settings.		
Network Topology Network Adapters Prefix Configuration	IPv6 settings displayed on this page have been detected of	on the internal network.	
Authentication	Internal network IPv6 prefixes:	2001:db8:2112::/48	
		Example: 2001:db8:ef3e::/48;2001:db8:ef3f::/48	
	IPv6 prefix assigned to DirectAccess client computers:	2001:db8:2112:1000::/64	
		< Back Next > Finish Cancel	

Figure A-2. Automatically detected IPv6 network prefixes

APPENDIX A DIRECTACCESS WITH NATIVE IPV6

When configuring DNS, the DNS server address for the Internal namespace will not be the familiar DNS64 IPv6 address ending in 3333::1. Instead, it will be the native IPv6 address assigned to the Internal network interface of the DirectAccess server (Figure A-3).

Sa Remote Access Setup				×
Configure infrastruct	Gerver Set Sure servers. I	up DirectAccess clients access these se	vers before connecting to resources on the internal network.	1
Network Location Server DNS DNS Suffix Search List Management	Enter DNS suffixes and internal DNS servers. DirectAccess client queries that match a suffix use the specified DNS server for name resolution. Name suffixes that do not have corresponding DNS servers are treated as exemptions, and DNS settings on client computers are used for name resolution.			
,,		Name Suffix	DNS Server Address	
	•	lab.richardhicks.net	2001:db8:2112:150c:79df:7ac8:c0c1:88c9	6
		nls.lab.richardhicks.net		
	Selec O L O L	t a local name resolution option: Ise local name resolution if the nam Ise local name resolution if the nam	e does not exist in DNS (most restrictive) e does not exist in DNS or DNS servers are	
	01	inreachable when the client compu Ise local name resolution for any kii	er is on a private network (recommended) nd of DNS resolution error (least restrictive)	ancel

Figure A-3. DNS server IPv6 address

Load Balancing

The default IPv6 prefix length for DirectAccess clients using the IP-HTTPS IPv6 transition technology is /64. When enabling load balancing, the administrator may encounter an error message stating **The length of the prefix used to assign IPv6 addresses to DirectAccess clients connecting over IP-HTTPS should be 59 bits** (Figure A-4).



Figure A-4. IP-HTTPS IPv6 prefix-length error message

APPENDIX A DIRECTACCESS WITH NATIVE IPV6

To resolve this issue, click **Edit** on **Step 2** in the Remote Access Management console, select **Prefix Configuration**, change the IPv6 prefix assigned to DirectAccess client computers to /**59**, and click **Next**, **Finish** twice, and then **Apply** (Figure A-5).

Sa Remote Access Setup		×	
Remote Access S Configure DirectAcce	Server Setup ss and VPN settings.		
Network Topology Network Adapters Prefix Configuration	IPv6 settings displayed on this page have been detected o	on the internal network.	
Authentication	Internal network IPv6 prefixes:	2001:db8:2112::/48	
		Example: 2001:db8:ef3e::/48;2001:db8:ef3f::/48	
	IPv6 prefix assigned to DirectAccess client computers:	2001:db8:2112:1000::/59	
		< Back Next > Finish Cancel	

Figure A-5. Change the IPv6 prefix assigned to DirectAccess client computers

Once the IP-HTTPS IPv6 prefix has been changed, enable load balancing as outlined in Chapter 6, "Configure DirectAccess Load Balancing." When IPv6 is deployed natively, the UI will prompt the administrator for new dedicated external IPv4 and IPv6 addresses (Figure A-6).

Before You Begin Load Balancing Method External DIPs	Configure dedicated IP enabled, the current pr addresses (VIPs) for the	addresses (DIPs) for the server external adapter. With load balancing imary DIPs of the network adapters will be used as the virtual IP e load balanced cluster.
Internal DIPs	IPv4 address:	203.0.113.241
		Example: 203.0.113.18
Completion	Subnet mask:	255.255.255.0
		Example: 255.255.0.0
	IPv6 address:	2001:db8:2112:150c::da1
		Example: 2001:db8:f::7
	Subnet prefix length:	64
		Example: 64
	203.0.113.242	will also be used as a dedicated IP address (DIP).

Figure A-6. Configure the external dedicated IPv4 and IPv6 addresses

Note It is not necessary to change the internal IPv6 address of the DirectAccess server when enabling load balancing. Only the dedicated IPv4 address will be changed.

Multisite

When adding an entry point to an existing DirectAccess multisite deployment, the UI will prompt for an IPv6 prefix to be assigned to DirectAccess client computers accessing this entry point (Figure A-7).



Figure A-7. Multisite entry point IPv6 prefix assignment for DirectAccess client computers

Network Prefix Routing

The IPv6 network routing tables on the internal network must be configured to allow remote DirectAccess client connectivity. Routes must be created to forward packets that are destined for any DirectAccess client IPv6 network prefixes to the Internal network interface of the DirectAccess server. The IPv6 prefix used by remote DirectAccess clients is determined by the IPv6 transition technology used to connect to the DirectAccess server.

6to4

The use of the 6to4 IPv6 transition technology should be avoided in all DirectAccess deployments, as there are potential configuration and stability issues associated with its use.¹ However, if 6to4 is used by DirectAccess clients, the **2002::**/**16** IPv6 prefix² must be routed to the Internal network interface of the DirectAccess server.

Note Remote clients can only access the internal network using 6to4 when DirectAccess is deployed in a single-server, single-site configuration. 6to4 should not be used by DirectAccess clients when load balancing is configured or multisite is enabled.

Teredo

Teredo addresses are derived from the **2001::**/**32** prefix, with the next 32 bits representing the DirectAccess server's primary external IPv4 address.³ For example, a client connecting to a DirectAccess server with a primary IPv4 address of **203.0.113.240** will use a Teredo IPv6 prefix of **2001:0:cb00:71f0::**/**64**. This IPv6 prefix must be routed to the Internal network interface of the DirectAccess server.

Note Remote clients can only access the internal network using Teredo when DirectAccess is deployed in a single server and single or multisite configuration. Teredo should not be used by DirectAccess clients when load balancing is configured, either in single or multisite deployments, unless an external load balancer capable of monitoring DirectAccess connection flows is implemented.

IP-HTTPS

IP-HTTPS addresses are derived from the IPv6 prefix that is defined during DirectAccess server configuration (Figure A-2). This prefix must be routed to the Internal network interface of the DirectAccess server.

^{&#}x27;https://directaccess.richardhicks.com/2015/02/02/disable-6to4-ipv6-transition-protocol-fordirectaccess-clients/

²https://en.wikipedia.org/wiki/6to4#Address_block_allocation

³https://en.wikipedia.org/wiki/Teredo_tunneling#IPv6_addressing

APPENDIX A DIRECTACCESS WITH NATIVE IPV6

When load balancing is enabled, a /59 IPv6 prefix derived from the original /48 site prefix is designated for the cluster. Each cluster member then uses a /64 prefix for DirectAccess client address assignment. The individual /64 IPv6 prefixes for each DirectAccess server in the cluster must be routed to their corresponding Internal network interfaces. The /59 entry-point prefix can be found by highlighting DirectAccess and VPN in the Remote Access Management console and highlighting an individual entry point (Figure A-8).

Entry Point Configuration Summary			
Entry point configuration:			
Entry point name: US West			
IP-HTTPS address:	da.richardhicks.net		
Prefix assigned to clients connecting over IP-HTTPS:	2001:db8:2112:1000::/59		
Server GPO:	lab.richardhicks.net\DirectAccess Server Settings		
Configure Entry Point Settings			

Figure A-8. IPv6 prefix assigned to clients connecting over IP-HTTPS HTTPS

Native IPv6 HTTPS

When the DirectAccess server is configured with a Global Unicast Address (GUA) IPv6 address assigned to its External interface and it is accessed by a DirectAccess client that also has a GUA IPv6 address, the client will not be able to establish a remote connection to internal resources unless the DirectAccess server is configured as the IPv6 default gateway on the internal network.

Note Configuring the DirectAccess server as the IPv6 default gateway for the internal network is not an ideal solution in most cases. For this reason, it is recommended that the DirectAccess server not be configured with a GUA IPv6 address on its External network interface.

Managing Out

Managing out is supported in all deployment scenarios, including load-balanced and multisite configurations, without the need for a transition technology when IPv6 is natively deployed on the internal network. Managing out using native IPv6 requires the configuration of network prefix routing as described previously in this chapter.

Summary

DirectAccess implementations where IPv6 is natively deployed on the internal network are not yet common. However, there are only a few subtle differences when configuring DirectAccess when IPv6 is in use. When IPv6 is deployed on the intranet, careful attention must be paid to the internal IPv6 routing infrastructure to ensure that all IPv6 packets destined for DirectAccess client networks are forwarded to the appropriate DirectAccess server as necessary.

In addition, having IPv6 deployed natively allows for full support of outbound management capabilities in all DirectAccess deployment scenarios, including load-balanced and multisite configurations.

APPENDIX B

DirectAccess and Force Tunneling

DirectAccess clients use split tunneling in the default configuration, enabling them to access the Internet directly while at the same time being connected to the corporate network. This configuration is efficient, but it introduces some potential security risks that can be mitigated by enabling force tunneling.

How It Works

With force tunneling enabled, the Name Resolution Policy Table (NRPT) is configured to send DNS requests for all namespaces to the DNS64 service on the DirectAccess server. This differs fundamentally from split tunneling, where the NRPT is configured to only send DNS requests for the Internal namespace to the DNS64 service.

When configured, the end result is that all network access for connected DirectAccess clients is sent over the DirectAccess connection, including requests for both internal and public resources.

Use Cases

Force tunneling is often enabled to address the following security challenges.

Web-Browsing Policy

The most common use case for enabling force tunneling is to enforce access-control policies for web browsing on connected DirectAccess clients. This ensures that DirectAccess clients are protected from accessing non-approved websites regardless of whether they are inside or outside the network.

Network Bridging

Commonly, force tunneling is enabled to prevent packets from being routed from the Internet through the DirectAccess client to the corporate network. This is more of a perceived risk than an actual one. Unlike traditional client-based VPN, DirectAccess IPsec connections use AuthIP, so each packet transmitted over the DirectAccess connection is authenticated. Even if it were somehow possible to bridge the Internet and DirectAccess connections, these packets would be dropped because they are not properly authenticated.

Prerequisites

An internal web proxy server must be deployed to support force tunneling for DirectAccess clients. In addition, IP-HTTPS is the only supported IPv6 transition technology in this scenario. It is recommended that all other IPv6 transition technologies be disabled on the client.¹

Enable Force Tunneling

To enable force tunneling, open the Remote Access Management console, highlight **DirectAccess and VPN**, and then click **Edit** on **Step 1**. Click **Select Groups** and select the option to **Use force tunneling**. Click **Next** and then click **Finish** twice (Figure B-1).

Sa Remote Access Setup	×
DirectAccess Clien Enable DirectAccess for r	t Setup managed computers in specified security groups, and configure client settings.
Deployment Scenario Select Groups Network Connectivity Assistant	Select one or more security groups containing client computers that will be enabled for DirectAccess. Image: Clients (LAB\DirectAccessClients) Add Image: Clients (LAB\DirectAccessClients) Add Image: Clients (LAB\DirectAccessClients) Remove Image: Clients (LAB\DirectAccess Clients) Remove Image: Clients (LAB\DirectAccess Clients) Remove Image: Clients (LAB\DirectAccess for mobile computers only) Remove With this setting enabled, all mobile computers in the specified security groups will be enabled as DirectAccess clients. Image: Clients clients Image: Clients clients Image: Clients clients Image: Clients clients clients Image: Clients clients connect to the internal network and to the Internet via the Remote Access server. Image: Clients
	< Back Next > Finish Cancel

Figure B-1. Enable force tunneling

¹https://directaccess.richardhicks.com/2013/08/27/disabling-unused-ipv6-transitiontechnologies-for-directaccess-clients/

Alternatively, force tunneling can be enabled by opening an elevated PowerShell command window on the DirectAccess server and entering the following command:

Set-DAClient -ForceTunnel Enabled

Name Resolution Policy Table

Enabling force tunneling automatically configures the NRPT to direct name-resolution requests for all namespaces to the DNS64 service running on the DirectAccess server. The DirectAccess server's public hostname and the Network Location Server (NLS) are automatically excluded (Figure B-2).

Sa Remote Access Setup				×
Infrastructure S Configure infrastruc	Server Set ture servers.	up DirectAccess clients access these ser	vers before connecting to resources on the internal network.	1
Network Location Server DNS DNS Suffix Search List Management	Enter DNS suffixes and internal DNS servers. DirectAccess client queries that match a suffix use the specified DNS server for name resolution. Name suffixes that do not have corresponding DNS servers are treated as exemptions, and DNS settings on client computers are used for name resolution.			
-		Name Suffix	DNS Server Address	
	•	<any suffix=""></any>	2002:cb00:71f0:3333::1	
		da.richardhicks.net		
		nls.lab.richardhicks.net		
		ct a local name resolution option: Jse local name resolution if the nam Jse local name resolution if the nam Inreachable when the client compu Jse local name resolution for any kir	e does not exist in DNS (most restrictive) e does not exist in DNS or DNS servers are er is on a private network (recommended) id of DNS resolution error (least restrictive)	
			< Back Next > Finish	Cancel

Figure B-2. Force tunneling DNS server configuration

Define Corporate Proxy

To define a proxy server to be used by DirectAccess clients, open an elevated PowerShell command window on the DirectAccess server and enter the following command:

```
Get-DnsClientNrptRule -GpoName [DirectAccess client settings GPO name]
```

When using the default name of the DirectAccess client settings GPO created when installing DirectAccess, the command would look like this:

Get-DnsClientNrptRule -GpoName "DirectAccess Client Settings" | Where-Object Namespace -eq "." | Select-Object Name

Note the name of the NRPT rule for the namespace "" in the output of the previous command. Enter it along with the name and port of the proxy server in the following PowerShell command:

Set-DnsClientNrptRule -DAEnable \$True -DAProxyServerName [proxy server name:port]
-DAProxyType "UseProxyName" -Name [NRPT rule name] -GpoName [DirectAccess client settings
GPO name]

For example, using the proxy server name proxy.lab.richardhicks.net on port 8080, the command would look like this:

```
Set-DnsClientNrptRule -DAEnable $true -DAProxyServerName "proxy.lab.richardhicks.net:8080"
-DAProxyType "UseProxyName" -Name "DA-{3ee344b4-b7c3-4cd7-a91f-b0182ca07f34}" -GpoName
"DirectAccess Client Settings"
```

Note The option to define a proxy server when force tunneling is enabled is not available in the Remote Access Management console. It must be performed using PowerShell.

Limitations and Drawbacks

Force tunneling brings with it some limitations and potential drawbacks. The following should be considered carefully when choosing to enable force tunneling.

Poor Performance

Many public Internet sites today already use encryption. Tunneling encrypted traffic inside the IPsecencrypted DirectAccess connection increases CPU utilization on both the client and the server. Crucially, the added protocol overhead caused by double encryption introduces additional network latency that often results in a degraded user experience.

This becomes exponentially worse when supporting Windows 7 DirectAccess clients that are connecting with the IP-HTTPS IPv6 transition technology. Windows 7 clients use only encrypted cipher suites when establishing an IP-HTTPS transition tunnel, resulting in *triple* encryption when accessing encrypted resources on the Internet.

Reduced Scalability

Force tunneling increases CPU utilization on the DirectAccess server. In addition, the amount of network traffic processed by the DirectAccess server negatively impacts scalability, resulting in far fewer concurrent connections being supported by a single server.

Web-Browsing Experience

Much of the content accessed on the Internet today is served via Content Delivery Networks (CDNs), which are geographically distributed to ensure content is delivered from locations nearest to the client. Force tunneling can disrupt proper CDN functionality, as Internet requests will appear to come from the location of the proxy server, not the actual location of the DirectAccess client. Content may be served from suboptimal locations, resulting in further degraded performance. Further, geography-specific content (for example, local news or weather, or time-zone-specific information) may not be delivered correctly.

In addition, DirectAccess clients communicate with the DirectAccess server using IPv6 exclusively. Requests for any Internet resources by an IPv4 address will fail.

Force Tunneling and OTP

Force tunneling prevents the operation of one-time password (OTP) strong user authentication. These two configurations are mutually exclusive and cannot be enabled at the same time.

All or Nothing

Enabling force tunneling is an all or nothing choice. There are no supported options for whitelisting specific websites to be excluded from the force-tunneling requirement. When this option is selected, all client traffic is forced back over the DirectAccess connection. This is especially challenging for Voice over IP (VoIP) software such as Skype for Business (SFB). The added latency introduced often degrades call and video quality for remote users.

Summary

Force tunneling can be enabled for DirectAccess clients in order to address some of the security challenges imposed by split tunneling. However, there are some serious limitations and potentially negative side effects to implementing this change.

A more effective alternative to enabling force tunneling is to use the remote filtering capabilities of an existing on-premise firewall or web proxy server. Also, there are some excellent web-based security solutions for controlling Internet access for DirectAccess clients. Leveraging these will provide additional security for remote clients, while at the same time reducing the demands on the DirectAccess infrastructure. It will also provide a much better overall user experience for clients accessing Internet resources when connected via DirectAccess.

APPENDIX C

DirectAccess Security Hardening

The DirectAccess server is an access gateway by which remote users can access resources on the internal network. As such, it makes an appealing target for attackers. It is vital that the DirectAccess server is properly secured to ensure that it is not compromised.

In addition to common security implementation best practices, careful attention should be given to some of the default settings for the IP-HTTPS IPv6 transition technology, the SSL/TLS configuration, and the Windows firewall. Service hardening and attack-surface reduction can also be performed to further improve overall system security.

Security Best Practices

The DirectAccess server should be configured using industry standard security best practices,¹ which include removing or disabling any unneeded roles or features and disabling unused services. In addition, following security administration best practices and securing administrative workstations² is encouraged.

IP-HTTPS Preauthentication

When a client establishes a connection to the DirectAccess server using the IPv6 transition technology, the client authenticates the server, but the server does not authenticate the client. This is by design, as the transition tunnel was never meant to be a security enforcement point. That job is capably left to IPsec.

The default configuration for IP-HTTPS leaves open the potential for an unauthorized client to establish an IP-HTTPS connection to the DirectAccess server, allowing it to obtain an IPv6 address using the standard IPv6 Neighbor Discovery³ process. This exposes the server and clients to possible IPv6 denial-of-service (DoS) attacks.⁴

Enabling IP-HTTPS preauthentication can mitigate this risk. The most effective way to do this is with an application delivery controller (ADC)^{5,6}. If a suitable ADC is not available, IP-HTTPS preauthentication can be enabled on the IP-HTTPS listener itself.

https://technet.microsoft.com/en-us/library/dd277328.aspx

²https://blogs.technet.microsoft.com/askpfeplat/2016/03/14/secure-administrative-workstations/ ³https://en.wikipedia.org/wiki/Neighbor_Discovery_Protocol

⁴https://www.ernw.de/download/newsletter/ERNW_Newsletter_53_MS_DA_Security_Assessment_Signed.pdf 5https://directaccess.richardhicks.com/2016/05/10/directaccess-ip-https-preauthentication-usingcitrix-netscaler/

[%]https://directaccess.richardhicks.com/2016/05/23/directaccess-ip-https-preauthentication-usingf5-big-ip/

To enable IP-HTTPS preauthentication, open an elevated PowerShell command window on the DirectAccess server and enter the following command:

netsh http show sslcert

Note the certificate hash of the SSL certificate assigned to the IP-HTTPS listener and provide it when entering the following commands:

```
netsh http delete sslcert ipport=0.0.0.0:443
netsh http add sslcert ipport=0.0.0.0:443 certhash=[certificate_hash] appid={5d8e2743-ef20-
4d38-8751-7e400f200e65} clientcertnegotiation=enable dsmapperusage=enable
```

Note The previous steps must be performed on each DirectAccess server in load-balanced or multisite deployments.

Once IP-HTTPS preauthentication is enabled, only clients with a certificate issued by the internal PKI will be able to establish an IP-HTTPS connection to the DirectAccess server.

Note Using IP-HTTPS preauthentication requires the deployment of computer certificates to all DirectAccess clients. However, certificate authentication for IPsec is optional. Preauthentication can still be performed in scenarios where the Kerberos Proxy is used.

Windows Firewall

For edge-facing and perimeter/DMZ deployments, where the DirectAccess server is configured with two network interfaces, configuration of the Windows firewall is crucial. Performing a port scan of the DirectAccess server's External network interface in the default configuration commonly indicates critical Transmission Control Protocol (TCP) ports left open and exposed to the Internet, including Remote Procedure Call (RPC - TCP port 135) and Server Message Block (SMB - TCP port 445) (Figure C-1).



Figure C-1. DirectAccess server external network port scan

To remediate this exposure, remove the Public firewall profile from all firewall rules in the following firewall groups:

- Remote Access
- File and Printer Sharing
- Windows Remote Management
- World Wide Web Services (HTTP)
- Secure World Wide Web Services (HTTPS)

Alternatively, open an elevated PowerShell command window on the DirectAccess server and enter the following commands:

```
Set-NetFirewallRule -DisplayGroup "Remote Access" -Profile Public -Enabled False
Set-NetFirewallRule -DisplayGroup "File and Printer Sharing" -Profile Public -Enabled False
Set-NetFirewallRule -DisplayGroup "Windows Remote Management" -Profile Public -Enabled False
Set-NetFirewallRule -DisplayGroup "World Wide Web Services (HTTP)" -Profile Public -Enabled
False
Set-NetFirewallRule -DisplayGroup "Secure World Wide Web Services (HTTPS)" -Profile Public
-Enabled False
```

Note These steps must be performed on each DirectAccess server in load-balanced or multisite deployments.

Considerations for ICMP

Ping with Internet Control Message Protocol (ICMP) echo requests can be helpful for troubleshooting network connectivity, especially for DirectAccess deployments. However, the default security posture of DirectAccess exempts ICMP from IPsec policy processing. As such, it might be possible for an unauthorized user to perform network reconnaissance of hosts on the internal network that accept and respond to ICMP echo requests.

The only way to effectively mitigate this risk is to implement IP-HTTPS preauthentication as outlined previously.

SSL/TLS

The IP-HTTPS IPv6 transition technology relies on Secure Sockets Layer (SSL) and Transport Layer Security (TLS) for authentication and encryption for DirectAccess clients. SSL v3⁷ is enabled by default on the DirectAccess server. In addition, the default configuration supports RC4 cipher suites.⁸ For the highest level of security and protection, SSL v3 and RC4 cipher suites should be disabled.

To disable SSL v3, open the registry editor (regedit.exe) on the DirectAccess server and navigate to **HKLM\SYSTEM\CurrentControlSet\Control\SecurityProviders\SCHANNEL\Protocols\SSL 3.0\Server**; set the DWORD value of **Enabled** to **0**.

Note Create this registry key and value if it does not already exist.

To disable support for SSL and TLS cipher suites that use RC4, navigate to **HKLM\SYSTEM\ CurrentControlSet\Control\SecurityProviders\SCHANNEL\Ciphers** and set the DWORD value of **Enabled** to **0** in each of the following registry keys:

- RC 128/128
- RC4 40/128
- RC4 56/128

The following is a script to disable SSL v3 and RC4 cipher suites. Open an elevated PowerShell command window on the DirectAccess server and enter the following commands:

```
# // Disable SSL v3
New-Item -Path "HKLM:\SYSTEM\CurrentControlSet\Control\SecurityProviders\SCHANNEL\Protocols\
SSL 3.0\Server" -Force
```

New-ItemProperty -Path "HKLM:\SYSTEM\CurrentControlSet\Control\SecurityProviders\SCHANNEL\ Protocols\SSL 3.0\Server" -PropertyType dword -Value 0 -Name Enabled

```
# // Disable RC4 Cipher Suites
$writable = $true
$key = (get-item HKLM:\SYSTEM\CurrentControlSet\Control\SecurityProviders\SCHANNEL\).
OpenSubKey("Ciphers", $writable).CreateSubKey("RC4 128/128")
$key.SetValue("Enabled", "0", "DWORD")
```

⁷https://blog.qualys.com/ssllabs/2014/10/15/ssl-3-is-dead-killed-by-the-poodle-attack ⁸https://blog.qualys.com/ssllabs/2013/03/19/rc4-in-tls-is-broken-now-what

```
$key = (get-item HKLM:\SYSTEM\CurrentControlSet\Control\SecurityProviders\SCHANNEL\).
OpenSubKey("Ciphers", $writable).CreateSubKey("RC4 56/128")
$key.SetValue("Enabled", "0", "DWORD")
```

```
$key = (get-item HKLM:\SYSTEM\CurrentControlSet\Control\SecurityProviders\SCHANNEL\).
OpenSubKey("Ciphers", $writable).CreateSubKey("RC4 40/128")
$key.SetValue("Enabled", "0", "DWORD")
```

Note Repeat these steps on each DirectAccess server in the load-balanced cluster and/or multisite deployment.

Null Cipher Suites

DirectAccess includes support for null-encrypted cipher suites. They are used by Windows 8.x and Windows 10 clients when using the IP-HTTPS IPv6 transition technology to connect to the DirectAccess server. The use of null-encrypted cipher suites is an important scalability and performance feature. It prevents the needless double encryption of DirectAccess communication.

Disabling support for null cipher suites should be avoided, as this provides no additional security benefits. Unlike SSL/TLS-based VPN or a web server, the DirectAccess workload is unique in that the payload is already encrypted. Encrypting it again serves no purpose. Removing support for null-encrypted cipher suites only reduces the overall scalability and performance of the solution.

Server Core

To provide the highest level of security for the DirectAccess server, it is recommended that the Server Core deployment mode be used. Server Core is a refactored installation option for Windows Server 2016 that does not include a graphical user interface (UI) or any Windows Shell components. Not only does this configuration drastically reduce the attack surface of the server, but it also reduces servicing requirements and disk space usage and speeds up system start-up times.

When a server is deployed using Server Core, it must be managed exclusively from the command line. Often it is easier to perform the initial installation, configuration, and testing with the full GUI installed. Once DirectAccess has been configured and tested, then the GUI can be removed prior to placing the server into production.

To convert a full GUI installation to Server Core, open an elevated PowerShell command window on the DirectAccess server and enter the following command:

Uninstall-WindowsFeature Server-Gui-Mgmt-Infra

Once complete, the server can only be managed locally via the command line using PowerShell, netsh. exe, or native operating system commands.

To manage the DirectAccess server remotely using either PowerShell or the Remote Access Management console, install the Remote Access Management Tools role on another Windows Server 2016 or 2012 R2 server by opening an elevated PowerShell command window and entering the following command:

Install-WindowsFeature RSAT-RemoteAccess -IncludeAllSubFeature
Note The DirectAccess server can be managed from a Windows 10 workstation by installing the Remote Server Administration Tools (RSAT), found here: https://www.microsoft.com/en-us/download/details.aspx?id=45520

Minimal Server Interface

An alternative to using Server Core is to configure the Minimal Server Interface. This is an installation mode that provides some of the benefits of Server Core but retains some of the familiar GUI management tools, such as the Remote Access Management console. To convert a full GUI installation to the Minimal Server Interface, open an elevated PowerShell command window on the DirectAccess server and enter the following command:

Uninstall-WindowsFeature Server-Gui-Shell

Summary

DirectAccess is a secure remote-access solution out of the box, but it can benefit from some additional security-hardening steps to further ensure the highest level of protection.

The default security posture can be improved by performing IP-HTTPS preauthentication and making some adjustments to the Windows firewall. The SSL/TLS configuration can be altered to mitigate potential security challenges, and the attack surface can be reduced significantly with the use of the Server Core configuration.

Index

A

Accounting inbox, 185-186 RADIUS, 186-187 Active Directory additional GPOs, 16 administrative rights, 15 forest/domain functional level, 15 group policy objects, 15 requirements and configuration, 15 RODC, 15 security groups, 15 Active Directory Certificate Services (AD CS) server, 30 Active Directory Domain Services (AD DS), 9 Anti-hammering capabilities, 133 Application Delivery Controller (ADC), 17 Authenticated IP (AuthIP), 6 Azure Traffic Manager, 123

B

Bi-directional, 1

C

Certificate Authority (CA), 144 certification, 16 management console, 149 SSL certificate. 36 Certificate Revocation List (CRL), 16, 36, 203 Certificate Signing Request (CSR), 36-38 Certification Authority (CA), 67-68, 134 Client configuration (troubleshooting) certificates, 208 domain connectivity, 208 group policy, 207-208 IPv6, 209 network connectivity, 208 operating systems, 205 control panel, security and system, 205 systeminfo.exe, 206

services, 212 transition technologies, IPv6 6to4, 209 IP-HTTPS, 210-211 teredo, 210 Windows firewall, 212-214 Client migration, 234-235 Clients, DirectAccess, 14 connectivity validation, 15 IPv6, 14 operating systems, 14 SKUs. 14 Windows Firewall, 14 Computer certificates authentication, 16 authority, 16 clients, 16 requirements, 16 SSL certificates, 16 Connection Security Rules (CSRs), 5, 10, 196 IPv6 address, 215-216 Windows firewall, 214-215 Connectivity troubleshooting connection security rules, 214, 216 internal servers, 218-219 IPsec connections, 219-220 name resolution Netsh, 221-222 NRPT, 220-221 nslookup command, 222-223 PowerShell command, 222 ping tunnel endpoints, 216-218 tools and commands client troubleshooting, 228 connection status, 223-225 connectivity assistant, 225 firewall logging, 225 IPsec auditing, 225 message analyzer, 226 Nmap, 227 tracing, 227 Content Delivery Networks (CDNs), 265

INDEX

D

DAProbeUser, 150 dedicated IP address (DIP), 91 Denial-of-service (DoS), 267 DirectAccess bi-directional, 1 client operating systems, 5 evolution of, 3 challenges, 4 Forefront UAG, 4 Windows Server 2012, 4 Windows Server 2012 R2, 4 Windows Server 2016, 4 IPv6 6to4, 2 **IP-HTTPS**, 2 network topology, 3 outbound management, 2 Teredo, 2 transition technologies, 2 translation components, 3 limitations and drawbacks, 7 meaning, 7 not a protocol, 2 seamless and transparent, 1 security, 6 vs. VPN, 7-8 work process, 5 DirectAccess Connectivity Assistant (DCA), 61, 134-135 connectivity status, 169-170 connectivity troubleshooting, 225 diagnostics advance usage, 170 .cab file, 171-172 log file directory, 170-171 GPO (see Group Policy Object (GPO)) installation, 168 local DNS resolution, 172 operation, 169 restart, 169 v2.0, 160 **Directory Certificate** Services (AD CS), 9 Domain Name System (DNS) configuration, 71 external, 18 DNS64 service, 3, 72 internal. 17 local name-resolution, 73 multisite, 105 server addresses, 72 suffix search list, 73-74

E

Edge-facing deployments, 22 Encryption keys, 133 Enhanced Key Usage (EKU), 16, 30 External load balancer (ELB), 83–84 configuration, 101 method selection, 99–100 VIP assignment, 10–11, 100

E F

File Replication Service (FRS), 15 Force tunneling, 261 corporate proxy definition, 263-264 enable force tunneling, 262 limitation and drawbacks all/nothing choice, 265 OTP. 265 poor performance, 264 reduced scalability, 264 web-browsing experience, 265 name resolution policy table, 263 network bridging, 261 prerequisites, 262 web-browsing policy, 261 working process, 261 Forefront Unified Access Gateway (UAG), 4 Fully Qualified Domain Name (FQDN), 36, 47, 65

G

Geographic redundancy clients, 103 Windows 7, 103 Windows 8.x and Windows 10, 103 high availability, 103 multisite (see Multisite) outage, 103 Getting Started Wizard (GSW), 45 configuration, 45 confirm policy application, 54-55 deployment options, 46 apply settings, 48-49 DirectAccess, 47 edge, 47 GPO. 50-51 infrastructure servers, 54 installation, 47 network topology, 47-48 remote access server, 53 remote access windows, 46 remote clients, 51-52 review and edit, 49-50 VPN. 47

limitations and drawbacks, 55 client support, 56 deployment flexibility, 56 DirectAccess client target, 55 **IP-HTTPS certificate**, 56 network location server, 56 operations status window, 54-55 running, 46 Global Server Load Balancer (GSLB), 104, 123, 159 configuration, 124 deployment scenarios, 123 active/passive failover, 124 geolocation, 124 weighted distribution, 124 entry point table, 131 operation, 130-131 post-deployment entry point configuration, 128 global load balancing configuration, 125-126 IP address, 129 summary, 126-127, 129-130 syntax, 130 tasks pane, 124-125 Global Unicast Address (GUA), 209, 260 Graphical User Interface (GUI), 21, 40, 45 installation selections, 43 RAS role service, 41-42 remote access server role, 40 Group Policy Management Console (GPMC), 161 Group Policy Object (GPO), 7, 15, 34, 111-112, 160, 232 client configuration, 207 deployment, 167-168 DNS entry, 239 ISATAP state, 241 object creation admin script, 165-166 DTEs configuration, 163 email address, 162 enable local name resolution, 163-164 GPO, 161 internal web resource, 165 Organizational Unit (OU), 241 router name, 240 server configuration, 196-197 templates, 161 Windows firewall, 244 action section, 245-246 ISATAP IPv6 prefix, 247-248 profile checking, 246-247 remote desktop rule, 244 rules creation. 245 WMI filter, 166-167

H

Hyper-V virtual switches, 88-89

🛛 I, J

Inbox accounting, 185-186 Infrastructure servers, 54 Infrastructure tunnel, 6 Internet Information Services (IIS), 36 Intranet tunnel, 6 Intrasite Automatic Tunnel Addressing Protocol (ISATAP), 2, 19, 237 client connectivity testing, 241-242 DNS, 238-239 group policy, 239-241 manual configuration, 238 remote management, 243 router supports, 237 IP-HTTPS, 160 IPv6, 2 network prefix routing, 259-260 pre-authentication, 267 IPsec auditing, 225 IPv6, 251 6to4.2 advantage, 251 clients. 14 Denial-of-Service (DoS), 6 **IP-HTTPS**, 2 load balancing client computer, 256 IPv4 addresses, 257 length error message, 255 managing out, 237, 260 multisite, 258 network prefix routing 6to4.259 IP-HTTPS, 259-260 native IPv6, 260 teredo, 259 network topology, 3 outbound management, 2 readiness, 251 remote access setup wizard DNS server address. 254 network adapter selection, 252 prefix configuration, 253 server, 10 Teredo, 2 transition technologies, 2 translation components, 3

INDEX

K

Kerberos Proxy, 134

L

Link Local Multicast Name Resolution (LLMNR), 73 Load balancing capacity planning, 85 definition, 85 DirectAccess servers add/remove servers, 98-99 network adapter and IP-HTTPS, 98 selection, 96-97 external load balancer (ELB), 84 configuration, 101 method selection, 99-100 VIP assignment, 100 IPv6 client computer, 256 IPv4 addresses, 257 length error message, 255 Windows NLB (see Network Load Balancing (NLB))

M

Manage-out function bidirectional, 237 IPv6, 237 ISATAP, 19 (see also Intrasite Automatic Tunnel Addressing Protocol (ISATAP)) remote management, 243 supportability, 19 Windows firewall additional services, 248-249 GPO, 244-248 Message analyzer, 226 Microsoft Management Console (MMC), 36 Migration, 231 client migration, 234-235 configuration client and server, 234 public hostname, 233 unique security group, 232 configuration changes, 235 delegated administration, 235 QA and testing, 235 requirements, 231 group policy objects, 232 IP addresses, 231 public hostname, 231 unique security groups, 232 unique client requirements, 235

Minimal Server Interface, 272 Monitor. See System monitoring Multicast operating mode, 84 Multifactor Authentication (MFA), 134 Multisite Active Directory Security groups, 104 DirectAccess servers, 104 DNS, 105 entry point, 123 first entry point client GPO, 120 client support, 110-111, 119-120 commit option, 112-113 creation, 105 deployment, 106-107 details, 114-115 global load balancing, 109-110 GPO setting, 111–112 IP-HTTPS certificate, 118-119 IPv4 address, 115-116 network topology, 116-117 public hostname, 117-118 server GPO, 122 summary, 122-123 tasks pane, 113-114 Windows 8.x/10 clients, 108 GSLB (see Global Server Load Balancing (GSLB)) implementation, 104 **IP-HTTPS certificate**, 105 IPv6, 258 process enable, 105 security groups, 104 SSL certificates, 104 Windows 7 clients, 159

N

Name Resolution Policy Table (NRPT), 2, 71, 220, 261, 263 NAT64 service. 3 NetBIOS, 73 Network Access Protection (NAP) integration, 4 Network adapters, 66 Network Address Translation (NAT), 159 Network connectivity, 199 client configuration, 208 firewall profiles, 199 internal networks and services, 200 Internet, 200-202 Network Connectivity Assistant (NCA), 15, 63-64, 134, 160, 212 Network Interface Cards (NICs), 11 Network Load Balancing (NLB), 10, 83 drawbacks, 84

enable load balancing commit configuration, 93-94 external dedicated IP address, 91-92 internal dedicated IP address, 91, 93 method. 90-91 tasks pane, 89-90 feature, 85 GUI feature, 86-87 Hyper-V virtual switches, 88-89 installation selections, 87-88 operating mode multicast, 84 unicast. 84 PowerShell, 85 VMware clusters. 95 MAC address, 94 multicast cluster operation mode, 96 Network Location Server (NLS), 17, 54, 56, 69-71, 231 SSL certificate, 17 web server, 17 Network Mapper (Nmap) tool, 227 Network topology, 64-65 multisit, 116-117 nslookup command, 222-223

0

Object Identifier (OID), 16 One-time passwords (OTP), 15, 18, 160 authentication, 138 Certificate Authority, 149 certificate templates configuration compatibility tab, 138-139 extensions tab, 142 general tab, 139-140 security tab, 140-141 subject name format, 141-142 deployment expense, 157 flexibilities, 157 functionalities, 158 increased complexity, 157 scalability and performance, 158 user experience, 158 DirectAccess configuration authentication, 153-154 CA servers, 152 certificate templates, 152-153 management servers list, 154 RADIUS server, 151 two-factor authentication, 150-151

end user experience credentials, 156-157 sign-in info, 155-156 workpalce connection action, 155 force tunnelling, 265 group policy object, 165 OTP certificate templates application policies, 148-149 CA database, 147 compatability, 143 display name, 143-144 issuance requirements, 147-148 security permissions, 145 subject name format, 145-146 RADIUS OTP server, 150 solutions, 133-134 Open Systems Interconnection (OSI) model, 84

🛛 P, Q

Perimeter/DMZ deployments, 22 Personal identification number (PIN), 133 Physical and virtual server, 21 certificates, 29 computer (machine) certificate, 29 automatic enrollment, 34-36 certificate templates, 32-33 enrollment, 33-34 GPO security filtering, 36 security tab, 31-32 subject name format, 31 workstation authentication template, 30 DirectAccess-VPN role, 39 GUI. 40-43 PowerShell, 40 dual-NIC configuration, 22 external interface additional address, 25 DNS, 26 IPv4 address, subnet mask and default gateway, 24-25 LMHOSTS and NetBIOS, 27 network connection ordering, 27-28 internal interface, 22 IPv4 address, subnet mask and server, 24 network connections, 23 join domain and updates, 29 nodes configuration, 43 operating system installation, 21 single-NIC configuration, 21 SSL certificate, 36 certificate request creation, 37-38 CSR, 37 DigiCert utility window, 38-39 static routes, 28-29 third-party software, 29

INDEX

Physical smart cards, 133 Ping tunnel endpoints, 216-218 Planning and design phase (Server) domain membership, 9 edge firewall configuration, 12 edge facing, 12 LAN, 13 NAT. 13 perimeter/DMZ network, 13 geographic redundancy, 11 IPv6, 10 load balancing, 10 virtual IP addressing, 10 network topology considerations, 13 edge facing, 11 LAN, 12 perimeter/DMZ, 12 redundancy, 10 SKUs, 9 system requirements, 9 Windows Firewall, 10 PowerShell command, 40 client window, 207-208 cmdlet, 135 Get-NetFirewallProfile, 204 Get-RemoteAccessConnectionStatistics, 184 Get-RemoteAccess ConnectionStatisticsSummary, 184 Get-RemoteAccessUserActivity, 192 Resolve-DnsName, 200-201 Resolve-DNSName, 222 Test-NetConnection, 200-201 window, 199 Public Key Infrastructure (PKI), 4, 231

R

RADIUS accounting, 186-187 OTP server, 150 Read-Only Domain Controllers (RODC), 15 Redundancy. See Geographic redundancy Remote Access Dial-In User Service (RADIUS), 175 Remote Access Setup Wizard, 46, 57 configuration window, 57-58 deployment options configuration, 58 DirectAccess, 59 DirectAccess and VPN, 59 **VPN**, 59 DirectAccess adapters, 66 application servers, 81-82 authentication, 67

configuration changes, 76 confirm policy application, 80 deployment scenario, 60-61 DNS, 71-74 GPO settings, 77 groups selection, 62 infrastructure servers, 69 installation. 59 location server, 69-70 management servers, 74-75 NCA, 63-64 network topology, 64-65 PowerShell script, 79-80 remote access server, 64 remote clients, 60 step-by-step deployment wizard, 59-60 text file and configuration, 80 Remote Desktop Protocol (RDP), 243 **Remote Server Administration** Tools (RSAT), 95, 272 Reporting additional fields, 188-189 detailed client statistics. 189-190 PowerShell command, 192 remote access, 187-188 save option, 191-192 search connections, 190-191

S

Security hardening considerations, 270 **IP-HTTPS pre-authentication**, 267 Minimal Server Interface, 272 null cipher suites, 271 security best practices, 267 server core, 271 server external network port scan, 269 SSL/TLS, 270 Windows firewall, 268-269 Server Core, 271 Server Virtualization Validation Program (SVVP), 9 Skype for Business (SFB), 265 Smart cards authentication, 135 DirectAccess configuration, 135-136 end user experience, 136 PIN. 138 sign-in info, 137 workplace connection, 137 physical cards, 133 virtual cards, 133 Strong user authentication, 18 certificate server, 18 force tunneling, 18

OTP solutions, 18 RSA SecurID, 18 security groups, 18 smart cards, 18 user accounts. 18 System Center Configuration Manager (SCCM), 1, 29, 75, 169, 243 System monitoring, 175 dashboard remote access, 175-176 warning and error status, 176-177 operations status detailed error message, 178 details. 177 PowerShell command, 179 remote access client status client information and statistics, 181-182 client status, 179-180 fields adding, 180-181 PowerShell command window, 184-185 queries, 183 search option, 183

T

Teredo, 2 Threat Management Gateway (TMG), 4 Transition tunnel, 104 Troubleshooting client (see Client configuration (troubleshooting)) client connection process, 195 connectivity (see Connectivity troubleshooting) server configuration authentication, 202-203 certificates, 203 computer certificate, 203 group policy, 196-198 health, 198-199 IPv6, 203 name resolution, 202 network connectivity, 199-202 operations status, 198-199 services, 204 SSL certificate, 203 unsupported configurations, 205 Windows firewall, 203-204

Trusted Platform Module (TPM), 133 Two-factor authentication, 133 certification authority, 134 client authentication, 134 DirectAccess configuration, 135 OTP (*see* One-time passwords (OTP)) requirements, 134 smart cards, 133 authentication, 135 DirectAccess configuration, 135–136 end user experience, 136–138 Windows 7 clients, 135

U

Unicast operating mode, 84 Unified Access Gateway (UAG), 231 Unique Local Address (ULA), 210

V

Virtual IP address (VIP), 10, 165 Virtual Private Networking (VPN), 1, 7–8 Virtual smart cards, 133

🛛 W, X, Y, Z

Web Application Proxy (WAP), 9 Wildcard certificate, 105 Windows 7 clients DCA configuration (see DirectAccess Connectivity Assistant (DCA)) DCA v2.0, 160 degraded performance, 159 deployment considerations, 159 multisite deployment, 159 reduced scalability, 160 Windows 8.x and Windows 10 clients, 103 Windows firewall with Advanced Security (WFAS), 2, 10, 214 Windows Internal Database (WID), 175, 185 Windows Management Instrumentation (WMI), 160 Windows Server 2008 R2, 231 2012/2012 R2, 231 Windows Server Update Services (WSUS), 29, 75